KENNEDY®

DATA SHEET

QUALITY INDUSTRIAL TOOLING

Carbide Burrs - Cylindrical Ball Nose

- Uncoated
- Suitable for deburring and polishing of cast iron, cast steel, carbon steel, alloy steel and stainless steel up to HRC65 hardness
- Not suitable for milling large amounts of material
- Ideal for light stock removal at high rpms



Rapid cut (Cut 3):

For use on aluminium, fibreglass, plastics, hard rubber and zinc alloy

Chipbreaker (Cut 9):

For use on cast iron, carbon steel, alloy steel 50RC and 60RC

Please note:

Workpiece and tools should always be steady and well supported.
Always ensure that at least 70% of the shank length is clamped by the collet or chuck of the tool being used. Always ensure that the tool is rated to the recommended operating speed of the burr.

Head Dia. (mm)	Head Length (mm)	Cut Type	Overall Length (mm)	Shank Dia. (mm)	Order Code
3	12	Chipbreaker	40	3	KEN-210-1080K
6	12	Chipbreaker	45	3	KEN-210-1120K
6	19	Rapid Cut	50	6	KEN-210-1140K
6	18	Chipbreaker	50	6	KEN-210-1160K
8	20	Chipbreaker	65	6	KEN-210-1200K
10	20	Rapid Cut	65	6	KEN-210-1220K
10	20	Double Cut	65	6	KEN-210-1230K
10	20	Chipbreaker	65	6	KEN-210-1240K
12	25	Rapid Cut	70	6	KEN-210-1300K
12	25	Chipbreaker	70	6	KEN-210-1320K
16	25	Chipbreaker	70	6	KEN-210-1400K

© Copyright 2021 - Kennedy Tools