KENNEDY®

DATA SHEET

QUALITY INDUSTRIAL TOOLING

Carbide Burrs - Flame Shape

- Uncoated
- Suitable for deburring and polishing of cast iron, cast steel, carbon steel, alloy steel and stainless steel up to HRC65 hardness
- Not suitable for milling large amounts of material
- Ideal for light stock removal at high rpms



Rapid cut (Cut 3):

For use on aluminium, fibreglass, plastics, hard rubber and zinc alloy

Chipbreaker (Cut 9):

For use on cast iron, carbon steel, alloy steel 50RC and 60RC

Please note:

Workpiece and tools should always be steady and well supported.
Always ensure that at least 70% of the shank length is clamped by the collet or chuck of the tool being used. Always ensure that the tool is rated to the recommended operating speed of the burr.

Head Dia. (mm)	Head Length (mm)	Cut Type	Overall Length (mm)	Shank Dia. (mm)	Order Code
3	6	Chipbreaker	40	3	KEN-210-2120K
8	20	Chipbreaker	65	6	KEN-210-2160K
12	32	Chipbreaker	75	6	KEN-210-2320K
15	35	Double Cut	80	6	KEN-210-2390K
16	35	Chipbreaker	80	6	KEN-210-2400K

© Copyright 2021 - Kennedy Tools