KENNEDY®

DATA SHEET

QUALITY INDUSTRIAL TOOLING

Safety Goggles KEN-960-8130K

CONDOR

Frame, lens and elastic strap of fireproof material, wide elastic band with silicone inserts to improves stability.



Features & Benefits

- Clear polycarbonate/acetate lens
- Field of view: >40°
- Lens thickness (+/-.01):2.25mm
- Curvature: Base 5 Cylindric
- Optical class: 1
- VLT% (+/-5%): 91.2
- UV protection: 380nm
- double lens with thermal breakage technology protects against heat, fogging and impacts
- Technical treatments: Antifog PLUS and Antiscratch PLUS
- Unvented
- Suitable for foundry work
- Weight: 122g
- Variant available with quick-release claws suitable for use with different types of helmet
- RX insert available
- Category III

Standards: EN166, EN170, EN172
Frame Marking: U EN166 3 4 5 9 BT 2C-3 0068 CE
Lens Marking : 2C-1.2 U 1 BT 9 K N 0068 CE

Protection against droplets and splashes of liquids (3)
Protection against large dust particles (>0.5 um) (4)
Protection against molten metals and hot solids (9)
Protection against gases and fine dust particles (<0.5 um) (5);
Protection against high-speed particles 120 m/s - medium energy (B)
Protection against high-speed particles at extreme temperatures (T)
Resistance to surface damage by fine particles (K)
Resistance to fogging of oculars (N)

© Copyright 2020 - Kennedy Tools