Mod. 7630.B

COPOLYMER POLYPROPYLENE WATERPROOF CASE


Large cases IP67 certified. Two man lift side handles and retractable handle. Self-oiling free running wheels. Three colors available and two internal standard configurations.







METRIC MM-KG-C°




INTERNAL DIMENSIONS	
L LENGTH	765 mm
W WIDTH	485 mm
D DEPTH	305 mm
LID	60 mm
BASE	245 mm

EXTERNAL DIMENSIONS	
L LENGTH	860 mm
W WIDTH	560 mm
D DEPTH	355 mm

OTHER DATA	
WEIGHT EMPTY	13.56 Kg
WEIGHT WITH FOAM	16.39 Kg
WEIGHT WITH CUSTOM FOAM	Kg
VOLUME	113.10 lt
BUOYANCY	81.80 Kg/max
OPERATING TEMPERATURE	°C min -33 / max +90

IMPERIAL IN-LBS-F°



INTERNAL DIMENSIONS	
L LENGTH	30 1/8 in
W WIDTH	19 1/8 in
D DEPTH	12 in
LID	2 3/8 in
BASE	9 5/8 in

EXTERNAL DIMENSIONS	
L LENGTH	33 7/8 in
W WIDTH	22 1/16 in
D DEPTH	14 in

OTHER DATA	
WEIGHT EMPTY	29.89 lbs
WEIGHT WITH FOAM	36.13 lbs
WEIGHT WITH CUSTOM FOAM	lbs
VOLUME	29.85 gal
BUOYANCY	180.33 lbs/max
OPERATING TEMPERATURE	°F min -27.4 / max +194