TUSKER SCREENING – LOWVIS GREEN LV1

Description

Reinforced for extra strength and tear resistance, a dark green PVC welding screen unique to Safety First Manufacturing Co Ltd. Recommended for applications where no visibility is required, its matt finish eliminates glare. Lowvis Green gives a high performance in all welding applications and is our best selling curtain. Curtains are eyeleted on one edge as standard, but curtains can be joined by press studs or velcro fastening. Eyelets can be inserted all round if required.



Application and Advantages

- **Reinforced for extra strength and tear resistance**
- **Matt finish eliminates glare**
- **Suitable for all welding applications where no visibility is required**

Specifications

- In accordance with BS EN150.25980.2014
- Flame retardant to test method: BS5438, test 2A and 2B
- Dark green, matt finish reinforced PVC
- Cold crack - -6ºC
- Burst strength - 825MIN
- Breaking load (N/5cm) - L 340 MIN
  - T 220 MIN
- Tongue tear - L 130 MIN
  - T 220 MIN
- Resistance to flex cracking (cycles) 250,000 MIN
- Storage conditions -5ºC to +25ºC room temp
- Cleaning - Wash in mild detergent

Sizes

(Other sizes can be made to order)

6ft x 4ft
6ft x 6ft
6ft x 8ft



Properties

Weight – 340+/-7.5% g/m2
Thickness – 450 micron nominal

SPECIFICATION

The information contained in this data sheet is believed to be true and accurate at the time of printing. Any statement contained or inferred to within are an expression of opinion and presented without guarantee. It is up to the user to determine suitability of use or potential patent infringement for specific applications.