# Professional Construction site cable reel with Powerblock KC 3210 5 IP 44, 33+5 m H07BQ-F 3G2.5

For construction site use in accordance with DGUV 203-006 (formerly BGI 608) and permanent outdoor use IP 44.









MADE IN GERMANY | 5 YEARS MANUFACTURER GUARANTEE | DGUV-I 203-006 K2 | SPECIAL ROBUST | IP 44

| | |
|---|---|
| **Product number** | 9212380210 |
| **EAN** | 4007123687589 |

## DESCRIPTION

- With mobile power block and four additional sockets for handy use on scaffolding or roofs, etc.
- Powerblock with visual readiness indicator, hinged metal suspension hook and strap.
- In addition to the power block: four splash-proof socket outlets with self-closing lids.
- Professional drum with all-round roll-over protection.
- Stable on all four sides - perfect cable routing on all four sides.
- Large, sturdy folding swivel handle for effortless winding and unwinding of the cable.
- Robust carrying handles and plug garage on all four sides.
- The Rubbabren housing and drum material made of a plastic-rubber mix is extremely shock and impact resistant. For continuous use under the toughest conditions.
- Reel body cold impact resistant down to -25 °C and drum brake.
- BQ cable: acid- and oil-resistant, weather- and microbe-resistant and cold-resistant down to -40 °C.
- 5 splash-proof 230 V protective contact sockets.
- With extra robust safety plug.
- Overheating protection with indicator light in the event of overheating and overloading.
- Category 2 equipment (K2 DGUV 203-005): For use in harsh operating conditions with high mechanical, physical and chemical.

# Professional Construction site cable reel with Powerblock KC 3210 5 IP 44, 33+5 m H07BQ-F 3G2.5

For construction site use in accordance with DGUV 203-006 (formerly BGI 608) and permanent outdoor use IP 44.



**Product number** 9212380210
**EAN** 4007123687589

## TECHNICAL DATA

| | | | |
|---|---|---|---|
| **Cable quality** | PUR (polyurethane) | **Plug system socket** | Type F (Protective contact) |
| **Cable length** | 33 m + 5 m | **Plug system plug** | Type E and F (Protective contact with earth hole) |
| **Cable designation** | H07BQ-F 3G2,5 | **Max. current carrying capacity** | 16 A |
| **Cable colour** | red | **Nominal input voltage** | 230 V |
| **Reel diameter** | 320 mm | **Degree of protection (IP)** | IP44 |
| **Plug system CEE socket** | Without | | |

## PACKAGING, DIMENSIONS AND WEIGHTS

| | | | |
|---|---|---|---|
| **UP** | 1 | **Weight of product (including packaging)** | 9 kg |
| **Weight of product (without packaging)** | 8.94 kg | **Dimension LxWxH (incl. packing)** | 33 cm x 38.5 cm x 40.5 cm |
| **Dimension LxWxH (without packing)** | 29 cm x 37 cm x 37 cm | | |

## SCOPE OF DELIVERY

Professional Construction site cable reel with Powerblock KC 3210 5