juna

S3 EN ISO 20345 : 2011 SRC

PRODUCT CHARACTERISTICS

Sole injected in France

7h water-repellent leather

The+ PARADE TECHNOLOGIES

VPS SYSTEM

Supports the arch of the foot



PULL-UP LEATHER
7H DAMP
RESISTANCE



2855 BROWN | SIZE: 36 TO 47

COMPOSITION

Upper	Pull-up leather
Linning	Fabric
Toe Cap	Steel
Stay clean insole	Felt. Removable. Anti-bacterial. Anti-fungal.
Puncture proof insert	Stainless steel
Sole	Two-density polyurethane
Weight for size 37*	460g * Weight per shoe
Weight for size 42*	540g * Weight per shoe

**

Size coefficient 42	Flat		Heel	
	Standard	Parade	Standard	Parade
SRA ceramic floor / Nals (soap solution)	0,32	0,46	0,28	0,43
SRB Steel / Glycerine (oil)	0,18	0,20	0,13	0,20

SAFETY TABLE

- Toe cap (200J)
- P — Antipuncture sole
- SRC — Antislip sole **
- E — Shock-absorption
- A — Antistatic
- FO — Oil and fuel resistant shoe
- WRU — Water-repellent upper

PARADE SAS • Route de Chaudron - St-Pierre-Montlimart - 49110 Montrevault-sur-Èvre - France • Ph. +33(0) 2 41 75 32 37 • Mail: contact@parade-protection.com
Parade reserves the right to modify the product's manufacturing. ©Parade, All rights reserved. Non-contractual document. Update March 2020