# 39 - Inch short-reach combination wrenches



## Standards:

**ASME B107.100**

## Description:

- Short combination wrenches: the short handle and compact head allow for high handiness. Ideal for confined access.
- OGV® profile with 12-point ring for powerful tightening while protecting the nut. H suffix = 6-point ring.
- Ring head angled at 15°.
- Open end head angled at 15°.
- Dimensions in inches: from 1/8" to 11"16.
- Presentation: satin chrome finish.

© FACOM 2020

| | A [in] | Length L [mm] | Thickness E [mm] | Thickness E1 [mm] | Head Width B [mm] | Weight [Kg] | Hex Size [mm] |
|---|---|---|---|---|---|---|---|
| **39.1/2** | 1/2" | 141.0 | 5.8 | 8.0 | 28.0 | 0.05 | 12.0 |
| **39.1/4** | 1/4" | 90.0 | 4.1 | 5.0 | 15.0 | 0.015 | 6.0 |
| **39.1/8H** | 1/8" | 77.0 | 3.1 | 3.1 | 10.0 | 0.01 | 6.0 |
| **39.11/16** | 11/16" | 165.0 | 6.9 | 10.0 | 36.5 | 0.1 | 12.0 |
| **39.11/32** | 11/32" | 98.0 | 4.8 | 6.0 | 19.4 | 0.025 | 6.0 |
| **39.3/16H** | 3/16" | 82.0 | 3.5 | 4.0 | 11.8 | 0.01 | 6.0 |
| **39.3/8** | 3/8" | 103.0 | 5.1 | 6.4 | 21.5 | 0.03 | 6.0 |
| **39.5/16** | 5/16" | 94.0 | 4.5 | 5.8 | 17.2 | 0.02 | 6.0 |
| **39.5/32H** | 5/32" | 77.0 | 3.1 | 3.1 | 10.0 | 0.01 | 6.0 |
| **39.5/8** | 5/8" | 158.0 | 6.7 | 9.6 | 34.4 | 0.09 | 12.0 |
| **39.7/16** | 7/16" | 109.0 | 5.3 | 6.8 | 23.7 | 0.035 | 6.0 |
| **39.7/32H** | 7/32" | 84.0 | 3.5 | 4.0 | 11.8 | 0.01 | 6.0 |
| **39.9/16** | 9/16" | 147.0 | 6.0 | 8.5 | 30.2 | 0.07 | 12.0 |
| **39.9/32** | 9/32" | 90.0 | 4.1 | 5.0 | 15.0 | 0.015 | 6.0 |

© FACOM 2020