XENON S1P

SRC

Standard EN ISO 20345 : 2011

LEMAITRE
Safety since 1974



ParaBolic® Technology

- **Excellent grip**
- **Anti-fatigue spring effect**
- **MSD prevention**

Size 35 to 48 Réf. **XENOS1PGR**

Product Highlights

- **Abrasion resistant 3D textile upper and suede finish leather upper:** very good ventilation inside the shoe, quick drying.
- **Highly breathable 3D textile lining** thanks to its honeycomb structure, pleasant feeling of comfort.
- **Interlocking heel:** reinforced stability, foot support
- **Protective Toe-Cap** : stainless steel
- **Puncture-resistant midsole**: stainless steel



SPORTY PU2D antistatic sole

- **Injection below foot level**: adaptation of the leather to the shape of the foot, great flexibility of the sole and excellent breathability
- **Optimized grip surface and rounded heel strike**: unisex flat sole with a «sports» look
- **Parabolic® Patent** : anti-fatigue spring effect, reinforced stability
- **Rounded heel strike**: respects the natural rolling of the foot, comfort when driving

USAGE

- Construction workers, logisticians and drivers

FRENCH TRADEMARK

DEVELOPED RESPECTING THE FOOT ANATOMY

lemaitre-securite.com

An exacting attitude to quality is our culture, safety our priority

XENON S1P

SRC

Standard EN ISO 20345 : 2011

VARIANT



Xenon S1 SRC
XENOS10GR

Characteristics of the upper

- **Upper material:** abrasion-resistant 3D textile and split leather velour finish
- **Tongue with gusset:** 3D abrasion resistant textile
- **Lining:** micro-ventilated 3D textile

Characteristics of the sole

- **Designation:** SPORTY
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**
  forward flat slip: 0,37 (standard ≥ 0,32)
  forward heel slip: 0,32 (standard ≥ 0,28)
- **SRB Adhesion coefficient:**
  forward flat slip: 0,27 (standard ≥ 0,18)
  forward heel slip: 0,20 (standard ≥ 0,13)

Practical information

Weight of one shoe size 42: 705 g

CERTIFICATION N° 0075/007/161/05/19/1693 EXT 47/04/20

Packaging

size 35 to 43		size 44 to 48	
shoebox	315 x 220 x 125 mm	**shoebox**	355 x 220 x 130 mm
carton	635 x 445 x 325 mm	**carton**	660 x 450 x 360 mm
	10 shoeboxes per carton		10 shoeboxes per carton

Gencods

35	3237154378359	**42**	3237154378427
36	3237154378366	**43**	3237154378434
37	3237154378373	**44**	3237154378441
38	3237154378380	**45**	3237154378458
39	3237154378397	**46**	3237154378465
40	3237154378403	**47**	3237154378472
41	3237154378410	**48**	3237154378489

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear

SBP	✓	✓			
S1	✓		A	E	Fo
S1P	✓	✓	A	E	Fo
S2	✓		A	E	Fo	Wru
S3	✓	✓	A	E	Fo	Wru

200 J toe-cap: protection of the forefoot against impact and crushing.

Anti-perforation insert 1100 N: foot protection against perforation.

- **A** Anti-static footwear
- **E** Shock absorption at the heel
- **Fo** Fuel oil-resistant outsole
- **Wru** Water penetration and water absorption resistant upper
- **ESD** Electrostatic discharge
- **Ci** Insulation against cold
- **Hi** Insulation against heat
- **Hro** Outsole resistance to hot contact
- **Wr** Water resistant
- **An** Ankle protection

- **SRA** Slip-resistance on ceramic floors with detergent
- **SRB** Slip-resistance on steel floors with glycerol
- **SRC** = **SRA** + **SRB**

Lemaitre Sécurité
17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

LEMAITRE
Safety since 1974

DON_LS 04 TDS 0070
update: 06/07/21

Member of SYNAMAP

afaq ISO 9001 Qualité AFNOR CERTIFICATION

afaq ISO 14001 Environnement AFNOR CERTIFICATION