Geberit Mapress Copper elbow adaptor union 90° with female thread



Example image



APPLICATION PURPOSES

- For cold and hot potable water
- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For district heating water ≤ 120 °C
- For service water and process water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For technical building systems, industry and shipbuilding

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- Union nut made of brass
- Seal ring made of CIIR, black
- Flat gasket made of EPDM
- Pressing socket with transparent protection plug

TECHNICAL DATA

Medium temperature with flat gasket EPDM	0–100 °C
Product material	Gunmetal / lead-free gunmetal

Art. no.	DN	d, ø mm	Rp "	G "	Product material	arc °	L cm	L1 cm	Z cm	Z1 cm
65382	12 / 15	15	1/2	3/4	Lead-free gunmetal	90	5.7	3.2	3.7	1.9
65392	15	18	1/2	3/4	Lead-free gunmetal	90	5.7	3.2	3.7	1.9
65384	20	22	3/4	1	Gunmetal	90	6.4	3.6	4.3	2.1
65385	25	28	1	1 1/4	Lead-free gunmetal	90	7.2	4.4	4.9	2.7

Art. no.	DN	d, ø mm	Rp "	G "	Product material	arc °	L cm	L1 cm	Z cm	Z1 cm
65386	32	35	1 1/4	1 1/2	Lead-free gunmetal	90	8	5	5.4	3.1
65387	40	42	1 1/2	1 3/4	Lead-free gunmetal	90	8.7	5.3	5.7	3.4
65388	50	54	2	2 3/8	Gunmetal	90	10.1	6.4	6.6	4.1