TREKTEX S3

Standard EN ISO 20345 : 2011

LEMAITRE
Safety since 1974



Parabolic® Outsole
- Excellent grip
- Anti-fatigue spring effect
- MSD prevention

Membrane lining waterproof breathable
- 100% waterproof, breathable and anti-bacterial
- optimal foot breathing
- comfort improvement
- full-length shoe

Sizes 35 to 49 Ref. **TREXS30BF**

Product Highlights

- **All-terrain shoe available with men's and women fit.**
- **2,0 mm thick high strengh leather** (against abrasion, tearing and puncture).
- **Reinforced vamp and quarter with very few seams**
- **Tongue with gusset** to avoid any infiltration of dust / stones.
- **Back pull for easy donning.**
- **Memory Foam Titan insole for immediate and long-lasting comfort:** antibacterial properties, respects foot hygiene
- **Protective toe-cap:** composite HDFC.
- **Puncture-resistant midsole**: high tenacity fabric "0" penetration.



TRAIL PU2D antistatic sole

- **Protruding studs:** grip and hold on uneven ground, breaking up earth while walking.
- **Liquid and mud drainage channels** to prevent aquaplaning.
- **Parabolic® patent** with dynamic anti-fatigue effect.
- **15 mm stepped heel** for improved safety, especially on ladders.

USE

- Public works, forestry and agriculture, green spaces, roads, networks.
- Wet environments and difficult terrain.

FRENCH TRADEMARK

lemaitre-securite.com

Lemaitre takes care.

TREKTEX S3

Standard EN ISO 20345 : 2011

Characteristics of the upper

- **Upper material:** water-repellent pull-up leather,
- **Tongue with gusset**
- **Lining:** complete waterproof-breathable membrane liner

Characteristics of the sole

- **Designation:** TRAIL PU2D
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**
  forward flat slip: 0,40 (standard ≥ 0,32)
  forward heel slip: 0,45 (standard ≥ 0,28)
- **Coefficient d'adhérence SRB :**
  forward flat slip: 0,21 (standard ≥ 0,18)
  forward heel slip: 0,18 (standard ≥ 0,13)

VARIANT



Trek brun S3
TREKS30BFVA

Practical information

Women's fitting 35-39	**Men's fitting** 40-49
AET N° 0075/007/161/10/19/3219 EXT 06/03/22	Weight of one shoe size 42: 704 g
	AET N° 0075/007/161/10/19/3219 EXT 07/03/22

Packaging

size 35 to 39	**size 40 to 49**
shoebox 355 x 290 x 130 mm	**shoebox** 355 x 340 x 130 mm
carton 670 x 305 x 370 mm	**carton** 670 x 355 x 360 mm
5 shoeboxes per carton	**5 shoeboxes per carton**

Gencods

35	3237154446355	**43**	3237154446430
36	3237154446362	**44**	3237154446447
37	3237154446379	**45**	3237154446454
38	3237154446386	**46**	3237154446461
39	3237154446393	**47**	3237154446478
40	3237154446409	**48**	3237154446485
41	3237154446416	**49**	3237154446492
42	3237154446423		

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear			
SBP			
S1			A E Fo
S1P			A E Fo
S2			A E Fo Wru
S3			A E Fo Wru

200 J toe-cap: protection of the forefoot against impact and crushing.

Anti-perforation insert 1100 N: foot protection against perforation.

- A — Anti-static footwear
- E — Shock absorption at the heel
- Fo — Fuel oil-resistant outsole
- Wru — Water penetration and water absorption resistant upper
- ESD — Electrostatic discharge
- Ci — Insulation against cold
- Hi — Insulation against heat
- Hro — Outsole resistance to hot contact
- Wr — Water resistant
- An — Ankle protection

- SRA — Slip-resistance on ceramic floors with detergent
- SRB — Slip-resistance on steel floors with glycerol
- SRC = SRA + SRB

Lemaitre Sécurité
17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com

LEMAITRE
Safety since 1974

DON_LS 04 TDS 0173
update: 20/03/24

Member of SYNAMAP