



jalas® FIRE 1578 FIRE & RESCUE

EN 15090:2012 F1PA, SRC, T, CI

Learn more

HEAT RESISTANCE SAFETY BOOT

Safety boot in specially treated leather with heat resistance para-aramid thread in the seams provides a max operating heat limit of 400°C/752°F for 30 minutes. Nail protection in steel, toecap in aluminium, PU midsole and a rubber outsole.

CHARACTERISTICS

- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable
- Excellent shock absorption

FUNCTIONS

- ProNose toe reinforcement
- Wide fit
- KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit)
- Heat-resistant upper
- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Padded boot shaft
- Ventilating insole
- Pull loops
- Waterproof
- Reflector
- Specially designed details
- Double shock absorption zones

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Toe injuries, nail penetration, antistatic, wet feet

PRIMARY ENVIRONMENTS OF USE

Outdoors, all-year use, warm surfaces, environments with risk for outsole penetration, moist environments, oily and greasy environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Mining, fire fighting, rescue work

SPECIFICATION

TYPE Safety footwear, Boots
CATEGORY Cat. III
NAIL PROTECTION MATERIAL Steel
FITTING Wide
COLLECTION Fire
UPPER MATERIAL PU-coated leather
PRONOSE MATERIAL PU
TOECAP MATERIAL Aluminium
LINING MATERIAL Polyester, polyamide, Drylock membrane
INSOLE FX2 Pro
INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Double shock absorption zones in Poron® XRD®
MIDSOLE MATERIAL PU midsole
OUTSOLE MATERIAL Nitrile rubber outsole
COLOUR Black, Yellow
NET WEIGHT, (SIZE 42) 1.41 kg

COMPLIANCE

CE Cat. III

EAC

EN 15090:2012
F1PA, SRC, T, CI

ÖNORM Z 1259

DGUV 112-191

FEATURES

- Anti-static properties
- Ergothan Shock Absorption System
- Heat-resistant upper
- Aluminium toecap
- Oil-resistant outsole
- ProNose toe reinforcement
- Wide fit
- Heat-resistant outsole
- Nail protection in steel
- Waterproof

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
38	5	5½	6½	1578-38	6408487502583
39	6	6½	7½	1578-39	6408487502590
40	6½	7½	8½	1578-40	6408487502606
41	7	8	9	1578-41	6408487502613
42	8	9	10	1578-42	6408487502620
43	9	9½	11	1578-43	6408487502637
44	10	10½	11½	1578-44	6408487502644
45	10½	11	12½	1578-45	6408487502651
46	11	12	13	1578-46	6408487502668
47	12	13	14	1578-47	6408487502675
48	13	13½	14½	1578-48	6408487502682
49	14	14½	15½	1578-49	6408487503818
50	15	15½	16½	1578-50	6408487503825

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.