



jalas® GRAN PREMIO 1508 GP

EN ISO 20345:2011 S3, SRC, HRO, CI, HI ASTM F2413-18 M/I/C SD 35 PR

Learn more

FOR THE REALLY TOUGH CONDITIONS

This high-cut safety boot is made for the really tough conditions. For convenience it has an extra-wide fit, technical fleece lining and BOA® Fit System. For safety it has FX2 Pro insole with PORON®XRD® for shock absorption, nitrile rubber outsole for excellent grip on cold or slippery surfaces, a stabilizer arch to secure grip on ladders, steel nail penetration insert and lightweight aluminium toe cap. Use it where ordinary safety shoes are not enough.

CHARACTERISTICS

- Excellent grip
- Perfect fit
- Extra comfortable
- Excellent shock absorption

FUNCTIONS

- ProNose toe reinforcement
- Wide fit
- Padded boot shaft
- Heat-resistant upper
- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Easy clean upper
- Bellows tongue
- Polstered shaft edge
- Ventilating insole
- BOA® Fit System
- Ankle support
- Pull loops
- ESD
- Antistatic/ATEX
- Water repellent leather
- Heat insulating
- Double shock absorption zones
- Conforms with IEC 61340-5-1 (ESD)

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Toe injuries, nail penetration, sprain injuries, antistatic, slipping, strain injuries

PRIMARY ENVIRONMENTS OF USE

Dry environments, clean environments, cold environments, warm environments, wet environments, oily and greasy environments, dirty environments, harsh environments, environments with explosive risks

PRIMARY INDUSTRIES OF USE

Agriculture, mining, oil, gas, petrochemical, pulp and paper, rubber and plastic, glass, bricks, concrete, metal fabrication, machinery and equipment, mro, transportation, building and construction

SPECIFICATION

TYPE , Boots/Ankle boots
CATEGORY Cat. II
NAIL PROTECTION MATERIAL Steel
FITTING Wide
COLLECTION Gran Premio
UPPER MATERIAL PU-coated leather
PRONOSE MATERIAL PU
TOECAP MATERIAL Aluminium
LINING MATERIAL Technical fleece
INSOLE FX2 Pro
INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Double shock absorption zones in Poron® XRD®
MIDSOLE MATERIAL PU midsole
OUTSOLE MATERIAL Nitrile rubber outsole
FASTENING BOA® Fit System
COLOUR Black
NET WEIGHT, (SIZE 42) 1.46 kg

COMPLIANCE

CE Cat. II

EN ISO 20345:2011
S3, SRC, HRO, CI, HI

EAC TP TC 019:2011

ASTM F2413-18
M/I/C
SD 35 PR

ÖNORM Z 1259

DGUV 112-191

FEATURES

- Anti-static properties
- Ergothan Shock Absorption System
- ESD
- Aluminium toecap
- Oil-resistant outsole
- ProNose toe reinforcement
- Wide fit
- Heat-resistant outsole
- Water repellent
- Winter model
- Nail protection in steel

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
35	2	3½	4	1508-35	6408487531293
36	3	4	5	1508-36	6408487531330
37	4	5	6	1508-37	6408487531378
38	5	5½	6½	1508-38	6408487531415
39	6	6½	7½	1508-39	6408487531453
40	6½	7½	8½	1508-40	6408487531491
41	7	8	9	1508-41	6408487531538
42	8	9	10	1508-42	6408487531576
43	9	9½	11	1508-43	6408487531613
44	10	10½	11½	1508-44	6408487531651
45	10½	11	12½	1508-45	6408487531699
46	11	12	13	1508-46	6408487531736
47	12	13	14	1508-47	6408487531774
48	13	13½	14½	1508-48	6408487531811
49	14	14½	15½	1508-49	6408487531859
50	15	15½	16½	1508-50	6408487531897

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.