CALGARY FEMME S2

SRC Ci 0% METAL

Standard EN ISO 20345 : 2011

LEMAITRE
Safety since 1974



ParaBolic® Technology

- Excellent grip
- Anti-fatigue spring effect
- MSD prevention

Size 35 to 42

Réf. **CALFS20BL**

Product Highlights

- **Smooth water-repellent microfiber upper**: Lightweight, breathable, tear and abrasion resistant. Easy maintenance.
- **Breathable and comfortable model**: Hygienic lining made of absorbent fibers. High sweat absorption capacity, quick drying.
- **No laces to avoid retention of biological matter.**
- **Elastic support on the instep:** perfect fit.
- **Heel shock absorption**: fatigue reduction and MSD prevention.
- **Protective toe-cap** : composite HDFC.



Parabolight sole PU2D antistatic.

- **Specific proportions for the female foot morphology:** comfortable footwear.
- **Sole adapted to tiled and slippery floors.**
- **Parabolic patent®** with dynamic anti-fatigue effect.
- **Asymmetrical profile with structured «summer tire» / «winter tire» design:** stability.
- **Numerous bending notches:** flexible sole, suitable for kneeling work.

USAGE

- Food industry
- Paint booths
- Laboratories

FRENCH TRADEMARK

DEVELOPED RESPECTING THE FOOT ANATOMY

lemaitre-securite.com

Lemaitre takes care.

CALGARY FEMME S2

SRC Ci 0% METAL

Standard EN ISO 20345 : 2011

VARIANT



Impala Femme S2 SRC
IMPFS20BL

Characteristics of the upper

- **Upper material:** smooth waterproof microfiber
- **Tongue:** smooth waterproof microfiber
- **Lining:** non-woven absorbent fibers

Practical information

Weight of one shoe size 37 : 324 g

CERTIFICATION N° 0075/007/161/01/19/0284 EXT 13/05/19

Packaging

size 35 to 42	
shoebox	317 x 199 x 104 mm
carton	565 x 415 x 325 mm
	10 shoeboxes per carton

Characteristics of the sole

- **Designation:** Parabolight
- **Material:** PU / PU
- **Antistatic sole**
- **SRA Adhesion coefficient:**
  forward flat slip: 0,33 (standard ≥ 0,32)
  forward heel slip: 0,36 (standard ≥ 0,28)
- **SRB Adhesion coefficient:**
  forward flat slip: 0,23 (standard ≥ 0,18)
  forward heel slip: 0,21 (standard ≥ 0,13)

Gencods

35	3237154256350	**39**	3237154256398
36	3237154256367	**40**	3237154256404
37	3237154256374	**41**	3237154256411
38	3237154256381	**42**	3237154256428

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear			
SBP			
S1			A E Fo
S1P			A E Fo
S2			A E Fo Wru
S3			A E Fo Wru

200 J toe-cap: protection of the forefoot against impact and crushing.

Anti-perforation insert 1100 N: foot protection against perforation.

- **A** Anti-static footwear
- **E** Shock absorption at the heel
- **Fo** Fuel oil-resistant outsole
- **Wru** Water penetration and water absorption resistant upper
- **ESD** Electrostatic discharge
- **Ci** Insulation against cold
- **Hi** Insulation against heat
- **Hro** Outsole resistance to hot contact
- **Wr** Water resistant
- **An** Ankle protection

- **SRA** Slip-resistance on ceramic floors with detergent
- **SRB** Slip-resistance on steel floors with glycerol
- **SRC** = **SRA** + **SRB**

Lemaitre Sécurité
17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com

LEMAITRE
Safety since 1974

DON_LS 04 TDS 0098
update: 15/05/24

Member of SYNAMAP

afaq ISO 9001 Qualité AFNOR CERTIFICATION

afaq ISO 14001 Environnement AFNOR CERTIFICATION