TENERE S3 *black sole*

Standard EN ISO 20345 : 2011

LEMAITRE
Safety since 1974



ParaBolic® Technology

- Excellent grip
- Anti-fatigue spring effect
- MSD prevention

LE PLUS PRODUIT

Protection TPU à l'arrière.
TPU rear protection.

Sizes 35 to 49 Ref. **TENES30BFSN**

Product Highlights

- **All-terrain shoe available with men's and women fit.**
- **2,0 mm thick high strengh leather** (against abrasion, tearing and puncture).
- **Reinforced front of the shoe** for an extended life span over time.

Fourrure synthétique pour la saison froide
synthetic fur for cold weather

- **Furred lining, good thermal insulation** for harsh weather conditions.
- **Anatomical, antibacterial Energy+ insole:** reduces impact and fatigue, neutralizes odors.
- **Protective toe-cap:** composite HDFC.
- **Puncture-resistant midsole**: high tenacity fabric "0" penetration.



TRAIL PU2D antistatic sole

- **Protruding studs:** grip and hold on uneven ground, breaking up earth while walking.
- **Liquid and mud drainage channels** to prevent aquaplaning.
- **Parabolic® patent** with dynamic anti-fatigue effect.
- **15 mm stepped heel** for improved safety, especially on ladders.

USE

- Public works, forestry and agriculture, green spaces, roads, networks.

FRENCH TRADEMARK

DEVELOPED RESPECTING THE FOOT ANATOMY

lemaitre-securite.com

Lemaitre takes care.

TENERE S3 *black sole*

Ci SRC 0% METAL

Standard EN ISO 20345 : 2011

Characteristics of the upper

- **Upper material:** water-repellent pull-up grain leather with reinforced anti-abrasion toecap
- **Lining:** synthetic fur
- **Side ties:** water-repellent pull-up grain leather

Characteristics of the sole

- **Designation:** TRAIL PU2D
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**
  forward flat slip: 0,40 (standard ≥ 0,32)
  forward heel slip: 0,45 (standard ≥ 0,28)
- **Coefficient d'adhérence SRB :**
  forward flat slip: 0,21 (standard ≥ 0,18)
  forward heel slip: 0,18 (standard ≥ 0,13)

VARIANT



Tenere S3 *red sole*
TENES30BFSR

Practical information

Women's fitting 35-39	**Men's fitting** 40-49
Weight of one shoe size 38: 660 g	Weight of one shoe size 42: 800 g
AET N° 0075/007/161/04/16/0375 EXT 07/06/16	**AET N°** 0075/007/161/04/16/0375 EXT 01/05/16

Packaging

size 35 to 49
shoebox 350 x 340 x 130 mm
carton 670 x 355 x 360 mm
5 shoeboxes per carton

Gencods

35	3237154061350	**43**	3237154061435
36	3237154061367	**44**	3237154061442
37	3237154061374	**45**	3237154061459
38	3237154061381	**46**	3237154061466
39	3237154061398	**47**	3237154061473
40	3237154061404	**48**	3237154061480
41	3237154061411	**49**	3237154061497
42	3237154061428		

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear						
SBP	●	●				
S1	●		A	E	Fo	
S1P	●	●	A	E	Fo	
S2	●		A	E	Fo	Wru
S3	●	●	A	E	Fo	Wru

● 200 J toe-cap: protection of the forefoot against impact and crushing.

● Anti-perforation insert 1100 N: foot protection against perforation.

- A — Anti-static footwear
- E — Shock absorption at the heel
- Fo — Fuel oil-resistant outsole
- Wru — Water penetration and water absorption resistant upper
- ESD — Electrostatic discharge
- Ci — Insulation against cold
- Hi — Insulation against heat
- Hro — Outsole resistance to hot contact
- Wr — Water resistant
- An — Ankle protection

- SRA — Slip-resistance on ceramic floors with detergent
- SRB — Slip-resistance on steel floors with glycerol
- SRC = SRA + SRB

Lemaitre Sécurité
17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com

LEMAITRE
Safety since 1974

DON_LS 04 TDS 0174
update: 20/03/24

Member of SYNAMAP

afaq ISO 9001 Qualité AFNOR CERTIFICATION

afaq ISO 14001 Environnement AFNOR CERTIFICATION