# DATASHEET - 32NHG000B-690



**Fuse-link, LV, 32 A, AC 690 V, NH000, gL/gG, IEC, dual indicator, live gripping lugs**

Powering Business Worldwide

**Catalog No.** 32NHG000B-690

**EL-Nummer (Norway)** 0001664102

## Delivery program

| | | | |
|---|---|---|---|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | low voltage |
| Rated current | I | A | 32 |
| Rated voltage | | | AC 690 V |
| Construction size | | | NH000 |
| Utilization category | | | gL/gG |
| Status indicator | | | dual (combination) indicator system |
| Description | | | live gripping lugs |
| Breaking Capacity | | kA | 120 |
| Standard/Approval | | | IEC |
| Shape | | | square body with knife blade contacts |
| Standards/Regulations | | | IEC 60269-2 fuse system A<br>DIN 43620<br>VDE 0636-2 |

## Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])

| | | | |
|---|---|---|---|
| Construction size | | | NH000 |
| Rated current | | A | 32 |
| Rated voltage | | V | 690 |
| Voltage type | | | AC |
| Rated switching capacity | | kA | 120 |
| Utilization category | | | gL/gG (cable protection/equipment protection) |
| Type of fuse status indicator | | | Combination fuse status indicator |
| Insulated metal gripping lugs (IMGL) | | | No |

## Additional product information (links)

| | |
|---|---|
| Product datasheet (PDF) | http://www.cooperindustries.com/content/dam/public/bussmann/iec-electrical/resources/data-sheets/bus-iec-ds-720109-nh690vfuselinks.pdf |


© 12/2018 by Eaton Industries GmbH