Specifications

Eaton 289868



Catalog Number: 289868

Eaton xEnergy Basic LV systems Low voltage switchgear. Busbar support 250A

General specifications

Product Name	**Catalog Number**
Eaton xEnergy Basic other accessory	289868
EAN	**Product Length/Depth**
4015082898687	150 mm
Product Height	**Product Width**
40 mm	50 mm
Product Weight	**Compliances**
0.078 kg	RoHS conform

Powering Business Worldwide

Product specifications

Busbar position

Bottom rear

Current rating - max

250 A

Busbar distance

20 mm

Busbar height

5 mm

Busbar thickness - max

20 mm

Number of poles

Four-pole

Amperage rating

250 A

Rated short-time withstand current (Icw)

15 kA

Mounting position

Universal

Functions

Additional equipment

Mounting method

Surface mounting

Floor standing distribution board

Material

Plastic

Resources

Brochures

eaton-xenergy-basic-light-brochure-br014024-en-us.pdf

Catalogs

eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf

Declarations of conformity

DA-DC-03_Z-BB

Sales notes

eaton-f3a-flange-flyer-fl019005en-en-us.pdf

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia