Date: 11/04/2023

TR10-C, 1xPt100, 3-w, Cl.B, -50/250°C (F), terminal block

TR10-C RTD assembly with fabricated threaded protection tube

Item number:	45788289
Quantity:	1 pcs.
Order code:	TR10-C-ZZZZ-13DR-BS1A-ZZ-A2AGDL501601300305-ZZZZ R1C 031560RZ-ZA-Z-WIKA0Z
Overview:	TR10-C, 1xPt100, 3-w, Cl.B, -50/250°C (F), terminal block Diameter measuring insert: Ø 6 mm, 1.4571, BS (Alu), Strd.-gland, M20x1.5, terminal block Protection tube: Form 2G, 1.4571, Ø 9x1mm, M24 x 1,5 - G1/2B, MH=130 mm , U1=160mm Sealing: Without Specifications according to data sheet: TE 60.03 Measuring insert length (spare) [l5]: 315 mm Protection tube total length (spare) [L]: 305 mm
Details:	TR10-C RTD assembly with fabricated threaded protection tube Specifications according to data sheet: TE 60.03 1xPt100, 3-wire Class B, IEC 60751 Temperature range of selected class: -50...+250°C Head / housing: BS, Aluminum, flat cover Cable entry: Standard cable entry Thread size cable entry: M20 x 1.5 Transmitter: Without (terminal block) Connection to neck tube: M24 x 1,5 Protection tube: Straight, thread, form 2G DIN 43772 Protection tube diameter: 9x1 mm Process connection: G 1/2 B Protection tube material: Stainless steel 1.4571 Insertion length [A] [U1]: 160 mm Neck length [MH/N]: 130 mm Diameter measuring insert: 6 mm Sheath material measuring insert: Stainless steel 1.4571 Sealing: Without Protection tube total length (spare) [L]: 305 mm Measuring insert length (spare) [l5]: 315 mm

© 2023 - WIKA Instruments s.a.r.l.