
RELECO by TURCK



Relay compatible with sockets:

S3-B, S3-S, S3-MP, S3-MS, S3-L, S3-PO



C3-A30

CE

General purpose
Three pole, change-over contacts

10 A 250 V AC1 0.5 A 110 V DC1
10 A 30 V DC1 0.5 A 220 V DC1

Contacts

Materials:	Standard, code 0	AgNi
	Optional, code 8	AgNi + 10µ Au
	Optional, code 9	AgNi + 0.2µ Au
Max. switching current		10 A
Max. peak inrush current (20 ms)		30 A
Max. switching voltage		250 V
Max. AC load (Table 1)		2.5 KVA
Max. DC load (Table 2)		

Coils (Ohms ±10% @ 20°C)

Pull-in voltage	≤0.8 x U_n
Drop-out voltage	≥0.1 x U_n
Nominal coil power	2.2 VA (AC)/1.3 W (DC)

VAC	Ω	mA	VDC	Ω	mA
24	67	92	24	433	54
48	296	46	48	1K8	27
115	1K7	19	110	9K2	12
230	7K1	9.5	220	36K1	6

Insulation

Dielectric strength (1 minute): Open contacts	1,000 V
Between adjacent poles	2.5 KV
Between contacts and coil	2.5 KV
Isolation resistance at 500 V	≥1 GΩ
Isolation, IEC 61810-1:	2.5 KV/3

Specifications

Operate time + bounce time	16 ms
Release time + bounce time	8 ms
Ambient temperature	-40°C (no ice) to +70°C
Mechanical life ops.	10 Mill. AC, 20 Mill. DC relays
Electrical life at nominal load	100,000 ops.
Operating frequency at nominal load	1,200/hour
Protection degree	IP 40/RT1
Weight avg.	90 g

Table 1 Electrical Life, ops. x 10^6






Table 2 Max. DC Load



Dimensions - mm



Standard Types

AC 50 Hz, (60 Hz)**: 24, 48, 115,** (120)**, 230,** (240)

X = LED (standard)	**C3-A30X.....VAC**
RC suppressor	**C3-A30R.....VAC**

DC 24, 48, 110, 220

X = LED, no polarity (standard)	**C3-A30X..... VDC**
Free-wheeling diode	**C3-A30DX .... VDC**
Polarity and free-wheeling diodes	**C3-A30FX..... VDC**
AC/DC bridge rectifier (24, 48 or 60 V)	**C3-A30BX .... VDC**

CE RoHS compliant cULus cSPus Lloyd´s CCC PG IEC 61810 EN 60947