MOJAVE S3

Norme EN ISO 20345 : 2011

LEMAITRE
Safety since 1974



ParaBolic® Technology

- Excellent grip
- Anti-fatigue spring effect
- MSD prevention

Size 35 to 49 Ref. **MOJAS30BNSN**

Product Highlights

- **Footwear available with men's and women's fit.**
- **2,0 mm thick high strengh leather** (against abrasion, tearing and puncture).
- **Reinforced front of the shoe** for an extended life span over time.
- **Anatomical and antibacterial Energy+ insock:** reduced impact and fatigue, odor neutralization.
- **Protective toe-cap:** composite HDFC.
- **Puncture-resistant midsole**: high tenacity fabric "0" penetration.



TRAIL PU2D antistatic sole

- **Protruding studs:** grip and hold on uneven ground, breaking up of soil while walking.
- **Drainage channels for liquids and mud** to avoid any risk of aquaplaning
- **Parabolic® patent** providing a feeling of dynamism and anti-fatigue.
- **15 mm raised heel** for more safety particularly on ladder rungs.

USAGE

- Civil engineering, forestry and agricultural works, green spaces, roads and networks.
- Wet environments and difficult terrain

FRENCH TRADEMARK

DEVELOPED RESPECTING THE FOOT ANATOMY

lemaitre-securite.com

An exacting attitude to quality is our culture, safety our priority

MOJAVE S3

Ci SRC 0% METAL

Standard EN ISO 20345 : 2011

Characteristics of the upper

- **Upper material:** waterproof pull-up leather
- **Lining:** 3D microporous fabric
- **Boot loop:** water-repellent full grain leather

Characteristics of the sole

- **Designation:** TRAIL PU2D
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**
  forward flat slip: 0,40 (standard ≥ 0,32)
  forward heel slip: 0,45 (standard ≥ 0,28)
- **SRB Adhesion coefficient:**
  forward flat slip: 0,21 (standard ≥ 0,18)
  forward heel slip: 0,18 (standard ≥ 0,13)

VARIANT



Tenere - black sole S3
TENES30BFSN
warm lining for icy-cold environments

Practical information

Women's fitting 35-39	**Men's fitting** 40-49
Weight of one shoe size 38: 655 g	Weight of one shoe size 42: 785 g
AET N° 0075/007/161/10/19/3219 EXT 05/05/21	**AET N°0075/007/161/10/19/3219 EXT 04/05/21**

Packaging

size 35 to 49	
shoebox	350 x 340 x 130 mm
carton	670 x 355 x 360 mm
	5 shoeboxes per carton

Gencods

35	3237154432358	**43**	3237154432433
36	3237154432365	**44**	3237154432440
37	3237154432372	**45**	3237154432457
38	3237154432389	**46**	3237154432464
39	3237154432396	**47**	3237154432471
40	3237154432402	**48**	3237154432488
41	3237154432419	**49**	3237154432495
42	3237154432426		

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear					
SBP					
S1			A	E	Fo
S1P			A	E	Fo
S2			A	E	Fo Wru
S3			A	E	Fo Wru

200 J toe-cap: protection of the forefoot against impact and crushing.

Anti-perforation insert 1100 N: foot protection against perforation.

- A — Anti-static footwear
- E — Shock absorption at the heel
- Fo — Fuel oil-resistant outsole
- Wru — Water penetration and water absorption resistant upper
- ESD — Electrostatic discharge
- Ci — Insulation against cold
- Hi — Insulation against heat
- Hro — Outsole resistance to hot contact
- Wr — Water resistant
- An — Ankle protection

SRA — Slip-resistance on ceramic floors with detergent

SRB — Slip-resistance on steel floors with glycerol

SRC = SRA + SRB

Lemaitre Sécurité
17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com

LEMAITRE
Safety since 1974

DON_LS 04 TDS 0044
update: 02/06/22

Member of SYNAMAP

afaq ISO 9001 Qualité AFNOR CERTIFICATION

afaq ISO 14001 Environnement AFNOR CERTIFICATION