JALKANBAN SAS ESD JIJI166

* Brevet International Déposé

S1P CI HI SRC
EN ISO 20345:2011
35 to 48



- **Suede leather**
- **PU/PU sole by BASF®**
- **ESD / Dissipative**
- **Polymer toe cap type B and midsole no metallic**

❖ Urban sport-style safety shoe incorporating **MAXI-Soft Duo™** anti-fatigue technology designed for work stations that require standing for long periods (Upright or sustained activity)..

❖ Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes ESD Environmental Class II tested according to **EN 61340-4-3** and **EN 61340-5-1**.

❖ Suede leather. Perforated quarters and top of upper for better foot ventilation. Fluorescent markings on the back of the heel.

❖ Upper lined in breathable **3D Surf** mesh with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.

❖ Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.

❖ Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.

❖ Lace up on seven pairs of no metallic eyelets. Grey laces 160 cm.

❖ Perforated insole for enhanced comfort : **MAXI-Soft Duo™** composed of **a soft BASF® Dynamic PU** midsole with heat sensitive memory foam and a maximum size **BASF® Elastopan insert** that improves weight distribution by reducing pressure points and absorbs and relieves body stress associated with a prolonged standing working position and when walking. Anatomical, breathable and fitted with the **Link ESDTM system**, an innovative and seamless, multi-contact, static electricity dissipater. (Patent pending).



❖ Ergonomic shoe, with broad synthetic polymer toe cap **Springtane-B ™**. Impact resistance to 200 Joules. Minimum height after test ≥ 4mm in relation to the Type A toe cap in accordance with Standard 22568-2:2019.

❖ Stab-resistant structural insole and liner in **FleXtane™ By Jallatte ESD**, in compliance with standard 12568:2010, antistatic, **100% composite**. Sewn directly onto the upper and covering **100% of the foot for total protection**.

❖ Heel stiffener to reinforce the heel seat.

❖ **BASF® PU / PU sole** with an urban sport design, linear profile and excellent slip resistance.

Slip resistance tests results EN Standard :
EN ISO 20345 : 2011 **Requirement SRC** (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent
On flat **0,62** (>0,32) – On the heel **0,48** (>0,28)

SRB Test ground steel/lubricant : glycerine
On flat **0,23** (>0,18) – On the heel **0,19** (>0,13)

- BExtremely light and flexible support base.
- Constant energy return over the entire surface.
- Reduced feeling of fatigue due to posture.
- Relief that facilitates the evacuation of fluids.



Weight	Gross weight (42) : 1456 g / Net weight (42) : 1240 g			
Size	35 to 39	40 to 42	43 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	687 x 226 x 350	687 x 432 x 348	689 x 511 x 351	689 x 260 x 348

Document non contractuel
Copyright JALLATTE
Diffusion Controlée

14/04/2022

www.jallatte.com