# RAFIX 16, multipole connector



### fields of application

- Measurement-control-regulation
- Electrical engineering
- Mechanical and system engineering
- Industrial robots

### special features

- Suitable for RAFIX 16 switching elements with plug-in connection

## description

Connection accessories for RAFIX 16 switching elements.

Ermöglicht ein gleichzeitiges Anschließen sämtlicher Anschlüsse eines Schaltelementes. Bestückbar mit Flachsteckhülsen 2,8 mm breit.

## technical data

**general**

| | |
|---|---|
| Operating temperature, min. | -25 °C |
| Operating temperature, max. | 70 °C |
| Packaging unit | 10 pcs. |
| net weight | 6.0 g |
| MOQ order | 10 pcs. |
| RoHS compliant | Yes |
| REACH compliant | Yes |

**mechanical data**

| | |
|---|---|
| Fixing | Latching |
| Terminal on the rear | Flat quick-connect terminal 2.8 x 0.8 |

### direct links

- RAFI eCatalog

The information in this data sheet only contains general descriptions and / or performance features, which may not apply precisely as described to the respective application, and which my change due to further product enhancements. The technical data, illustrations and other information about our products are the mere results of individual technical testing. These descriptions and other product features are only binding if they expressly agreed upon at the time of the conclusion of a binding contract. In all other cases, we reserve the right to make technical changes as well as changes of availability. Pictures and other graphic illustrations are approximations only. All product names may be trademarks or brand names of the RAFI Group or any other sub-supplier of RAFI. The use of such by any third parties for their own purposes may infringe the rights of the respective entity holding those rights.


**RAFI GmbH & Co. KG**

Ravensburger Str. 128-134
88276 Berg / Ravensburg
Germany
www.rafi-group.com,
info.headquarters@rafi-group.com