Date: 11/04/2023

SC15.30.100 0 ... 200°C CL.2

Tension thermometer - Indicating temperature controller SC15

Item number:	6151555
Quantity:	1 pcs.
Order code:	SC15-ZZ30100AZ04CLT2AAZZZZZZZZZC0200Z01V0600300ZZZ6 ZZZZZZZZ1ZZZZZZZB2EZ
Overview:	SC15.30.100 0 ... 200°C CL.2 standard, plastic case Panel mounting with clamp, 2 adjustable changeover switches, adjusting knob push in 5 A non-inductive at max. 250VAC 50/60Hz terminal block Capillary [FL]: 2.00 m Copper double copper braided, 2x Supportspirales (sensor - case) Connection design: BF1 Insertion length [L1] o. [U1]: 300 x 6 mm Stainless Steel Dial background: White *WIKA*
Details:	Tension thermometer - Indicating temperature controller SC15 Specifications according to data sheet: TV 28.02 Model: SC15 - combistat Design: standard, plastic case Nominal size [NG, d1]: 100 mm Mounting option: Panel mounting with clamp, Unit: °C Scale range: 0 ... 200°C Contact type: 2 adjustable changeover switches, Contact adjustment: adjusting knob push in Switch rating: 5 A non-inductive at max. 250VAC 50/60Hz Cable connection: terminal block Capillary material: Copper double copper braided, Capillary [FL]: 2.00 Connection design: BF1 - Plain stem, Probe material: Stainless Steel Probe diameter [d5] o. [F1]: 6 mm Insertion length [L1] o. [U1]: 300 Manufacturer logo: *WIKA* Accuracy class: class 2 per EN 13190 Capillary protection: 2x Supportspirales (sensor - case) Dial background: White

© 2023 - WIKA Instruments s.a.r.l.