SKYTEC | CIRRUS™

SUPPLE AND LIGHTWEIGHT WITH CUT RESISTANCE AND PU PALM

Offers dexterity and comfort with good resistance to cuts, rips and punctures. The thin polyurethane coating allows components and materials to be handled precisely.

FEATURES

- Cut resistant: Level B (EN 388:2016)
- Supple and lightweight
- Extremely durable
- Offers outstanding flexibility with a tactile touch
- Excellent grip in both dry and damp environments
- Anatomically designed for comfort, dexterity and fit
- Coated with polyurethane on palm up to fingers
- Sanitized® antimicrobial finish provides extra freshness



CUT LEVEL B

Sanitized Actifresh

VENDING MACHINE COMPATIBLE

SUITABLE FOR

Typical Industries

- Aerospace
- Automotive
- Construction
- Engineering
- Glass
- Manufacturing

Suitable Applications

- Bottling or Canning
- Component Assembly
- Packaging
- Second Fix
- Warehousing and Distribution

CERTIFICATION

CAT II

CE

EN 388:2016

4X43B

See overleaf for explanation

Globus GROUP

SKYTEC® CIRRUS™

PRODUCT INFORMATION

MATERIALS	LINER:	13 gauge HPPE, nylon
	COATING:	Polyurethane (PU)
COLOUR	Grey	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

			VEND COMPATIBLE OPTION	
SIZE	**CODE**	**PACKAGING**	**CODE**	**PACKAGING**
7/S 8/M 9/L 10/XL 11/XXL	SKY461 SKY462 SKY463 SKY464 SKY465	10 pairs per bag 120 pairs per case	SKYV461 SKYV462 SKYV463 SKYV464 SKYV465	120 individually bagged pairs per case

RECOMMENDATIONS FOR USE

- USE: General handling glove with cut protection. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4 0-5 0-4 0-4 A-F P

- 0-4: Abrasion Resistance
- 0-5: Circular Blade Cut Resistance
- 0-4: Tear Resistance
- 0-4: Puncture Resistance
- A-F: Straight Blade Cut Resistance (EN ISO: 13997)
- P: Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globusgroup.com

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

Globus GROUP

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2021 Globus (Shetland) Ltd | SKY-DATA-CIRRUS-0420_1

EU Type-Examination Certificate issued by SATRA Technology Europe Limited. Bracetown Business Park. Clonee. D15YN2P. Republic of Ireland. (Notified Body No. 2777)
The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.