Date: 24/04/2023

232.30.160 -1 bar 2nd scale mmHg G1/2B lower mount

Bourdon Tube Pressure Gauges, Safety Pattern

Item number: 48737280

Quantity: 1 pcs.

Order code: 232.30-F-BV3105-GD-UZHZCZZ-ZZZZZZZ 213D31ZI3W0 Z2Z-ICZZZZZ12ZZZ
LABEL-PG1DE-ZZZZZ

Overview:
232.30.160 -1 bar 2nd scale mmHg G1/2B lower mount
Measuring System 316L
Ingress protection: IP 65
class 1.0
Window: laminated safety glass
Permissible medium temperature: + 200 °C
Permissible ambient temperature: -40 … +60 °C
Pressure Gauge Standard: International (standard Europe)
2nd scale red
WIKA
with Serial number
Label: WIKA standard without / with Tag-number

Details:
Bourdon Tube Pressure Gauges, Safety Pattern
Series EN 837-1
Model: 232.30
Specifications according to data sheet: PM 02.04
Measuring system: stainless steel
Case filling: without
Nominal size: 160 mm
Measuring range: vacuum- or compound-range
Scale range: -1...0 bar
2nd Scale or Special Scale: 2nd scale mmHg
Process connection: G 1/2 B
Connector location: lower mount
Window: laminated safety glass
Pointer: standard pointer
Accuracy class: class 1.0
Overpressure safe: standard
Case material: Stainless steel 1.4301
Case surface: bare
Material pressure element: Measuring System 316L
Case filling fluid: prepared for filling
Ingress protection: IP 65
Permissible medium temperature: + 200 °C
Permissible ambient temperature: -40 … +60 °C
Movement: stainless steel

© 2023 - WIKA Instruments s.a.r.l.

Packaging: single packing
Pressure Gauge Standard: International (standard Europe)
color for 2.scale (inside): red RAL 3020
Manufacturer logo: *WIKA*
with Serial number
Permissible ambient temperature: -40 … +60 °C

© 2023 - WIKA Instruments s.a.r.l.