5.03.773.794/0001

KIS.ME onboarding cable, USB to M12, L 400 mm



fields of application

- Measurement-control-regulation
- Electrical engineering
- Mechanical and system engineering
- Automotive
- Electro-medical
- Signalling systems
- Chemical industry
- Handheld terminals
- Industrial robots
- Model construction
- Home technology

description

The KIS.ME onboarding cable is primarily used for onboarding the KIS.ME devices in KIS.MANAGER. In addition, the cable can be used for productive use of the KIS.ME devices in 5 V mode.

technical data

general	
Color	black
Operating temperature, min.	-25 °C
Operating temperature, max.	50 °C
Packaging	Tüte
Packaging unit	1 pcs.
MOQ order	1 pcs.
RoHS compliant	Yes
REACH compliant	Yes
mounting diameters	
Outside dimension, length	400 mm
mechanical data	
Front side terminal	USB 2.0 type A
Terminal on the rear	M12 8-pin A-coded
electrical data	
Voltage type	DC

direct links

- RAFI eCatalog

The information in this data sheet only contains general descriptions and / or performance features, which may not apply precisely as described to the respective application, and which my change due to further product enhancements. The technical data, illustrations and other information about our products are the mere results of individual technical testing. These descriptions and other product features are only binding if they expressly agreed upon at the time of the conclusion of a binding contract. In all other cases, we reserve the right to make technical changes as well as changes of availability. Pictures and other graphic illustrations are approximations only. All product names may be trademarks or brand names of the RAFI Group or any other sub-supplier of RAFI. The use of such by any third parties for their own purposes may infringe the rights of the respective entity holding those rights.

RAFI GmbH & Co. KG

Ravensburger Str. 128-134
88276 Berg / Ravensburg
Germany
www.rafi-group.com,
info.headquarters@rafi-group.com