



jalas® GRAN PREMIO 1550 LOW

EN ISO 20345:2022 S2, HRO, CI, A

Learn more

EASY-TO-CLEAN LOAFER

Easy-to-clean safety loafer in specially treated leather with heat resistance para-aramid thread in the seams provides a max operating heat limit of 400°C/752°F for 30 minutes. Suitable for metal work, welding and other occasions when an easy cleaned upper is needed. Spacious last, toe cap in aluminium.

CHARACTERISTICS

- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable
- Excellent shock absorption

FUNCTIONS

- ProNose toe reinforcement
- Wide fit
- KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit)
- Heat-resistant upper
- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Water repellent
- Double shock absorption zones
- Conforms with IEC 61340-5-1 (ESD)
- Ventilating insole
- Polstered shaft edge

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF
Toe injuries, antistatic

PRIMARY ENVIRONMENTS OF USE
Outdoors, indoors, all-year use, warm surfaces

PRIMARY AREAS OF USE
Sheet-metal work, metalwork, welding, hot work

PRIMARY INDUSTRIES OF USE
Metal fabrication

SPECIFICATION

TYPE Safety footwear, Loafers
CATEGORY Cat. II
FITTING Wide
COLLECTION Gran Premio
UPPER MATERIAL PU-coated leather
PRONOSE MATERIAL PU
TOECAP MATERIAL Aluminium
LINING MATERIAL Polyester
INSOLE FX2 Pro-X
INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Double shock absorption zones in Poron® XRD®
MIDSOLE MATERIAL PU midsole
OUTSOLE MATERIAL Nitrile rubber outsole
COLOUR Black
NET WEIGHT, (SIZE 42) 1.17 kg

COMPLIANCE

CE Cat. II

EAC TP TC 019:2011

EN ISO 20345:2022 S2, HRO, CI, A

ÖNORM Z 1259

DGUV 112-191

FEATURES

- Anti-static properties
- Ergothan Shock Absorption System
- ESD
- Heat-resistant upper
- Aluminium toecap
- Oil-resistant outsole
- ProNose toe reinforcement
- Wide fit
- Heat-resistant outsole
- Water repellent

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
36	3	4	5	1550-36	6408487442476
37	4	5	6	1550-37	6408487442483
38	5	5½	6½	1550-38	6408487442490
39	6	6½	7½	1550-39	6408487442506
40	6½	7½	8½	1550-40	6408487442513
41	7	8	9	1550-41	6408487442520
42	8	9	10	1550-42	6408487442537
43	9	9½	11	1550-43	6408487442544
44	10	10½	11½	1550-44	6408487442551
45	10½	11	12½	1550-45	6408487442568
46	11	12	13	1550-46	6408487442575
47	12	13	14	1550-47	6408487442582
48	13	13½	14½	1550-48	6408487442599

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.