
Filter pressure regulator, Series 652

- G 1/4 G 3/8 G 1/2
- filter porosity 5 25 µm
- With integrated pressure gauge





Type	1-part
Parts	Filter pressure regulator
Working pressure min./max.	0 ... 16 bar
Ambient temperature min./max.	-20 ... 50 °C
Medium temperature min./max.	-20 ... 50 °C Extended temperature range min./max. (optional) -40 °C ... 80 °C
Medium	Compressed air Neutral gases
Adjustment range min./max.	0,5 ... 10 bar
Hysteresis	0.5 bar
Weight	See table below
	The delivered product varies from that in the illustration. See the drawing for an exact description.

Technical data

Part No.	Port	filter porosity	Flow	Condensate drain
			Qn	
G652APBK2GA00HA	G 1/4	5 µm	4450 l/min	fully automatic, open without pressure
G652APBK2GA00HN	G 1/4	5 µm	3800 l/min	semi-automatic, open without pressure
G652APBK3GA00HA	G 3/8	5 µm	4450 l/min	fully automatic, open without pressure
G652APBK3GA00HN	G 3/8	5 µm	4450 l/min	semi-automatic, open without pressure
G652APBK4GA00HA	G 1/2	5 µm	4490 l/min	fully automatic, open without pressure
G652APBL3GA00HA	G 3/8	5 µm	4450 l/min	fully automatic, open without pressure
G652APBK4GA00HN	G 1/2	5 µm	4490 l/min	semi-automatic, open without pressure
G652APBL2GA00HA	G 1/4	5 µm	3800 l/min	fully automatic, open without pressure
G652APBL2GA00HN	G 1/4	5 µm	3800 l/min	semi-automatic, open without pressure
G652APBL3GA00HN	G 3/8	5 µm	4450 l/min	semi-automatic, open without pressure
G652APBL4GA00HA	G 1/2	5 µm	4490 l/min	fully automatic, open without pressure
G652APBL4GA00HN	G 1/2	5 µm	4490 l/min	semi-automatic, open without pressure
G652APBP2GA00HA	G 1/4	5 µm	3800 l/min	fully automatic, open without pressure
G652APBP2GA00HN	G 1/4	5 µm	3800 l/min	semi-automatic, open without pressure
G652APBP3GA00HA	G 3/8	5 µm	4450 l/min	fully automatic, open without pressure
G652APBP3GA00HN	G 3/8	5 µm	4450 l/min	semi-automatic, open without pressure
G652APBP4GA00HA	G 1/2	5 µm	4490 l/min	fully automatic, open without pressure
G652APBP4GA00HN	G 1/2	5 µm	4490 l/min	semi-automatic, open without pressure
G652APJK2GA00HA	G 1/4	25 µm	4120 l/min	fully automatic, open without pressure
G652APJK2GA00HN	G 1/4	25 µm	4120 l/min	semi-automatic, open without pressure
G652APJK3GA00HA	G 3/8	25 µm	5420 l/min	fully automatic, open without pressure
G652APJK3GA00HN	G 3/8	25 µm	5420 l/min	semi-automatic, open without pressure

Part No.	Port	filter porosity	Flow Qn	Condensate drain
G652APJK4GA00HA	G 1/2	25 µm	5500 l/min	fully automatic, open without pressure
G652APJK4GA00HN	G 1/2	25 µm	5500 l/min	semi-automatic, open without pressure
G652APJL2GA00HA	G 1/4	25 µm	4120 l/min	fully automatic, open without pressure
G652APJL2GA00HN	G 1/4	25 µm	4120 l/min	semi-automatic, open without pressure
G652APJL3GA00HA	G 3/8	25 µm	5420 l/min	fully automatic, open without pressure
G652APJL3GA00HN	G 3/8	25 µm	5420 l/min	semi-automatic, open without pressure
G652APJL4GA00HA	G 1/2	25 µm	5500 l/min	fully automatic, open without pressure
G652APJL4GA00HN	G 1/2	25 µm	5500 l/min	semi-automatic, open without pressure
G652APJP2GA00HA	G 1/4	25 µm	4120 l/min	fully automatic, open without pressure
G652APJP2GA00HN	G 1/4	25 µm	4120 l/min	semi-automatic, open without pressure
G652APJP3GA00HA	G 3/8	25 µm	5420 l/min	fully automatic, open without pressure
G652APJP3GA00HN	G 3/8	25 µm	5420 l/min	semi-automatic, open without pressure
G652APJP4GA00HA	G 1/2	25 µm	5500 l/min	fully automatic, open without pressure
G652APJP4GA00HN	G 1/2	25 µm	5500 l/min	semi-automatic, open without pressure

Part No.	Pressure gauge
G652APBK2GA00HA	With integrated pressure gauge
G652APBK2GA00HN	With integrated pressure gauge
G652APBK3GA00HA	With integrated pressure gauge
G652APBK3GA00HN	With integrated pressure gauge
G652APBK4GA00HA	With integrated pressure gauge
G652APBL3GA00HA	With integrated pressure gauge
G652APBK4GA00HN	With integrated pressure gauge
G652APBL2GA00HA	With integrated pressure gauge
G652APBL2GA00HN	With integrated pressure gauge
G652APBL3GA00HN	With integrated pressure gauge
G652APBL4GA00HA	With integrated pressure gauge
G652APBL4GA00HN	With integrated pressure gauge
G652APBP2GA00HA	With integrated pressure gauge
G652APBP2GA00HN	With integrated pressure gauge
G652APBP3GA00HA	With integrated pressure gauge
G652APBP3GA00HN	With integrated pressure gauge
G652APBP4GA00HA	With integrated pressure gauge
G652APBP4GA00HN	With integrated pressure gauge
G652APJK2GA00HA	With integrated pressure gauge
G652APJK2GA00HN	With integrated pressure gauge
G652APJK3GA00HA	With integrated pressure gauge
G652APJK3GA00HN	With integrated pressure gauge
G652APJK4GA00HA	With integrated pressure gauge
G652APJK4GA00HN	With integrated pressure gauge
G652APJL2GA00HA	With integrated pressure gauge
G652APJL2GA00HN	With integrated pressure gauge
G652APJL3GA00HA	With integrated pressure gauge
G652APJL3GA00HN	With integrated pressure gauge
G652APJL4GA00HA	With integrated pressure gauge
G652APJL4GA00HN	With integrated pressure gauge
G652APJP2GA00HA	With integrated pressure gauge

Part No.	Pressure gauge
G652APJP2GA00HN	With integrated pressure gauge
G652APJP3GA00HA	With integrated pressure gauge
G652APJP3GA00HN	With integrated pressure gauge
G652APJP4GA00HA	With integrated pressure gauge
G652APJP4GA00HN	With integrated pressure gauge

Part No.	Material Reservoir	Material Condensate drain	Weight
G652APBK2GA00HA	Metal reservoir without window	Brass	0,69 kg
G652APBK2GA00HN	Metal reservoir without window	Plastic	0,69 kg
G652APBK3GA00HA	Metal reservoir without window	Brass	0,69 kg
G652APBK3GA00HN	Metal reservoir without window	Plastic	0,69 kg
G652APBK4GA00HA	Metal reservoir without window	Brass	0,69 kg
G652APBL3GA00HA	reservoir, metal, with inspection glass	Brass	0,69 kg
G652APBK4GA00HN	Metal reservoir without window	Plastic	0,69 kg
G652APBL2GA00HA	reservoir, metal, with inspection glass	Brass	0,69 kg
G652APBL2GA00HN	reservoir, metal, with inspection glass	Plastic	0,69 kg
G652APBL3GA00HN	reservoir, metal, with inspection glass	Plastic	0,69 kg
G652APBL4GA00HA	reservoir, metal, with inspection glass	Brass	0,69 kg
G652APBL4GA00HN	reservoir, metal, with inspection glass	Plastic	0,69 kg
G652APBP2GA00HA	Reservoir polycarbonate	Brass	0,55 kg
G652APBP2GA00HN	Reservoir polycarbonate	Plastic	0,55 kg
G652APBP3GA00HA	Reservoir polycarbonate	Brass	0,55 kg
G652APBP3GA00HN	Reservoir polycarbonate	Plastic	0,55 kg
G652APBP4GA00HA	Reservoir polycarbonate	Brass	0,55 kg
G652APBP4GA00HN	Reservoir polycarbonate	Plastic	0,55 kg
G652APJK2GA00HA	Metal reservoir without window	Brass	0,69 kg
G652APJK2GA00HN	Metal reservoir without window	Plastic	0,69 kg
G652APJK3GA00HA	Metal reservoir without window	Brass	0,69 kg
G652APJK3GA00HN	Metal reservoir without window	Plastic	0,69 kg
G652APJK4GA00HA	Metal reservoir without window	Brass	0,69 kg
G652APJK4GA00HN	Metal reservoir without window	Plastic	0,69 kg
G652APJL2GA00HA	reservoir, metal, with inspection glass	Brass	0,69 kg
G652APJL2GA00HN	reservoir, metal, with inspection glass	Plastic	0,69 kg
G652APJL3GA00HA	reservoir, metal, with inspection glass	Brass	0,69 kg
G652APJL3GA00HN	reservoir, metal, with inspection glass	Plastic	0,69 kg
G652APJL4GA00HA	reservoir, metal, with inspection glass	Brass	0,69 kg
G652APJL4GA00HN	reservoir, metal, with inspection glass	Plastic	0,69 kg
G652APJP2GA00HA	Reservoir polycarbonate	Brass	0,55 kg
G652APJP2GA00HN	Reservoir polycarbonate	Plastic	0,55 kg
G652APJP3GA00HA	Reservoir polycarbonate	Brass	0,55 kg
G652APJP3GA00HN	Reservoir polycarbonate	Plastic	0,55 kg
G652APJP4GA00HA	Reservoir polycarbonate	Brass	0,55 kg
G652APJP4GA00HN	Reservoir polycarbonate	Plastic	0,55 kg

Nominal flow Qn at p1= 10 bar , p2= 6.3 bar and Δp = 1 bar

Technical information


Max. achievable compressed air class acc. to ISO 8573-1:2010 5 : 8 : 4 (5 µm filter porosity) und 6 : 8 : 4 (25µm filter porosity)
Other filter porosities on request.

Technical information

Material	
Housing	Aluminum
Front plate	Polyamide
Seals	Nitrile butadiene rubber
Filter insert	Sintered bronze
Condensate drain	Brass Plastic

Dimensions

Dimensions




To remove the reservoir, allow a clearance of 80 mm from the bottom of the reservoir drain.
*Variable dimension based on the type of drain specified, if an automatic drain is specified, add another 5 mm to the “J” dimension.

Dimensions


Series	A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	S	T	V	W	X	Y
652	248	94,5	66	33	69	30,5	4	160	25	41,75	42	50	20	10	61,5	84	105,5	29	14,5	6,3	7	11

Diagrams


Flow diagram, G 1/4



Flow diagram, G 3/8




Flow diagram, G 1/2



Accessories overview

Accessories overview



Ordering information

G 651 A P B P 2 G A00 H N


Thread connection
G = ISO 228/1-G [1]
8 = NPTF

Product series
651
652
653

Revision letter
A

Product type
P = Filter/Regulator - Particulate


Elements
B = 5 µm (White)
J = 25 µm (Yellow)



Bowl type
K = Metal bowl without sight gauge
L = Metal bowl with sight gauge (glass)
P = Polycarbonate bowl with bowl guard

Port size
1 = 1/8 (651 Series)
2 = 1/4 (651 or 652 Series)
3 = 3/8 (652 Series)
4 = 1/2 (652 Series)
5 = 3/4 (653 Series)
6 = 1 (653 Series)

Gauge type
B = Digital pressure switch - PNP
C = Digital pressure switch - NPN
D = Digital gauge
G = Low profile integrated gauge bar/PSI
J = Low profile integrated gauge bar/PSI with pressure range indicators
Q = Round gauge bar/PSI
0 = No gauge port
P = Port Plate Rc 1/8




Drain type
0 = Without
A = Auto drain normally open
N = Manual/Semi-automatic drain
Q = Manual drain - Stainless steel



Pressure range
D = 0,2..3 bar
H = 0,5..10 bar
N = 0,5..16 bar (653 only) [2]

Options [3]
A00 = Without option
101 = Side Mounting Brackets
102 = Panel Nut (651 or 652)
103 = Tamper resistant
104 = Key lockable
105 = High temperature (+80°C)
106 = Low temperature (-40°C) [4]
109 = FPM seals
113 = Stainless steel fasteners
114 = Provision for key lock
117 = ATEX zones 1-21
119 = Panel Bracket with Panel Nut (651 or 652)
121 = Non-relieving
123 = Gauge type mounted for right-to-left flow
124 = CUTR Certification (EAC)
125 = CUTR Ex
202 = 105 + 109
2A9 = 105 + 106



[1] Conforms to ISO standards 1179-1.
[2] Metal Bowl Types K or L only.
[3] If multiple options are required, please use the on-line CAD configurator on the website to generate the part number (www.asco.com).
[4] Compressed air must be dry enough so no ice formation is present on the product. All bowls should be emptied prior to ambient temperatures dropping below 0°C.

Efficient pneumatic solutions, our program: cylinders and drives, valves and valve systems, air supply management



Visit us: Emerson.com/Aventics

Your local contact: Emerson.com/contactus

Emerson.com

Facebook.com/EmersonAutomationSolutions

LinkedIn.com/company/Emerson-Automation-Solutions

Twitter.com/EMR_Automation

An example configuration is depicted on the title page. The delivered product may thus vary from that in the illustration. Subject to change. This Document, as well as the data, specifications and other information set forth in it, are the exclusive property of AVENTICS GmbH. It may not be reproduced or given to third parties without its consent. Only use the AVENTICS products shown in industrial applications. Read the product documentation completely and carefully before using the product. Observe the applicable regulations and laws of the respective country. When integrating the product into applications, note the system manufacturer's specifications for safe use of the product. The data specified only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgement and verification. It must be remembered that the products are subject to a natural process of wear and aging.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Brand logotype are registered trademarks of one of the Emerson family of companies. All other marks are the property of their respective owners. © 2020 Emerson Electric Co. All rights reserved.
2020-12

EMERSON

CONSIDER IT SOLVED™