



jalas® HEAVY DUTY 1258

EN ISO 20345:2011 S3, SRC, CI, HRO, HI

Learn more

IT'S ALL IN THE NAME

It's all in the name – a tough safety shoe with highest level protection built for tough environments. Specialbehandlat läder med värmebeständig para-aramidtråd i sömmarna ger motståndskraft mot värme med en maximal drift på 400°C i 30 minuter. The oil and heat-resistant nitrile outer sole means excellent grip and JALAS® Composite Toe Cap, steel puncture protection and double impact protection zones in PORON® XRD® keep feet safe in extreme conditions.

CHARACTERISTICS

- Excellent grip
- Perfect fit
- Extra comfortable
- Excellent shock absorption

FUNCTIONS

- ProNose toe reinforcement
- Water repellent
- Anti-static properties
- Bellows tongue
- KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit)
- Heat-resistant upper
- Heat-resistant outsole
- Oil-resistant outsole
- Double shock absorption zones
- Conforms with IEC 61340-5-1 (ESD)
- Polstered shaft edge

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Toe injuries, nail penetration, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, warm surfaces, environments with risk for outsole penetration, oily and greasy environments, dirty environments, harsh environments

SPECIFICATION

TYPE Safety footwear, Low shoes
CATEGORY Cat. II
NAIL PROTECTION MATERIAL Steel
FITTING Regular
COLLECTION Heavy Duty
UPPER MATERIAL PU-coated leather
PRONOSE MATERIAL PU
TOECAP MATERIAL Composite
LINING MATERIAL Polyester, polyamide
INSOLE FX2 Climate
INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Merino wool, Double shock absorption zones in Poron® XRD®
MIDSOLE MATERIAL PU midsole
OUTSOLE MATERIAL Nitrile rubber outsole
FASTENING Hook-and-loop
COLOUR Black, Blue
NET WEIGHT, (SIZE 42) 1.4 kg

COMPLIANCE

CE Cat. II

EAC TP TC 019:2011

EN ISO 20345:2011
S3, SRC, CI, HRO, HI

ÖNORM Z 1259

DGUV 112-191

FEATURES

- Anti-static properties
- Oil-resistant outsole
- ProNose toe reinforcement
- Nail protection in steel
- Heat-resistant outsole
- Water repellent
- Composite toecap
- Ergothan Shock Absorption System
- ESD
- Heat-resistant upper

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
35	2	3½	4	1258-35	6408487505942
36	3	4	5	1258-36	6408487505959
37	4	5	6	1258-37	6408487505966
38	5	5½	6½	1258-38	6408487505973
39	6	6½	7½	1258-39	6408487505980
40	6½	7½	8½	1258-40	6408487505997
41	7	8	9	1258-41	6408487506000
42	8	9	10	1258-42	6408487506017
43	9	9½	11	1258-43	6408487506024
44	10	10½	11½	1258-44	6408487506031
45	10½	11	12½	1258-45	6408487506048
46	11	12	13	1258-46	6408487506055
47	12	13	14	1258-47	6408487506062
48	13	13½	14½	1258-48	6408487506079

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.