



## jalas® TEMPUS 5618

EN ISO 20345:2011 S1, P, SRC  ASTM F2413-18 M/I/C SD 35 PR  ASTM F3445-21 SR

Learn more

## LIGHT WEIGHT, FOR WORK AND LEISURE

Light weight safety shoe for work and leisure. Breathable, sporty and comfortable with advanced shock absorbing with PORON XRD, protective toe cap and a soft and flexible nail penetration insert made of textile material. The well proven outsole has a very effective grip pattern and is made of a special nitrile rubber for high durability. The JALAS® Tempus shoes are ESD and antistatic certified to be used in ESD protected work environments.

### CHARACTERISTICS

- Excellent shock absorption
- Excellent grip
- Perfect fit
- Extra comfortable
- Very breathable
- Extremely light

### FUNCTIONS

- Double shock absorption zones
- Oil-resistant outsole
- Anti-static properties
- Ventilating insole
- Low weight
- Bellows tongue
- Conforms with IEC 61340-5-1 (ESD)
- Soft
- Ergonomically shaped



*All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.*

## PREVENTS RISK OF

Toe injuries, nail penetration, antistatic, slipping

## PRIMARY ENVIRONMENTS OF USE

Indoors, environments with risk for outsole penetration, dry environments, clean environments

## SPECIFICATION

**TYPE** Safety footwear, Low shoes
**CATEGORY** Cat. II
**NAIL PROTECTION MATERIAL** Plasma-treated composite (PTC) textile
**FITTING** Narrow/Regular
**COLLECTION** Tempus
**UPPER MATERIAL** Microfiber, Textile
**TOECAP MATERIAL** Steel
**LINING MATERIAL** Polyester, polyamide
**INSOLE** FX2 Pro Slim
**INNERSOLE MATERIAL** Textile, Soft EVA, Polyester-based conductive thread, Double shock absorption zones in Poron® XRD®
**MIDSOLE MATERIAL** EVA
**OUTSOLE MATERIAL** Nitrile rubber outsole
**FASTENING** Laces
**COLOUR** Black, White
**NET WEIGHT, (SIZE 42)** 0.93 kg

## COMPLIANCE

CE Cat. II

EAC TP TC 019:2011

Information/UIS

EN ISO 20345:2011
S1, P, SRC

ASTM F2413-18
M/I/C
SD 35 PR

ASTM F3445-21
SR

ÖNORM Z 1259

DGUV 112-191

## FEATURES

- Anti-static properties
- Ergothan Shock Absorption System
- ESD
- Oil-resistant outsole
- Steel toecap
- Nail protection in plasma-treated composite (PTC) textile

| SIZE | | | | ARTICLE NUMBER | EAN |
|---|---|---|---|---|---|
| EU | UK | US M | US W | | |
| 35 | 2 | 3½ | 4 | 5618-35 | 6408487543449 |
| 36 | 3 | 4 | 5 | 5618-36 | 6408487543494 |
| 37 | 4 | 5 | 6 | 5618-37 | 6408487543548 |
| 38 | 5 | 5½ | 6½ | 5618-38 | 6408487543593 |
| 39 | 6 | 6½ | 7½ | 5618-39 | 6408487543647 |
| 40 | 6½ | 7½ | 8½ | 5618-40 | 6408487543692 |
| 41 | 7 | 8 | 9 | 5618-41 | 6408487543746 |
| 42 | 8 | 9 | 10 | 5618-42 | 6408487543791 |
| 43 | 9 | 9½ | 11 | 5618-43 | 6408487543845 |
| 44 | 10 | 10½ | 11½ | 5618-44 | 6408487543890 |
| 45 | 10½ | 11 | 12½ | 5618-45 | 6408487543944 |
| 46 | 11 | 12 | 13 | 5618-46 | 6408487543999 |
| 47 | 12 | 13 | 14 | 5618-47 | 6408487544040 |
| 48 | 13 | 13½ | 14½ | 5618-48 | 6408487544095 |

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com



*All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.*