Specifications

# Eaton 248873




## Catalog Number: 248873

Z-DSA2-01-SL. Rotary switch, 2p, OFF, 0 - 1

### General specifications

| | |
|---|---|
| **Product Name** | **Catalog Number** |
| Eaton Distribution parts | 248873 |
| **EAN** | **Product Length/Depth** |
| 4015082488734 | 65 mm |
| **Product Height** | **Product Width** |
| 78.5 mm | 52 mm |
| **Product Weight** | **Compliances** |
| 0.12 kg | RoHS conform |

Powering Business Worldwide

## Product specifications

Equipment heat dissipation, current-dependent

1 W

Rated operational voltage (Ue) - max

690 V

Static heat dissipation, non-current-dependent

0 W

Voltage rating - min

440 V

Width in number of modular spacings

3

Number of poles

Two-pole

Color calotte

Other

Switch type

Off switch

Rated short-time withstand current (Icw)

10 kA

Lamp socket

Other

Ambient operating temperature - max

60 °C

Ambient operating temperature - min

-40 °C

Built-in depth

60 mm

Amperage rating

20 A

Voltage type

AC

Lamp type

Other

Degree of protection

IP20

Heat dissipation capacity

## Resources

Declarations of conformity

DA-DC-03_Z-DS

Drawings

eaton-wiring-diagram-z-ds-aufdr.jpg

eaton-dimensions-mas-ds3.jpg

0 W

Heat dissipation per pole, current-dependent

0 W

Lamp power

0 W

Number of contacts (change-over contacts)

0

Number of contacts (normally closed contacts)

0

Number of contacts (normally open contacts)

2

Inscription

Other

Rated operational current for specified heat dissipation (In)

20 A

Rated Switching Capacity

0.02 kA

---

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia