Date: 25/01/2024

732.51.100 400 mbar 2 x G 1/4 female

Differential pressure gauge

Item number:	9082859
Quantity:	1 pcs.
Order code:	732.51-ZZ E-8MG240Z-AA-UZZZZA ZZ-ZZZZ 7A 3IDZ3DFHZ-IZZZZZZ12ZZZ
Overview:	732.51.100 400 mbar 2 x G 1/4 female Connector location: lower mount case: with pressure blowout disk max. static pressure: 25 bar Overpressure safety: 4 bar class 1.6 Ingress protection: IP 54 Window: laminated safety glass Permissible ambient temperature: -20...+60 °C Permissible medium temperature: -20...+100 °C Pressure Gauge Standard: International (standard Europe) *WIKA* with Serial number
Details:	Differential pressure gauge Process industry series All wellded construction Model: 732.51 Specifications according to data sheet: PM 07.05 Case: stainless steel Bezel ring: stainless steel Movement: stainless steel Case filling: without Nominal size: 100 mm Scale range: 0...400 mbar Process connection: 2 x G 1/4 female Connector location: lower mount Permissible ambient temperature: -20...+60 °C Permissible medium temperature: -20...+100 °C Accuracy class: class 1.6 max. static pressure: 25 bar Overpressure safety: 4 bar Case material: Stainless steel 1.4301 Case surface: bare Ingress protection: IP 54 Pressure Gauge Standard: International (standard Europe) Manufacturer logo: *WIKA* Serial number: with Serial number Window: laminated safety glass

© 2024 - WIKA Instruments s.a.r.l.

case: with pressure blowout disk

© 2024 - WIKA Instruments s.a.r.l.