KombiSIGN 40 / ClassicLOOK

# LED Perm. light element 24VDC MC



| | |
|---|---|
| **Part No.:** | **634.450.55** |
| **Series:** | **KombiSIGN 40** |

| MECHANICAL DATA | |
|---|---|
| Height | 59 mm |
| Diameter | 40 mm |
| Materials | PC |
| Dome colour | Clear |
| Protection category | IP66<br>IP69K |
| Working temperature minimum | -30°C |
| Working temperature maximum | +60°C |
| Weight with packaging | 40 g |
| Product weight | 29 g |

| ELECTRICAL DATA | |
|---|---|
| Operating voltage | 24V |
| Operating voltage type | DC |
| Operating voltage tolerance | +/- 10% |
| Rated operational voltage | 24 VDC |
| Rated operational current | 60 mA |
| Rated inrush current | 500 mA |
| Protection class | Protection class 3 |
| Pollution degree | 3 |
| Request to external PSU | SELV/PELV |

| OPTICAL DATA | |
|---|---|
| Light source | LED |
| Light colour | MC 7 colours |
| Optical signal image | Permanent |
| Blink frequency (Hz) | 1 Hz |
| Service life optical | 50,000 h maximum |

| APPROVAL DATA | |
|---|---|
| Conforms with CE | Yes |
| WEEE | Yes |
| Conforms with RED directive | No |
| Conforms with ATEX-directive | No |
| Conforms with CCC | No |
| Conforms with UL | cULus |
| UL Type Rating | Type 12 |
| Conforms with FCC | No |
| Conforms with IC | No |


! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

KombiSIGN 40 / ClassicLOOK

# LED Perm. light element 24VDC MC

| | |
|---|---|
| EAC certificate available | Yes |
| Conforms with UKCA (Importer) | Yes (WERMA (UK) Ltd.) |
| Conforms with CMIM | No |
| Conforms with AS-I | No |
| ICAO Certification | No |
| Conforms with DNV | No |
| Conforms with RoHS CN | No |
| Conforms with VdS | No |
| MTTF-value [years] | 429 |

## DRAWING




! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.