TECHNICAL SPECIFICATION

EVO®3 Mid Peak OneTouch™ Slip Ratchet Vented

White / AJF160-000-100



DESCRIPTION

The EVO®3 Comfort Plus helmet combines a super strong shell for superior all day protection in the widest range of environments, with the comfort benefits of the new Evolution® 3D Adjustment™ harness system. EVO®3 is a true evolution of the long-established MK®2 and MK®3 helmets. The EVO®3 retains the JSP signature styling while incorporating developments first seen in the EVO®8. Packed full of the latest protection technology and features.

OPTIONS

Black (AJF160-001-100)
Blue (AJF160-000-500)
Green (AJF160-000-300)
Grey (AJF160-000-400)
Orange (AJF160-000-800)
Pink (AJF160-003-900)
Red (AJF160-000-600)
White (AJF160-000-100)
Yellow (AJF160-000-200)

SAFETY STANDARDS

EN 397

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

Peak
Mid

Impact Resistance
50 Joules

Resistance to Molten Metals and Hot Solids Helmets (optional)
Yes

Maximum Temperature
+50˚C

Minimum Temperature
-40˚C

HDPE Shell
Yes

Recyclable
Shell

Textile
Harness

Depth Adjustment
3D Harness

Slip Ratchet
Slip

Universal Accessories Slot
Yes

Ventilation
Yes

Reflective Option
Optional

Integrated Eyewear
Optional

ID card holder
Optional

BSI Kitemark
Yes

Optional 2 point chinstrap (EN397 & EN 812 compliant)
Optional

Optional 4 point chinstrap (EN397 Compliant)
Optional

JSPCheck
Yes

Product Weight
372g

Size
53-64cm

FEATURES



Firmest Fit Available

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. Available with either the Revolution® wheel ratchet or the OneTouch™ slip ratchet.



3D Adjustment

The comfortable textile harness features unique 1-2-3 point depth settings, offering the most precise fit attainable on an industrial safety helmet.



CR2™ Reflective

Using Class RA2, high intensity reflective. CR2™ is the biggest step-up in night time visibility/reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



Accessories

A universal attachment slot enables firm fitting of a range of Surefit™ safety visors and ear defenders. EVOSpec® Integrated eyewear is also available.



Supreme Comfort

A 6-point textile cradle harness system & Chamlon™ cotton sweatband offer unrivalled comfort.



JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.



Ventilation Option

Side and rear ventilation for optimum air movement inside the shell, reducing helmet temperatures by an average 2-3 degrees.

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

LOGO

- [x] Front
- [x] Back
- [x] Sides

RANGE



VIDEOS

- www.youtube.com/watch?v=PmDMMktdotQ
- www.youtube.com/watch?v=LdxMNctXLbg

DOWNLOADS

- Image Pack (ZIP)
- doc-invincible-evo3.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.