Hard-to-find made easy®

Spec Sheet

# USB Dual VGA over Cat5 KVM Console Extender - 650 ft / 200m

*StarTech ID: SV565DUTPU*



The SV565DUTPU USB Dual VGA KVM Console Extender over CAT5 UTP lets you Operate a Dual VGA PC or KVM switch up to 650ft (200 m) away, as if it was installed locally, at high-definition 1920x1200 resolution. PC connection cables are included with this product for a ready to use solution.

The dual VGA cat5 KVM extender supports easy to use hot-key and push button commands which allow you to switch between local and remote connected systems, while console connections at both ends of your setup provide easy access to all connected systems from either location. The hot-key commands also provide video adjustment controls for optimizing picture quality over varying distances. Extending over two standard Cat 5 (or better) cables gives you the ability to use existing infrastructure wiring to achieve remote access to your server or KVM switch.

Backed by a StarTech.com 3-year warranty and free lifetime technical support.

## Applications

- Ideal for controlling a PC in an area where fan or hard drive noise is unacceptable such as a television broadcast studio
- Control/Monitor a remote server from a harsh environment where the PC would not function properly due to heat/dust/etc. (factory, warehouse, mining, etc.)
- Can act as a thin client for power users controlling powerful rack mounted servers as their desktop machines
- Use one or more servers in a server room from a remote location within the same building or campus

**Features**

- Dual VGA KVM extender at 1920x1200 resolution
- Can be used with a single computer or connected to an existing KVM switch
- Extend up to 650 ft. (200 m) using 2 industry-standard UTP network cables
- KVM console connections available on both the local and remote end
- Supports most combo keyboard and mouse sets (including Wireless)
- Intuitive hot-key commands for fine-tuning video

StarTech.com
Hard-to-find made easy®

Spec Sheet

**Technical Specifications**

| | |
|---|---|
| Warranty | 3 Years |
| Color | Black |
| Enclosure Type | Steel |
| Product Height | 40 mm [1.6 in] |
| Product Length | 155 mm [6.1 in] |
| Product Weight | 535 g [18.9 oz] |
| Product Width | 80 mm [3.1 in] |
| Audio | No |
| Cables Included | Yes |
| KVM Ports | 2 |
| Multi-Monitor | Yes |
| PC Interface | USB |
| PC Video Type | VGA |
| Rack-Mountable | No |
| IP Control | No |
| Max Transfer Distance | 200 m (656 ft) |
| Maximum Analog Resolutions | 1920x1200 |
| Supported Resolutions | 1920x1200 @ 650 ft (200m) |
| Console Interface(s) | 2 - USB A (4 pin) Female |
| Console Interface(s) | 2 - VGA (15 pin; High Density D-Sub) Female |
| Host Connectors | 2 - VGA (15 pin; High Density D-Sub) Female |
| Other Interface(s) | 2 - RJ-45 Female |
| OS Compatibility | OS independent; No software or drivers required |
| **Note** | Product weights/measurements and connector types indicate a single unit only (either Host or Remote) |
| Center Tip Polarity | Positive |
| Input Current | 0.2A |
| Input Voltage | 110 ~ 240 AC |
| Output Current | 0.6A |
| Output Voltage | 9 DC |
| Plug Type | M |
| Power Source | AC Adapter Included |
| Humidity | 0~80% RH |

| | |
|---|---|
| Operating Temperature | 0°C to 40°C (32°F to 104°F) |
| Storage Temperature | -10°C to 60°C (14°F to 140°F) |
| Shipping (Package) Weight | 2.3 kg [5 lb] |
| Included in Package | 1 - Local Unit |
| Included in Package | 1 - Remote Unit |
| Included in Package | 2 - 6 ft 2-in-1 USB VGA KVM cables |
| Included in Package | 2 - Packs Rubber Feet |
| Included in Package | 1 - Universal Power Adapter (NA/EU/UK) and AU in Australia |
| Included in Package | 1 - Instruction Manual |

**Certifications, Reports and Compatibility**

RoHS Compliant Available