



jalas® HEAVY DUTY 1268

EN ISO 20345:2011 S3, SRC, CI, HRO, HI

Learn more

Nail protection material steel, toecap material composite, PU midsole, rubber outsole, upper material PU-coated leather

CHARACTERISTICS

- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable
- Excellent shock absorption

FUNCTIONS

- ProNose toe reinforcement
- Double shock absorption zones
- Conforms with IEC 61340-5-1 (ESD)
- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Water repellent
- Specially designed details
- BOA® Fit System
- Bellows tongue
- TPU heel support
- Polstered shaft edge

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Toe injuries, nail penetration, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, warm surfaces, dirty environments, harsh environments

SPECIFICATION

TYPE Safety footwear, Low shoes
CATEGORY Cat. II
NAIL PROTECTION MATERIAL Steel
FITTING Regular
COLLECTION Heavy Duty
UPPER MATERIAL PU-coated leather
PRONOSE MATERIAL PU
TOECAP MATERIAL Composite
LINING MATERIAL Polyester, polyamide
INSOLE FX2 Climate
INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Merino wool, Double shock absorption zones in Poron® XRD®
MIDSOLE MATERIAL PU midsole
OUTSOLE MATERIAL Nitrile rubber outsole
FASTENING BOA® Fit System
COLOUR Black, Blue
NET WEIGHT, (SIZE 42) 1.32 kg

COMPLIANCE

CE Cat. II

EAC TP TC 019:2011

EN ISO 20345:2011
S3, SRC, CI, HRO, HI

ÖNORM Z 1259

DGUV 112-191

FEATURES

- Anti-static properties
- Oil-resistant outsole
- ProNose toe reinforcement
- Composite toecap
- Ergothan Shock Absorption System
- ESD
- Nail protection in steel
- Heat-resistant outsole
- Water repellent

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
35	2	3½	4	1268-35	6408487506666
36	3	4	5	1268-36	6408487506673
37	4	5	6	1268-37	6408487506680
38	5	5½	6½	1268-38	6408487506697
39	6	6½	7½	1268-39	6408487506703
40	6½	7½	8½	1268-40	6408487506710
41	7	8	9	1268-41	6408487506727
42	8	9	10	1268-42	6408487506734
43	9	9½	11	1268-43	6408487506741
44	10	10½	11½	1268-44	6408487506758
45	10½	11	12½	1268-45	6408487506765
46	11	12	13	1268-46	6408487506772
47	12	13	14	1268-47	6408487506789
48	13	13½	14½	1268-48	6408487506796

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.