NEW

racer

S1P EN ISO 20345: 2011 SRC

PRODUCT CHARACTERISTICS

Non-magnetic

Breathable

THE + PARADE TECHNOLOGY EXTRAS

DRS SYSTEM 2 — New DRS version

VPS SYSTEM — Supports the arch of the foot

Be flex 2.0 — Extra-flexible sole

SHIELD ONE — Abrasion resistance level 4



LIGHT, COMFORTABLE TRAINER

■ 7824 BLACK | SIZE: 35 TO 48

COMPOSITION

Upper	Canvas + PU
Lining	3D mesh
Toe	Polycarbonate
Insole	Mesh over PU foam. Removable.
Anti-puncture sole	Non-metallic
Sole	Dual-density polyurethane
Weight size 42*	640 g * Weight per shoe

SAFETY TABLE

	Safety toe (resistant to 200 joules)
P	Anti-puncture sole
SRC	Non-slip** sole
E	Shock-absorbent
A	Anti-static
FO	Hydrocarbon-resistant

**

Size coefficient 42	Flat		Heel	
	Standard	Parade	Standard	Parade
SRA Anti-slip ceramic / Nals (soap solution)	0,32	0,49	0,28	0,54
SRB Anti-slip steel / Glycerine (oil)	0,18	0,18	0,13	0,15

PARADE SAS • Route de Chaudron - St-Pierre-Montlimart - 49110 Montrevault-sur-Èvre - France • Ph. +33(0) 2 41 75 32 37 • Mail: contact@parade-protection.com
Parade reserves the right to modify the product's manufacturing. ©Parade, All rights reserved. Non-contractual document. Update June 2021