Balance reels with steel cables

DP series: 4-25 kg load capacity




Technical characteristics

Temperature: +5°C to +60°C

Construction: Body : Aluminium
Cable : Stainless steel

Applications: Mounting Decks, Assembling, Packaging

- Gnooved knob adjusts spring tension
- Braking device for positioning the load at different heights
- Brake stops loads from falling if spring suddenly breaks
- Swivel safety hook for ceiling mounting
- Safety cable for ceiling mounting
- Stainless steel cable with special frictionless guide
- Cable wound in tapered drum rotating on ball bearings



A (mm)	B (mm)	Length (cable (m)	Min.Load (kg)	Max.load (kg)	Weight (kg)	Parts Numbers
551	140	2	4	7	4.94	**BAL 4070DP**
551	140	2	7	10	5.3	**BAL 70100DP**
551	140	2	10	14	5.67	**BAL 100140DP**
551	140	2	14	18	6.26	**BAL 140180DP**
551	140	2	18	22	5.89	**BAL 180220DP**
551	140	2	22	25	6.53	**BAL 220250DP**

PREVOST UK - G, Tower Business Park, Commercial Rd, Darwen BB3 0FJ - United Kingdom
Tel. : (+44) 0844 800 2788 - Fax : (+44) 0844 800 2789 - E-mail : sales@prevost-ltd.co.uk - www.prevost.eu International = PREVOST SAS - - C.S. 90208 - 74942 ANNECY-LE-VIEUX CEDEX - France Tel. : +33 (4)50 64 04 45 - Fax : +33 (0)4 50 64 00 10 - E-mail : sales@prevost.eu- www.prevost.eu

This document is non-contractual. PREVOST reserves the right to modify the features of its range without prior notice.