SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· **1.1 Product identifier**

· **Trade name: 419E**

· **Other Means of Identification:** Premium Acrylic Conformal Coating

· **Related Part Number:** 419E-Liquid, 419E-55ML, 419E-1L, 419E-4L, 419E-20L

· **UFI:** 59A0-M0FT-000G-S3D5

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Application of the substance / the mixture** Protective coating for printed circuit boards

· **Uses advised against** Not available

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

MG Chemicals Ltd. (Head Office)
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA
+(1) 905-331-1396
info@mgchemicals.com

MG Chemicals
Heame House, 23 Bliston Street
Sedgely Dudley DY3 1JA.
United Kingdom
+(44) 1663 362888

MG Chemicalst Ltd.
Level 2, Vision Exchange, Building Territorials Street,
Zone 1, Central Business, District,
Birkirkara CBD 1070,
MALTA

· **Further information obtainable from:** sds@mgchemicals.com

· **1.4 Emergency telephone number:**

Members of the public seeking specific information on poisons should contact:
In England and Wales: NHS 111 - dial 111
In Scotland: NHS 24 - dial 111

Verisk 3E (Access code: 335388)
+(44) 20 3514787
+(1) 760 476 3961
UK Toll free: +(0) 800 680 0425

*

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

(Contd. on page 2)

(Contd. of page 1)



GHS08 health hazard

Repr. 2	H361d	Suspected of damaging the unborn child.



GHS07

Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**
Butan-2-one
isobutyl isobutyrate
methyl salicylate
methyl methacrylate
n-butyl methacrylate

· **Hazard statements**

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H361d	Suspected of damaging the unborn child.
H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.

· **Precautionary statements**

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing mist, vapours, or spray.
P280	Wear protective gloves, protective clothing, and eye protection.
P370+P378	In case of fire: Use CO2, powder or water spray to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents and container in accordance with local, regional, and national regulations.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

(Contd. on page 3)

(Contd. of page 2)

· **Determination of endocrine-disrupting properties**		
78-93-3	Butan-2-one	List II

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**		
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3	Butan-2-one Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	46.0%
CAS: 97-85-8 EINECS: 202-612-5	isobutyl isobutyrate Flam. Liq. 3, H226; STOT SE 3, H335; Aquatic Chronic 3, H412	24.0%
CAS: 119-36-8 EINECS: 204-317-7 Index number: 607-749-00-8	methyl salicylate Repr. 2, H361d; Acute Tox. 4, H302; Skin Sens. 1B, H317 ATE: LD50 oral: 890 mg/kg	1.0%
CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	0.1%
CAS: 97-88-1 EINECS: 202-615-1 Index number: 607-033-00-5	n-butyl methacrylate Flam. Liq. 3, H226; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	0.1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **After inhalation:**
Remove person to fresh air and keep comfortable for breathing.
If feeling unwell: Call a POISON CENTRE or doctor.
If exposed or concerned: Get medical advice/attention.

· **After skin contact:**
Wash with plenty water.
If skin irritation or rash occurs: Get medical advice or attention.
Take off contaminated clothing and wash it before reuse.
If exposed or concerned: Get medical advice or attention.

· **After eye contact:**
Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice or attention.

· **After swallowing:**
Rinse mouth.
Do NOT induce vomiting.
If symptoms persist consult doctor.
If exposed or concerned: Get medical advice or attention.

· **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.

(Contd. on page 4)

(Contd. of page 3)

· **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

*

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**
· **Suitable extinguishing agents:**
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture**
Vapors are heavier than air. Vapors may travel to sources of ignition near the ground. They can cause flash fire or ignite explosively.
Prevent fire-fighting wash from entering waterway or sewer system.
· **Hazardous combustion products:**
Carbon Oxides (COx)
other toxic fumes

· **5.3 Advice for firefighters**
· **Protective equipment:** Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Remove or keep away all sources of extreme heat or open flames.
Avoid breathing mist, spray, or vapors.

· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Collect liquid in a sealable, chemical-resistant container.
Wash residue with a paper towel and place dirty towels in container.
Use soap and water to remove the last traces of residue.

· **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**
Wear protective gloves and eye protection.
Wash hands and exposed skin thoroughly after handling.
Take off contaminated clothing and wash it before reuse.
Contaminated work clothing should not be allowed out of the workplace.
Avoid breathing mist, spray, or vapors.
Use only outdoors or in a well-ventilated area.
Obtain, read and follow all safety instructions before use.

(Contd. on page 5)

(Contd. of page 4)

· **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Use explosion-proof apparatus / fittings and spark-proof tools.
Ground and bond container and receiving equipment.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Keep in a dry and clean area, away from incompatible substances

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Store locked up.

· **7.3 Specific end use(s)** See section 1.2

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**	
78-93-3 Butan-2-one	
WEL	Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV
80-62-6 methyl methacrylate	
WEL	Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

· **Ingredients with biological limit values:**	
78-93-3 Butan-2-one	
BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one

· **Additional information:**
The lists valid during the making were used as basis.
Refer to the national or regional occupational exposure limit regulation for abbreviations and acronyms.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

· **Respiratory protection:**
Advice should be sought from respiratory protection specialists.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

(Contd. on page 6)

(Contd. of page 5)

· **Hand protection**
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves: EN374

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Safety glasses or tightly sealed goggles: EN 166

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **Physical state**	Liquid
· **Form:**	Viscous
· **Colour:**	Clear
· **Odour:**	Sweetish
· **Odour threshold:**	Not determined.
· **Melting point/freezing point:**	Undetermined.
· **Boiling point or initial boiling point and boiling range**	80 °C
· **Flammability**	Highly flammable.
· **Lower and upper explosion limit**	
· **Lower:**	1.8 Vol %
· **Upper:**	11.6 Vol %
· **Flash point:**	-9 °C (78-93-3 Butan-2-one)
· **Auto-ignition temperature:**	400 °C
· **Decomposition temperature:**	Not determined.
· **pH**	Not determined.
· **Viscosity:**	
· **Kinematic viscosity at 20 °C**	>20.5 mm²/s
· **Dynamic:**	Not determined.
· **Solubility**	
· **water:**	Partly miscible.
· **Partition coefficient n-octanol/water (log value)**	Not determined.
· **Vapour pressure at 20 °C:**	60 hPa
· **Relative density at 25 °C:**	0.88
· **Vapour density (air=1):**	>2.14

(Contd. on page 7)

(Contd. of page 6)

· **Particle characteristics**	Not applicable.

· **9.2 Other information**

· **9.2.1 Information with regard to physical hazard classes**	
· **Flammable liquids**	Highly flammable liquid and vapour.
· **9.2.2 Other safety characteristics**	
· **Evaporation rate**	Not determined.
· **Ignition temperature:**	Product is not selfigniting.
· **Explosive properties:**	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· **Solvent content:**	
· **Organic solvents:**	46.00 %
· **VOC (EC)**	46.00 %
· **Solids content:**	28.9 %

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

· **10.2 Chemical stability** Chemically stable at normal temperatures and pressures.
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions** No dangerous reactions known.

· **10.4 Conditions to avoid**
Avoid open flames, excessive heat, sparks, ignition sources, and incompatible substances.

· **10.5 Incompatible materials:**
Oxidizing agents
Strong acids
Strong bases

· **10.6 Hazardous decomposition products:**
No dangerous decomposition products known.
Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
· **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**		
ATE (Acute Toxicity Estimates)		
Oral	LD50	89,000 mg/kg (ATE)

78-93-3 Butan-2-one		
Oral	LD50	2,737 mg/kg (rat)
Dermal	LD50	6,480 mg/kg (rabbit)
Inhalative	LC50/ 8 h	23,500 mg/m3 (rat)

(Contd. on page 8)

(Contd. of page 7)

97-85-8 isobutyl isobutyrate		
Oral	LD50	7,712 mg/kg (rat)
Dermal	LD50	10,626 mg/kg (rabbit)
119-36-8 methyl salicylate		
Oral	LD50	890 mg/kg (ATE) 887 mg/kg (rat)
80-62-6 methyl methacrylate		
Oral	LD50	7,872 mg/kg (rat)
97-88-1 n-butyl methacrylate		
Oral	LD50	22,600 mg/kg (rat)
Dermal	LD50	11,300 mg/kg (rabbit)
Inhalative	LC50/4 h	4,910 mg/L (rat)

· **Primary irritant effect:**
· **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
· **Serious eye damage/irritation** Causes serious eye irritation.
· **Respiratory or skin sensitisation** May cause an allergic skin reaction.
· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
· **Carcinogenicity** Based on available data, the classification criteria are not met.
· **Reproductive toxicity** Suspected of damaging the unborn child.
· **STOT-single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.
· **STOT-repeated exposure** Based on available data, the classification criteria are not met.
· **Aspiration hazard** Based on available data, the classification criteria are not met.
· **Summary of Effects and Symptoms by Routes of Exposure**
· **Eyes:** redness, serious irritation
· **Skin:**
rash, allergic contact dermatitis
dry skin
· **Inhalation:**
cough
headache
irritation of the respiratory tract
· **Swallowed:**
abdominal pain
nausea, vomiting
headache
cough
drowsiness
dizziness
· **Additional toxicological information:**
· **Delayed and immediate effects as well as chronic effects from short and long-term exposure**
Prolonged or repeated exposure may defat skin and cause skin dryness and cracking, and local redness and discomfort.
Prolonged or repeated exposure may cause skin allergies.

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**		
78-93-3	Butan-2-one	List II

(Contd. on page 9)

(Contd. of page 8)

SECTION 12: Ecological information

· **12.1 Toxicity**
· **Aquatic toxicity:** No further relevant information available.

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.

· **12.7 Other adverse effects**
· **Additional ecological information:**
· **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation** This material and its container must be disposed of as hazardous waste.

· **European waste catalogue**	
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP14	Ecotoxic

· **Uncleaned packaging:**
· **Recommendation:**
Containers may still present a chemical hazard/ danger when empty.
Dispose of contents in accordance with all local, regional, national, and international regulations.
Where possible retain label warnings and SDS and observe all notices pertaining to the product.

SECTION 14: Transport information

· **14.1 UN number or ID number**	
· **ADR, IMDG, IATA**	UN1263
· **14.2 UN proper shipping name**	
· **ADR, IMDG**	PAINT
· **IATA**	Paint

(Contd. on page 10)

(Contd. of page 9)

· **14.3 Transport hazard class(es)**

· **ADR, IMDG, IATA**



· **Class**	3 Flammable liquids.
· **Label**	3

· **14.4 Packing group**

· **ADR, IMDG, IATA**	II

· **14.5 Environmental hazards:** Not applicable.

· **14.6 Special precautions for user** Not applicable.

· **Hazard identification number (Kemler code):**	33
· **EMS Number:**	F-E,S-E
· **Stowage Category**	B

· **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.

· **Transport/Additional information:**



Limited Quantity

419E-55ML, 419E-1L, 419E-4L

· **ADR**

· **Limited quantities (LQ)**	5L
· **Excepted quantities (EQ)**	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· **Transport category**	2
· **Tunnel restriction code**	D/E

· **IMDG**

· **Limited quantities (LQ)**	5L
· **Excepted quantities (EQ)**	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN 1263 PAINT, 3, II

(Contd. on page 11)

(Contd. of page 10)

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Poisons Act**

· **Regulated explosives precursors (Part 1)**
None of the ingredients is listed.

· **Regulated poisons (Part 2)**
None of the ingredients is listed.

· **Reportable explosives precursors (Part 3)**
None of the ingredients is listed.

· **Reportable poisons (Part 4)**
None of the ingredients is listed.

· **Directive 2012/18/EU**
- · **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- · **Seveso category** P5c FLAMMABLE LIQUIDS
- · **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- · **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**
None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

· **Classification according to Regulation (EC) No 1272/2008**	
Flammable liquids	On basis of test data
Serious eye damage/irritation Skin sensitisation Reproductive toxicity Specific target organ toxicity (single exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· **Department issuing SDS:** Regulatory department
· **Contact:** sds@mgchemicals.com
· **Date of previous version:** 23.07.2024

(Contd. on page 12)

(Contd. of page 11)

· **Version number of previous version:** 5.00

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**