

Due to its wide operating voltage and automatic synchronisation, the Solex beacon is a flexible solution for all types of alarm and monitoring systems.

Powered by Xenon technology, the Solex is a cost effective solution that can compliment audible alarms in high-noise environments.


Features

- 3 light output variants
- 5 lens colour variants
- 9-60V
- Anti-tamper switch option

Benefits

- Manage the current to suit your application
- Use for fire warning or general signalling
- Wide operating voltage for maximum flexibility
- For use where security is an issue (tamper switch)
- Increased visibility from wide viewing angle of flash
- Synchronised flash

Dimensions




Technical Specification

Voltage	9 - 60Vdc
Current	40 / 88 / 240mA
Light Output	3 / 10 / 15cd
Flash Rate	Single flash @ 1Hz 60FPM
Monitoring	Reverse polarity
Temperature	- 25°C to + 70°C
Protection	IP21C (s)* IP65 (d)*
Construction	Base ABS, FR, PC lens
Weight	0.1Kg
Colour	Red or white base
Flash colour	Red, amber, blue, green or white

(s)* Shallow Base
(d)* Deep / U Base

Solex Amber - White Base



Catalogue Numbers

Reference	Cat No	Description
SO/R/SR/3C	531025FULL-0061	Solex Beacon, Red Lens, Red Body, Shallow Base, 3cd
SO/R/DR/3C	531025FULL-0087	Solex Beacon, Red Lens, Red Body, Deep Base, 3cd
SO/R/SR/10C	531024FULL-0060	Solex Beacon, Red Lens, Red Body, Shallow Base, 10cd
SO/R/DR/10C	531024FULL-0088	Solex Beacon, Red Lens, Red Body, Deep Base, 10cd
SO/R/SR/15C	531028FULL-0064	Solex Beacon, Red Lens, Red Body, Shallow Base, 15cd
SO/R/DR/15C	531028FULL-0111	Solex Beacon, Red Lens, Red Body, Deep Base, 15cd

VdS