Inline Fuseholder, 5x20 / 6.3x32 mm

new



5x20 mm with wire leads, 8601.2001.08



5x20 mm, 8601.2000



6.3x32 mm, 8601.2005

32 VAC · 2.5 W / 6.3 A · 32 VDC

Description
- Inline Fuseholder

Applications
- Automotive applications/aftermarket
- Audio aftermarket
- Lighting aftermarket


Weblinks
pdf-datasheet, html-datasheet, General Product Information, Approvals, CE declaration of conformity, RoHS, CHINA-RoHS, REACH, e-Shop, SCHURTER-Stock-Check, Distributor-Stock-Check, Detailed request for product


Technical Data

Shock-Safe Category	PC2
Fuse-Link	5 x 20 or 6.3 x 32 mm
Mounting	In-line
Terminal	Wires
Rated Voltage	32 VAC , 32 VDC
Rated current	6.3 A
Rated Power Acceptance IEC	2.5 W / 6.3 A @ Ta 23 °C
Degree of Protection	IP 40
Admissible Ambient Air Temp.	-40 °C to +85 °C
Material: Socket	Thermoplastic, UL 94V-0
Material: Terminals	Tin-Plated Brass
Storage Conditions	0 °C to 60 °C, max. 70% r.h.


Contact Resistance	< mΩ at 20 mV

Dimension






5x20 mm



6.3x32 mm

Mounting Instruction



All Variants

Holder	Fuse-Link	Wire	Colour Wire	Length [mm]	Order Number	
●	5 x 20mm	-	-	-	8601.2000	▮
●	5 x 20mm	18 AWG	dark pink	200	8601.2001.08	▮
●	6.3 x 32mm	-	-	-	8601.2005	▮
●	6.3 x 32mm	14 AWG	pink	200	8601.2005.08	

▮ Most Popular.

Availability for all products can be searched real-time:http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Wire Length: 8"

Packaging Unit Bulk (50 pcs.)

03.03.2015

The specifications, descriptions and illustrations indicated in this document are based on current information. All content is subject to modifications and amendments. Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability and test each product selected for their own applications.