Date: 12/04/2023

RLS-1000; Guide tube length: 500 mm; 1 switching output

RLS-1000; Guide tube length: 500 mm; 1 switching output

Item number: 48769730

Quantity: 1 pcs.

Order code: RLS-10003M303500ZZZZZZZZZZZZZZZZZZZ1CZ8P050004Z1
Z1W101ARS1ZL4

Overview:
RLS-1000; Guide tube length: 500 mm; 1 switching output
Magnetic float switch, Stainless steel version Model RLS-1000
Output Signal: 1 switching output
max. switching power: n.o./n.c.: AC 230 V; 100 VA; 1 A / DC 230 V; 50 W; 0,5 A
max. switching power: Changeover/SPDT: AC 230 V; 40 VA; 1 A / DC 230 V; 20 W; 0,5 A
Unit of measure switching position: mm
Switching function - Switch output 1 : changeover / SPDT
Switch position - Switch output 1 : 350 mm
Electrical connection: Angular connector DIN 175301-803 A, IP65
pin assignment el. connection: see product label
Process connection: Flange DN 50, form B per EN 1092-1 (DIN 2527), PN 16, installation from outside
Guide tube length: 500 mm mm
medium temperature: -30 °C ... 80 °C
Wetted parts: Stainless steel 1.4571
Float: Cylindrical float Ø 44 mm, 1.4571, PN16
Specifications according to data sheet: LM 50.03

Details:
RLS-1000; Guide tube length: 500 mm; 1 switching output
Magnetic float switch, Stainless steel version Model RLS-1000
Output Signal: 1 switching output
max. switching power: n.o./n.c.: AC 230 V; 100 VA; 1 A / DC 230 V; 50 W; 0,5 A
max. switching power: Changeover/SPDT: AC 230 V; 40 VA; 1 A / DC 230 V; 20 W; 0,5 A
Unit of measure switching position: mm
Switching function - Switch output 1 : changeover / SPDT
Switch position - Switch output 1 : 350 mm
Electrical connection: Angular connector DIN 175301-803 A, IP65
pin assignment el. connection: see product label
Process connection: Flange DN 50, form B per EN 1092-1 (DIN 2527), PN 16, installation from outside
Guide tube length: 500 mm mm
medium temperature: -30 °C ... 80 °C
Wetted parts: Stainless steel 1.4571
Float: Cylindrical float Ø 44 mm, 1.4571, PN16
Specifications according to data sheet: LM 50.03

© 2023 - WIKA Instruments s.a.r.l.