*Date: 17/04/2023*

# TR11-C, 1xPt100, 3-w, Cl.A, -30/250°C (F), T15, Removable

## TR11-C RTD assembly with fabricated threaded protection tube (tubing)

Item number: 48791727

Quantity: 1 pcs.

Order code: TR11-C-ZZZZ-13HT-BS1A-5L-ATGNDL90150ZZZ10178-ZZZZR12 018830LZ-Z1-Z-WIKA0-ZZ
T15.H-ZZZZZ-ZKK13C-P00000P00100-DZ000ZZ-ZZ A15 ZWIKA0W01SSZ

Overview:
TR11-C, 1xPt100, 3-w, Cl.A, -30/250°C (F), T15, Removable
Diameter measuring insert: 3 mm Stainless steel 316L

Head / housing: BS (Alu), Strd.-gland, M20 x 1.5
Transmitter: T15, Digital-transmitter, 4…20 mA, programmable on insert

Protection tube: Straight, thread
316L, Ø 6x1 mm, M24 x 1,5 - 1/2NPT, MH=Without U1=150mm

Sealing: Without
Specifications according to data sheet: TE 60.03
Measuring insert length (spare) [l5]: 188 mm

Protection tube total length (spare) [L]: 178 mm

Thermowell specials: Without

T15.H, Ex: Without, customer spec. Pt100, 3w, +0...+100°C

Specifications according to data sheet: TE 15.01
Configuration sensor: Pt100
Output signal: 4 ... 20 mA, 2-wire-design
Tamb: Standard -40...85°C
Transmitter Signalling of error: Down scale 3,5 mA

Details:
TR11-C RTD assembly with fabricated threaded protection tube (tubing)

Specifications according to data sheet: TE 60.03
1xPt100, 3-wire
Class A, IEC 60751
Temperature range of selected class: -30...+250°C
BS, Aluminum, flat cover
Cable entry: Standard cable entry
Thread size cable entry: M20 x 1.5
Transmitter: T15, Digital-transmitter, 4…20 mA, programmable
Protection tube: Straight, thread

*© 2023 - WIKA Instruments s.a.r.l.*

Connection to neck tube: M24 x 1,5
Protection tube diameter: 6x1 mm
Protection tube material: Stainless steel 316L
Process connection: 1/2 NPT
Insertion length [A] [U1]: 150 mm
Neck length [MH/N]: Without
Material measuring insert: Stainless steel 316L
Sealing: Without
Mounting-position transmitter: Measuring insert
Measuring insert: Removable
Diameter measuring insert: 3 mm
Thermowell specials: Without
Digital temperature transmitter for resistance sensors T15

Specifications according to data sheet: TE 15.01
Output signal: 4 ... 20 mA, 2-wire-design
Design: Head
Explosion protection: Without
Permissible ambient temperature transmitter: Standard -40...85°C
Configuration: Customer's specification
Configuration sensor: Pt100
Input configuration: 3-wire
Unit: °C
Measuring range start value - sign: Plus (incl. 0)
Measuring range start value: 0
Measuring range end value - sign: Plus (incl. 0)
Measuring range end value: 100
Transmitter Signalling of error: Down scale 3,5 mA

© 2023 - WIKA Instruments s.a.r.l.