KG200S11

Foot switch, K series, one pedal, with free actuation, plastic body, close. Contacts 1NO+1NC snap action



Product designation			One pedal, with free actuation - with cover
Product type designation			KG200
General characteristics			
Material			
	Housing		Self-extinguishing double-insulation polymer thermoplastic
Contact characteristics			
Type of contact			1NO+1NC Snap action
Thermal current Ith		A	10
IEC/EN 60947-5-1 designation			A600 Q600
Rated insulation voltage Ui		V	690
Rated impulse withstand voltage Uimp		kV	6
Insulation class			II
Short-circuit protection with fuse		Class/A	10 gG fuse
IEC Conventional free air thermal current Ith		A	10
Resistance per pole (average value)		mΩ	<10
Mechanical features			
Tightening torque (Max)			
	Contact terminals		
		Nm	1
		lbin	0.74lbft
Cable connection			Self-releasing screw terminal
Cable entry			1 x M20
Operations			
Mechanical life		cycles	>10000000
Ambient conditions			
Temperature			
	Operating temperature		
	min	°C	-25
	max	°C	+70
	Storage temperature		
	min	°C	-40
	max	°C	+70
Resistance & Protection			
IP degree			
	Terminals		IP20
	Body housing		IP54
Pollution degree			3
Dimensions			

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

KG200S11

Foot switch, K series, one pedal, with free actuation, plastic body, close. Contacts 1NO+1NC snap action



Certifications and compliance

Compliance

	EN 60447.
	IEC/EN 60204-1
	IEC/EN 60947-1
	IEC/EN 60947-5-1

Certificates

	EAC

ETIM classification

ETIM 8.0	EC001258 - Foot switch

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding