

Model Number

V31-GM-5M-PVC

M8, 4-pin socket, PVC cable

Features

- Knurled nut suitable for tool assembly
- Immunity to vibration, with mechanical latching
- Gold-plated and machined contacts

Dimensions



Technical data

General specifications		
Number of pins		4
Connection 1		female connector
Construction type 1		straight
Threading 1		M8
Connection 2		cable end
Electrical specifications		
Operating voltage	U_B	max. 30 V AC/DC
Operating current		max. 3 A
Volume resistance		< 5 mΩ
Ambient conditions		
Ambient temperature		Body: -40 ... 90 °C (-40 ... 194 °F) cable, fixed: -25 ... 70 °C (-13 ... 158 °F) cable, flexing: -5 ... 70 °C (23 ... 158 °F)
Pollution Degree		3
Mechanical specifications		
Contact elements		spring-loaded contact socket
Pin diameter		1 mm
Protection degree		IP67
Material		
Contacts		CuSn / Au
Contact surface		Au
Body		TPU, black
Cable		PVC
Slotted nut		Diecast zinc
Core insulation		PVC
Cable		fine-strand, flexible
Sheath diameter		Ø 4.3 mm
Bending radius		> 15 x cable diameter, induced > 10 x cable diameter, fixed
Color		grey
Cores		4 x 0.25 mm^2
Conductor construction		14 x 0.15 mm Ø
Length	L	5 m
Flammability		
Contact material		HB
Housing		V-2
Compliance with standards and directives		
Standard conformity		
Protection degree		EN 60529:2000
Standards		IEC 61076-2-104:2008
Flammability		Grip: UL 94

Electrical connection



Release date: 2013-03-28 19:44 Date of issue: 2013-03-28 109030_eng.xml

Subject to modifications without notice
Copyright Pepperl+Fuchs