TECHNICAL SPECIFICATION

EVO® Goggle Double Lens

Clear MistResist+ Inner Lens & Hardia+ Anti-Scratch Outer Lens / AGM020-823-000



DESCRIPTION

Engineered to offer outstanding performance, compatibility and comfort, with the option to fit an RX insert enabling safe use of prescription lenses. The double lens provides optimum fogging resistance, with NBR foam surround for enhanced comfort and improved fit.

OPTIONS

Clear MistResist+ Inner Lens & Hardia+ Anti-Scratch Outer Lens (AGM020-823-000)

SAFETY STANDARDS

EN 166 • EN 170

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

RADIATION PROTECTION BREAKDOWN filtering effect Scale Number
2C

Manufacturer's Trademark
JSP Dagger

Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles.
B

Protection from Liquid Droplets
3

Resistance to Molten Metals and Hot Solids Helmets (optional)
9

Resistance to fogging (optional)
N

Lens Material
Polycarbonate Outer Lens - Acetate Inner Lens

LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1.2

Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1

The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5˚C and +55˚C) Optional
T

Protection from Large Dust Particles (up to 40 um grain size)
4

Resistance to Surface Damage by Fine Particles (optional)
K

RX Insert
Optional

Product Weight
106g

FEATURES



Compatibility

Low profile design means the EVO® Goggle can be worn with an industrial safety helmet or bumpcap.



Comfort

Foam surround on the goggle housing for comfort and to ensure a good fit across a wide range of facial profiles.



RX Inserts

RX inserts are available for the EVO® Goggle range, for combined prescription and safety eyewear. Inserts can be taken to an optician for glazing with corrective lenses.



Improved Anti-Fog Protection

Double lens for improved anti-fog performance, with Hardia+™ coated polycarbonate outer lens and Mist Resist+™ acetate inner lens.

RANGE

evoGoggle™ evolution

DOWNLOADS

Image Pack (ZIP)
doc-evo-double-lens-goggle.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.