SKINDICHT® MR-M ATEX

SKINDICHT® MR-M ATEX, reducer, enables the use of cable glands with smaller connection threads than the existing threaded holes



Benefits

Enables the use of cable glands with smaller connection threads than the existing threaded holes
With guide slot for O-ring
Assembling with a wrench

Application range

Equipment group II / category 2G+1D
Devices, machines and apparatus
For mobile applications in offshore and marine industries
Chemical and petrochemical industry

Design

Metric connection thread according to DIN EN 60423
Basis for technical information DIN IEC 62444

Technical Data

Classification:	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: Cable gland
Certifications:	CE 0637 Ex II 2G Ex eb IIC Ex II 1D Ex ta IIIC IECEx IBE 13.0028X DIN EN 60079-0DIN EN 60079-7DIN EN 60079-31
Material:	Body: Nickel-plated brass O-ring: NBR
Temperature range:	-30 °C to +90 °C

Last Update (22.03.2017)
©2017 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

SKINDICHT® MR-M ATEX

Note
Photographs are not to scale and do not represent detailed images of the respective products.
* Prices are net prices without VAT and surcharges. Sale to business customers only.

Last Update (22.03.2017)
©2017 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

LAPP GROUP

PRODUCT INFORMATION

SKINDICHT® MR-M ATEX

Article number	Thread, male M1	Thread, inner M2	Overall height (mm)	Thread length, D (mm)	Outer Ø (mm)
SKINDICHT® MR-M ATEX					
52104570	16 x 1.5	12 x 1.5	10.5	5	19
52104571	20 x 1.5	16 x 1.5	13	6	24.5
52104572	25 x 1.5	20 x 1.5	15	7	30.1
52104573	32 x 1.5	25 x 1.5	16.5	8	37.2
52104574	40 x 1.5	32 x 1.5	16.5	8	45.6
52104575	50 x 1.5	40 x 1.5	19.5	10	55.3
52104576	63 x 1.5	50 x 1.5	18.5	8.5	71.3

Last Update (22.03.2017)
©2017 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16