Electromechanical sensors for pressure control OsiSense XM

Catalogue



Simply easy!™

Telemecanique Sensors

Contents

Electromechanical pressure and vacuum switches OsiSense XM

Selection guide . . . . . *pages 2 to 5*

- **General** ..... *pages 6 to 11*
- **Operating curves** ..... *pages 12 to 15*

Electromechanical pressure and vacuum switches for control circuits

For controlling the pressure of air, water, hydraulic oils, corrosive fluids and viscous products

- **Presentation and setting** ..... *page 16*
- **Characteristics** ..... *page 17*
- **References**
  - Pressure and vacuum switches XMLA, B, C and D ..... *pages 18 to 67*
  - Accessories and replacement parts ..... *page 68*
  - Dimensions ..... *pages 69 to 71*
  - Components materials of units in contact with fluid ..... *pages 72 and 73*

For controlling the pressure of air, water, hydraulic oils and corrosive fluids

- **Presentation and setting** ..... *page 74*
- **Characteristics** ..... *page 75*
- **References**
  - OsiSense ACW, sizes from: 0.7 to 131 bar ..... *pages 76 and 77*
  - OsiSense ADW, sizes from: 69 to 340 bar ..... *pages 78 and 79*
  - Dimensions ..... *pages 80 and 81*

For controlling the pressure of air and water

- **Presentation and setting** ..... *page 82*
- **Characteristics** ..... *page 83*
- **References**
  - OsiSense XMX and XMA, sizes from: 6 to 25 bar ..... *pages 84 and 85*
  - Accessories and replacement parts ..... *page 86*
  - Dimensions ..... *page 87*

Electromechanical pressure switches for power circuits

For controlling the pressure of water

- **Presentation and setting** ..... *page 88*
- **Characteristics** ..... *page 89*
- **References**
  - OsiSense FGT, FSG and FYG ..... *pages 90 to 92*
  - Dimensions ..... *page 93*

For controlling the pressure of air and water

- **Presentation** ..... *page 94*
- **Characteristics** ..... *page 95*
- **References**
  - OsiSense XMP, IP 54, sizes from: 6 to 25 bar ..... *pages 96 to 101*
  - OsiSense XMP, IP 65, sizes from: 6 to 25 bar ..... *pages 102 and 103*
  - Accessories and replacement parts ..... *page 104*
  - Dimensions ..... *page 105*

- **Product reference index** ..... *pages 106 and 107*

Electromechanical sensors for pressure control

OsiSense XM

Applications	Type of installation	**Control circuits**		**Control circuits**	
	Fluids controlled	**Air, water, hydraulic oils, corrosive fluids, viscous products**		**Air, water, hydraulic oils, corrosive fluids, viscous products**	**Air, hydraulic oils, corrosive fluids**
	Type of operation	**Detection of a single threshold (fixed differential)**	**Regulation between 2 thresholds (adjustable differential)**	**Dual stage switches Detection at each threshold (fixed differential)**	**Regulation between 2 thresholds (adjustable differential)**
							
Fluid characteristics		Air, fresh water, corrosive fluids, viscous products, up to 160°C Sea water, up to 30 °C, depending on model		Air, fresh water, corrosive fluids, viscous products, up to 160°C Sea water, up to 30 °C, depending on model	Air, oils and other non corrosive fluids (- 73…+ 125°C)	Oils and other fluids (- 25…+ 120 °C) Only oils, including synthetic oils, (- 30…+ 125 °C), depending on model
Sizes		- 1 bar…500 bar (- 14.5 psi…7250 psi)		- 1 bar…500 bar (- 14.5 psi…7250 psi)	0.7 bar…131 bar (10.15 psi…1900 psi)	69 bar…340 bar (1000 psi…4930 psi)
Dimensions of case (mm)	Width x height x depth	35 x 68 x 75	46 x 68 x 85	45 x 68 x 85	88 x 88 x 68	
Type of contacts		1 CO single-pole, snap action	2 CO single-pole, simultaneous, snap action	2 CO single-pole, staggered, snap action	1 CO or 2 CO single-pole, snap action	
Degree of protection		IP 66: switches with terminal connections IP 65: switches with connector	IP 66: switches with terminal connections	IIP 66: switches with terminal connections	IP 65	
Electrical connection		Connector : ■ EN 175301-803-A (ex-DIN 43650A), 4-pin male. Screw terminals: ■ 1 tapped entry M20 x 1.5 mm for ISO cable gland or ■ 1 tapped entry 1/2”-14 NPT for cable gland, depending on model.		Connector : ■ EN 175301-803-A (ex-DIN 43650A), 4-pin male. Screw terminals: ■ 1 tapped entry M20 x 1.5 mm for ISO cable gland or ■ 1 tapped entry 1/2”-14 NPT for cable gland, depending on model.	Screw terminals: ■ 1 tapped entry M20 x 1.5 mm for ISO cable gland or ■ 1 tapped entry for n° 13 cable gland, depending on model	
Fluid connection		G 1/4 (female) 1/4” - 18 NPTF (female) G 1¼” (female) for viscous products		G 1/4 (female) 1/4” - 18 NPTF (female) G 1¼” (female) for viscous products	G 1/4 (femelle)	G 3/8 (female)
Type reference		**XMLA**	**XMLB**	**XMLC**	**XMLD**	**ACW**	**ADW**
Pages		18 to 67		18 to 67	76 and 77	78 and 79

Other versions

Electromechanical pressure and vacuum switches with alternative tapped cable entries and/or fluid entries: NPT etc. Please consult our Customer Care Centre.

Electromechanical sensors for pressure control

OsiSense XM

Applications	Type of installation	**Control circuits**		**Power circuits**			
	Fluids controlled	**Air, water**		**Water**			**Air, water**
	Type of operation	**Regulation between 2 thresholds (adjustable differential)**		**Detection of a single threshold (fixed differential)**	**Regulation between 2 thresholds (adjustable differential)**		
							
Fluid characteristics		Air, fresh water, sea water (0…+ 70°C)		Fresh water, sea water (0…+ 70°C)			Air, fresh water, sea water (0…+ 70°C)
Sizes		6 bar, 12 bar and 25 bar (87 psi, 174 psi and 362.5 psi)		4.6 bar (66.7 psi)		7 bar (101.5 psi) / 10.5 bar (152.3 psi)	6 bar, 12 bar and 25 bar (87 psi, 174 psi and 362.5 psi)
Dimensions of case (mm)	Width x height x depth	57 x 78 x 97.5		73 x 73 x 102	72 x 77 x 106	72 x 73 x 102	57 x 78 x 97.5
Setting of switching points		Internal screws	External screws	Internal screws			
Type of contacts		1 CO single-pole, snap action		2 NC snap action			2 NC or 3 NC snap action
Degree of protection		IP 54		IP 20/IP 65			IP 54 or IP 65, depending on model
Electrical connection		Screw terminals: ■ 2 entries tapped for n° 13 cable gland, ■ one fitted with n° 13 cable gland, ■ one fitted with blanking plug.		Screw terminals: ■ 2 cable entries with grommet or ■ 2 cable entries with n° 13 cable gland			Screw terminals: ■ 2 entries incorporating n° 13 cable gland or without cable gland, depending on model
Fluid connection		G 1/4 or 4 x G 1/4 (female), depending on model		G 1/4 or R 1/4 (female or male)			G 1/4, G 3/8 or 4 x G 1/4 (female), depending on model
Type reference		**XMX**	**XMA**	**FTG●, FTG●NE**	**FSG●, FSG●NE**	**FYG22, FYG22NE**	**FYG32, FYG32NE** / **XMP**
Pages		84	85	90 to 92			96 to 103

Other versions

Electromechanical pressure switches with alternative tapped cable entries and/or fluid entries: ISO, NPT, etc. Please consult our Customer Care Centre.

Electromechanical pressure and vacuum switches
OsiSense XM

Function
The function of pressure and vacuum switches is the control or regulation of pressure or vacuum levels in hydraulic or pneumatic systems.
They transform the pressure change into a digital electrical signal when the preset switching points are reached.

Switches for power circuits
Switches with power electrical contacts, either 2-pole or 3-pole, designed for direct switching of single-phase or 3-phase motors (pumps, compressors, etc.).

Switches for control circuits
Switches with standard electrical contacts, designed for control of contactors, relays, power valves, PLC inputs, etc.

Pressure switch operating principle
Detection of a single threshold
The switches for detection of a single threshold (fixed differential) have a single adjustable setting point (PH). The differential between the high and low points (PH - PB) depends upon the natural characteristics of the switch. It is not adjustable.



Example: contact schematics of XMLA



— Adjustable value
--- Non adjustable value

PH = High point
PB = Low point

Regulation between 2 thresholds
The switches for regulation between 2 thresholds (adjustable differential) have both a high point setting (PH) and a low point setting (PB). Both of these points can be independently adjusted.



Example: contact schematics of XMLB



— Adjustable value

PH = High point
PB = Low point

Detection of 2 thresholds
The dual stage switches, for detection at each threshold, have an adjustable high point setting for each stage (PH1 and PH2). Both of these points can be independently adjusted. For both stages, the differential between the high point and the low point (PH1 - PB1 and PH2 - PB2) depends upon the natural characteristics of the switch. It is not adjustable.



Example: contact schematics of XMLD



— Adjustable value
--- Non adjustable value

PH = High point
PB = Low point



Electromechanical pressure and vacuum switches
OsiSense XM

Vacuum switch operating principle

Detection of a single threshold

The switches for detection of a single threshold (fixed differential) have a single adjustable setting point (PH). The differential between the high and low points (PH - PB) depends upon the natural characteristics of the switch. It is not adjustable.



Example: contact schematics of XMLA



— Adjustable value
--- Non adjustable value

PH = High point
PB = Low point

Regulation between 2 thresholds

The switches for regulation between 2 thresholds (adjustable differential) have both a high point setting (PH) and a low point setting (PB). Both of these points can be independently adjusted.



Example: contact schematics of XMLB



— Adjustable value

PH = High point
PB = Low point

Detection of 2 thresholds

The dual stage switches, for detection at each threshold, have an adjustable high point setting for each stage (PH1 and PH2). Both of these points can be independently adjusted.
For both stages, the differential between the high point and the low point (PH1 - PB1 and PH2 - PB2) depends upon the natural characteristics of the switch. It is not adjustable.



Example: contact schematics of XMLD



— Adjustable value
--- Non adjustable value

PH = High point
PB = Low point

Electromechanical pressure and vacuum switches
OsiSense XM

Terminology

Operating range
The difference between the minimum low point (PB) and the maximum high point (PH) setting values.

Size
Pressure switches and vacuum-pressure switches (vacu-pressure switches)
Maximum value of the operating range.

Vacuum switches
Minimum value of the operating range.

Switching point on rising pressure (PH)
Pressure switches
The upper pressure setting at which the pressure switch will actuate the contacts on rising pressure.

Vacuum switches
The lower vacuum setting at which the vacuum switch will reset the contacts on rising pressure.

Switching point on falling pressure (PB)
The pressure at which the switch output changes state on falling pressure.

Switches with fixed differential
The lower point (PB) is not adjustable and is entirely dependent on the high point setting (PH) and the natural differential of the switch.

Switches with adjustable differential
The adjustable differential enables the independent setting of the lower point (PB).

Differential
The difference between the switching point on rising pressure (PH) and the switching point on falling pressure (PB).

Spread
For dual stage switches, the spread indicates the difference between the 2 switching points on rising pressure (PH2 and PH1) and, for vacuum switches, the difference between the 2 switching points on falling pressure (PB2 and PB1).

Accuracy (switches with setting scale)


The tolerance between the point at which the switch actuates its contacts and the value indicated on the setting scale. Where very high setting accuracy is required (initial installation of the product), it is recommended to use separate measuring equipment (pressure gauge, etc.).

Electromechanical pressure and vacuum switches
OsiSense XM

Terminology (continued)

Repeat accuracy (R)



The tolerance between two consecutive switching operations.

Drift (F)



The tolerance of the switching point throughout the entire service life of the switch.

Accidental overpressure



Example 1: with destructive pressure level.



Example 2: with destructive pressure level and destructive pressure oscillations.
Without damping device
With damping device

This is an accidental pressure surge of very short duration (a few milliseconds).

If accidental overpressures occur and their duration is less than 50 milliseconds, the pressure damping device incorporated in the XML switches (sizes 10 bar and greater) will diminish the effect.

Maximum permissible pressure per cycle (Ps)

A pressure switch can withstand this pressure, without detrimental effect, on each cycle throughout its service life.

Its minimum value is at least equal to 1.25 times the switch size.

Maximum permissible accidental pressure

The maximum accidental pressure is at least equal to 2.25 times the switch size.

Destruction pressure

The maximum guaranteed pressure that the switch will withstand before its destruction, i.e. bursting, rupturing, component failure, etc.

Its value is at least equal to 4.5 times the switch size.

Electromechanical pressure and vacuum switches
OsiSense XM

Application range of pressure and vacuum switches XML, XMA and XMX, for control circuits

On standard loads
Continuous duty, frequent switching.



1 Standard PLC input, type 1
2 Standard PLC input, type 2
3 Switching capacity conforming to IEC 60947-5-1, utilisation category AC-15, DC-13
B300 240 V 1.5 A
R300 250 V 0.1 A
4 Switching capacity conforming to IEC 60947-5-1, utilisation category AC-15, DC-13
B300 120 V 3 A
R300 125 V 0.22 A
PLC: Programmable Logic Controller

Pressure switches	Application range
XMLA XMLB XMLC XMLD XMX, XMA	
XMLG XMLK	

On small loads
The use of electromechanical pressure and vacuum switches with programmable logic controllers is becoming more predominant.
On small loads, the reliability of the switches maintain a failure rate of less than 1 for 100 million operating cycles.

Electromechanical pressure and vacuum switches
OsiSense XM

Selection of switch size

After establishing the type of switch required for the application (single threshold detection or regulation between 2 thresholds), the selection of its size will depend on the following criteria:
- the differential: difference between the high point (PH) and the low point (PB),
- the maximum pressure permissible per cycle,
- repeat accuracy, precision and minimum drift.

Examples of a fixed differential pressure switch selection, for detection of a single threshold

Main criterion: minimum differential
Example: for a selected high point (PH) of 7 bar



XMLA010●●●●●
Differential = 0.5 bar



XMLA020●●●●●
Differential = 1 bar



XMLA035●●●●●
Differential = 2 bar

Select an XMLA010●●●●● (the lowest size)

Main criterion: tolerance to overpressures
Example: for a selected high point (PH) of 12 bar



XMLA020●●●●●
Permissible accidental overpressure = 45 bar



XMLA035●●●●●
Permissible accidental overpressure = 80 bar

Select an XMLA035●●●●● (the highest size)

Main criterion: repeat accuracy, precision and minimum drift
Example: for a selected high point (PH) of 18 bar



XMLA020●●●●●
Adjustable from 1 to 20 bar



XMLA035●●●●●
Adjustable from 1.5 to 35 bar

Select an XMLA035●●●●●

As a general rule, working at the upper or lower limits of the operating range should be avoided.

Units of pressure conversion table

	psi	kg/cm²	bar	atm	mm Hg (Torr)	mm H_2O	Pa
1 psi =	1	0.07031	0.06895	0.06805	51.71	703.7	6895
1 kg/cm² =	14.22	1	0.98066	0.96784	735.55	10 000	98 066
1 bar =	14.50	1.0197	1	0.98695	750.06	10 197	10^5
1 atm =	14.70	1.0333	1.0132	1	760.0	10 333	101 325
1 mm Hg (Torr) =	0.01934	1.360×10^{-3}	1.333×10^{-3}	1.316×10^{-3}	1	13.59	133.3
1 mm H_2O =	1.421×10^{-3}	10^{-4}	$\sim 10^{-4}$	$\sim 10^{-4}$	0.07361	1	~ 9.80
1 Pa =	1.45×10^{-4}	1.0197×10^{-5}	10^{-5}	9.8695×10^{-6}	7.5×10^{-3}	0.10197	1

Example: 1 bar = 14.50 psi = 10^5 Pa

Electromechanical pressure and vacuum switches

Fixed differential switches, for detection of a single threshold

Adjustment range of the high point



Defined by the difference between the minimum and maximum high point (PH) setting values.

For a high set point (PH), the lower point (PB) is fixed and cannot be adjusted.
For a low set point (PB1 or PB2), the higher point (PH1 or PH2) is fixed and cannot be adjusted.

Switching point on rising pressure (PH)



The upper pressure setting at which the pressure or vacuum switch will actuate the contacts on rising pressure.

Adjustable throughout the range on rising pressure.

Switching point on falling pressure (PB)



The pressure at which the switch contact changes state on falling pressure.

The lower point (PB) is not adjustable and is entirely dependent on the high point setting (PH) and the natural differential of the switch.

Differential



PH - PB = natural differential
The difference between the switching point on rising pressure (PH) and the switching point on falling pressure (PB).

This point is not adjustable and therefore, the value of the differential is fixed.
It is the natural differential of the switch (contact differential, friction, etc.).

Example



■ Consider a switching point on rising pressure (PH) of 40 bar (set value at which the contact will change state on rising pressure).
■ It can be seen that the switching point on falling pressure (PB) is 28 bar (fixed value at which the contact will return to its original state).
Conclusion:
□ the differential will be 40 - 28 = 12 bar.

Electromechanical pressure and vacuum switches

Adjustable differential switches, for regulation between 2 thresholds

Adjustment range of the high point



Defined by the difference between the minimum and maximum high point (PH) setting values.

Switching point on rising pressure (PH)



The upper pressure setting at which the pressure or vacuum switch will actuate the contacts on rising pressure.

Adjustable throughout the range on rising pressure.

Switching point on falling pressure (PB)



The pressure at which the switch contact changes state on falling pressure.

The adjustable differential enables the independent setting of the lower point (PB).

Differential



Low point < High point
PH - PB' = natural differential
PH - PB" = minimum differential

The difference between the switching point on rising pressure (PH) and the switching point on falling pressure (PB).

***Note:** the low point can be set at any value between PB' and PB".*

Example



1 Maximum differential
2 Minimum differential

■ Consider a switching point on rising pressure (PH) of 22 bar (set value at which the contact will change state on rising pressure).
■ It can be seen that the switching point on falling pressure (PB) can be between 4 and 19 bar inclusive (set value at which the contact will return to its original state).
Conclusion:
□ the maximum differential will be: 22 - 4 = 18 bar,
□ the minimum differential will be: 22 - 19 = 3 bar.

Electromechanical pressure and vacuum switches

Dual stage, fixed differential switches, for detection at each threshold

Adjustment ranges of the switching points PH1 and PH2 on rising pressure



Defined by the difference between the minimum and maximum high point setting values of each stage (PH1 and PH2).

Switching point PH2 on rising pressure



The upper pressure setting at which the pressure or vacuum switch will actuate the contacts on rising pressure.

Adjustable throughout the range on rising pressure.

Switching point PH1 on rising pressure



The upper pressure setting at which the pressure or vacuum switch will actuate contact 1 on rising pressure.

Spread



PH1 < PH2
PH2 - PH1' = maximum spread
PH2 - PH1" = minimum spread

The difference between switching points PH2 and PH1 on rising pressure.

Note: *switching point PH1 can be set at any value between PH1' and PH1".*

Example: Determining switching points on rising pressure for the 2 stages



1 Maximum spread
2 Minimum spread

■ Consider a 2nd stage switching point on rising pressure (PH2) of 20 bar (set value at which contact 2 will change state on rising pressure).
■ It can be seen that the 1st stage switching point (PH1) can be set between 4.5 and 17 bar on rising pressure.
Conclusion:
□ the maximum spread will be:
20 - 4.5 = 15.5 bar,
□ the minimum spread will be:
20 - 17 = 3 bar.

Electromechanical pressure and vacuum switches

Dual stage, fixed differential switches, for detection at each threshold

Adjustment range of high point (PH1 or PH2)



Defined by the difference between the minimum and maximum high point (PH1 or PH2) setting values for each stage.

For a high set point (PH), the lower point (PB) is fixed and cannot be adjusted.
For a low set point (PB1 or PB2), the higher point (PH1 or PH2) is fixed and cannot be adjusted.

Switching point on rising pressure (PH1 or PH2)



The upper pressure setting at which the pressure or vacuum switch will actuate the contact, for each stage, on rising pressure.

Adjustable throughout the range on rising pressure.

Switching point on falling pressure (PB1 or PB2)



The pressure at which the switch contact changes state, for each stage, on falling pressure.

The lower point (PB) is not adjustable and is entirely dependent on the high point setting (PH) and the natural differential of the switch.

Differential



PH - PB = natural differential
The difference between the switching point on rising pressure (PH) and the switching point on falling pressure (PB), for each stage.

This point is not adjustable and therefore, the value of the differential is fixed.
It is the natural differential of the switch (contact differential, friction, etc.), for each of its 2 stages.

Example: stage 1 = segment EF stage 2 = segment GH



1 Maximum spread
2 Minimum spread

For stage 2 (segment GH):
■ Consider a switching point on rising pressure (PH2) of 20 bar (set value at which contact 2 will change state on rising pressure).
■ It can be seen that the switching point on falling pressure (PB2) is 14 bar (fixed value at which contact 2 will return to its original state).
Conclusion:
for stage 2, the differential will be:
20 - 14 = 6 bar.
Repeat the same procedure for stage 1 (segment EF).

Electromechanical pressure and vacuum switches
OsiSense XM
OsiSense XML for control circuits

Presentation

OsiSense **XML** pressure and vacuum switches are designed for use in control circuits.
They are used to control the pressure of hydraulic oils, fresh water, sea water, air, steam, corrosive fluids or viscous products, up to 500 bar.

OsiSense **XMLA** pressure and vacuum switches have a fixed differential and are used for detection of a single threshold. They incorporate 1 CO single-pole contact.
OsiSense **XMLB** pressure and vacuum switches have an adjustable differential and are used for regulation between 2 thresholds. They incorporate 1 CO single-pole contact.
OsiSense **XMLC** pressure and vacuum switches have an adjustable differential and are used for regulation between 2 thresholds. They incorporate 2 CO single-pole contacts.
OsiSense **XMLD** pressure and vacuum switches are dual stage switches, each stage with a fixed differential, and are used for detection at each threshold. They incorporate 2 CO single-pole contacts (one per stage).

Setting

When setting OsiSense XML pressure and vacuum switches, adjust the switching point on rising pressure (PH) first and then the switching point on falling pressure (PB).

OsiSense XMLA pressure and vacuum switches with fixed differential



Switching point on rising pressure
The switching point on rising pressure (PH) is set by adjusting the red screw 1.

Switching point on falling pressure
The switching point on falling pressure (PB) is not adjustable.
The difference between the tripping and resetting points of the contact is the natural differential of the switch (contact differential, friction, etc.).

OsiSense XMLB and XMLC pressure and vacuum switches with adjustable differential



Switching point on rising pressure
The switching point on rising pressure (PH) is set by adjusting the red screw 1.

Switching point on falling pressure
The switching point on falling pressure (PB) is set by adjusting the green screw 2.

OsiSense XMLD dual stage pressure and vacuum switches with fixed differential for each threshold



Switching point on rising pressure of stage 1 and stage 2
The first stage switching point on rising pressure (PH1) is set by adjusting the red screw 1.
The second stage switching point on rising pressure (PH2) is set by adjusting the blue screw 2.

Switching point on falling pressure
The switching points on falling pressure (PB1 and PB2) are not adjustable.
The difference between the tripping and resetting points of each contact is the natural differential of the switch (contact differential, friction, etc.).

Electromechanical pressure and vacuum switches
OsiSense XM
OsiSense XML for control circuits

Environment characteristics

Conformity to standards		CE, IEC/EN 60947-5-1, UL 508, CSA C22-2 no. 14
Product certifications		All products: UL, CSA, EAC XMLA and XMLB: CCC, BV, LROS
Protective treatment		Standard version "TC". Special version "TH"
Ambient air temperature	**°C**	For operation: -25…+70. For storage: -40…+70
Fluids or products controlled		Hydraulic oils, air, fresh water, sea water Steam, corrosive fluids, viscous products, depending on model
Materials		Case: zinc alloy Component materials in contact with fluid: see pages 72 and 73
Operating position		All positions
Vibration resistance		4 gn (30...500 Hz) conforming to IEC 60068-2-6 except **XML●L35●●●●●**, **XML●001●●●●●** and **XMLBM03●●●●●**: 2 gn
Shock resistance		50 gn conforming to IEC 60068-2-27 except **XML●L35●●●●●**, **XML●001●●●●●** and **XMLBM03●●●●●**: 30 gn
Electric shock protection		Class I conforming to IEC 1140, IEC 536 and NF C 20-030
Degree of protection		Screw terminal models: IP 66 conforming to IEC/EN 60529 Connector models: IP 65 conforming to IEC/EN 60529
Operating rate	**Op. cycles/ min**	Piston version switches: ⩽ 60 (for temperatures > 0 °C) Diaphragm version switches: ⩽ 120 (for temperatures > 0 °C)
Repeat accuracy		< 2%
Fluid connection		G 1/4 (BSP female) conforming to NF E 03-005, ISO 228 or 1/4"-18 NPTF For sizes ⩾ 300 bar, use the gasket supplied with the product. This gasket is also available as a separate part, reference **XMLZL010**.
Electrical connection		Screw terminal models: ISO M20 x 1.5 or 1/2" NPT tapped entry For an entry tapped for no.13 (DIN Pg 13.5) cable gland, replace the last number of the reference with 1 (for example, **XMLA010A2S12** becomes **XMLA010A2S11**) Connector models: EN 175301-803-A (ex-DIN 43650) connector

Contact block characteristics

Rated operational characteristics		~ AC-15, B300 (Ue = 240 V, Ie = 1.5 A; Ue = 120 V, Ie = 3 A) ⎓ DC-13; R300 (Ue = 250 V, Ie = 0.1 A), conforming to IEC 60947-5-1 Appendix A, EN 60947-5-1
Rated insulation voltage		Ui = 500 V conforming to IEC/EN 60947-1 Ui = 300 V conforming to UL 508, CSA C22-2 no. 14
Rated impulse withstand voltage		U imp = 6 kV conforming to IEC/EN 60947-1
Type of contacts		Silver tipped contacts **XMLA** and **XMLB**: 1 CO single-pole contact (4 terminals), snap action **XMLC**: 2 CO single-pole contacts (8 terminals), simultaneous, snap action **XMLD**: 2 CO single-pole contacts (8 terminals), staggered, snap action
Resistance across terminals	**mΩ**	< 25 conforming to NF C 93-050 method A or IEC 255-7 category 3
Terminal referencing		Conforming to CENELEC EN 50013
Short-circuit protection		10 A cartridge fuse type gG (gl)
Connection		Screw clamp terminals. Minimum clamping capacity: 1 x 0.5 mm²/ AWG 20 Maximum clamping capacity: 2 x 2.5 mm²/AWG 14

Electrical durability
Conforming to IEC/EN 60947-5-1 Appendix C
Utilisation categories AC-15 and DC-13

Operating rate: 3600 operating cycles/hour
Load factor: 0.5

XMLA and **XMLB**
AC supply ~ 50/60 Hz
⎓ Inductive circuit, Ithe = 10 A



DC supply ⎓
Power broken in W
for 1 million operating cycles

Voltage	V	24	48	120
⎓	W	31	29	26

XMLC and **XMLD**
AC supply ~ 50/60 Hz
⎓ Inductive circuit, Ithe = 10 A



DC supply ⎓
Power broken in W for 5 million operating cycles

Voltage	V	24	48	120
⎓	W	10	7	4

Electromechanical vacuum switches
OsiSense XML
Size - 1 bar (- 14.5 psi)
Fixed differential, for detection of a single threshold
Switches with 1 CO single-pole contact

OsiSense XMLA vacuum switches | **With setting scale**





Adjustable range of switching point (PB) (Falling pressure)		**- 0.28…- 1 bar (- 4.06…- 14.5 psi)**		
Electrical connection		DIN connector	Terminals	
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*				
Fluids controlled *(2)*	Hydraulic oils, fresh water, air, up to + 70 °C	**XMLAM01V2C11**	**XMLAM01V2S12**	**XMLAM01V2S13**
	Hydraulic oils, fresh water, air, corrosive fluids, up to + 160 °C Sea water, up to + 30 °C	**XMLAM01T2C11**	**XMLAM01T2S12**	**–**
Weight (kg)		0.685	0.715	0.715
Complementary characteristics not shown under general characteristics (page 17)				
Natural differential (add to PB to give PH)	At low setting *(3)*	0.24 bar (3.48 psi)		
	At high setting *(3)*	0.24 bar (3.48 psi)		
Maximum permissible pressure	Per cycle	5 bar (72.5 psi)		
	Accidental	9 bar (130.5 psi)		
Destruction pressure		18 bar (261 psi)		
Mechanical life		3 x 10^6 operating cycles		
Connection		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Vacuum switch type		Diaphragm		

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLAM01V2S12** becomes **XMLAM01V2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: ± 0.05 bar (± 0.72 psi).

Operating curves





— Adjustable value
--- Non adjustable value

Connection

Terminal model



Connector model

Vacuum switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For vacuum switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical vacuum switches
OsiSense XM, OsiSense XML
Size - 1 bar (- 14.5 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 1 CO single-pole contact

OsiSense XMLB vacuum switches | **With setting scale**





Adjustable range of switching point (PB) (Falling pressure)		**- 0.14…- 1 bar (- 2.03…- 14.5 psi)**	
Electrical connection		DIN connector	Terminals
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*			
Fluids controlled *(2)*	Hydraulic oils, fresh water, air, up to + 70 °C	**XMLBM02V2C11**	**XMLBM02V2S12**	**XMLBM02V2S13**
	Hydraulic oils, fresh water, air, corrosive fluids, up to + 160 °C Sea water, up to + 30 °C	**XMLBM02T2C11**	**XMLBM02T2S12**	**XMLBM02T2S13**
Weight (kg)		1.015	1.030	1.030

Complementary characteristics not shown under general characteristics (page 17)

Possible differential (add to PB to give PH)	Min. at low setting *(3)*	0.13 bar (1.88 psi)		
	Min. at high setting *(3)*	0.13 bar (1.88 psi)		
	Max. at high setting	0.8 bar (11.6 psi)		
Maximum permissible pressure	Per cycle	5 bar (72.5 psi)		
	Accidental	9 bar (130.5 psi)		
Destruction pressure		18 bar (261 psi)		
Mechanical life		3 x 10^6 operating cycles		
Connection		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Vacuum switch type		Diaphragm		

(1) For 1 entry tapped for no. 13 cable gland, replace ***S12*** *with* ***S11*** *(for example,* ***XMLBM02V2S12*** *becomes* ***XMLBM02V2S11****).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: ± 0.02 bar (± 0.29 psi).

Operating curves





1 Maximum differential
2 Minimum differential

— Adjustable value

Connection

Terminal model



Connector model

Vacuum switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For vacuum switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical vacuum switches
OsiSense XML
Size - 1 bar (- 14.5 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 2 CO single-pole contacts

OsiSense XMLC vacuum switches	**With setting scale**



Adjustable range of switching point (PB) (Falling pressure)	**- 0.14…- 1 bar (- 2.03…- 14.5 psi)**
Electrical connection	Terminals
Fluid connection	G 1/4 (female)

References *(1)*

Fluids controlled *(2)*	Hydraulic oils, fresh water, air, up to + 70 °C	**XMLCM02V2S12**
	Hydraulic oils, fresh water, air, corrosive fluids, up to + 160 °C Sea water, up to + 30 °C	**XMLCM02T2S12**
Weight (kg)		1.015

Complementary characteristics not shown under general characteristics (page 17)

Possible differential (add to PB to give PH)	Min. at low setting *(3)*	0.13 bar (1.89 psi)
	Min. at high setting *(3)*	0.14 bar (2.03 psi)
	Max. at high setting	0.8 bar (11.6 psi)
Maximum permissible pressure	Per cycle	5 bar (72.5 psi)
	Accidental	9 bar (130.5 psi)
Destruction pressure		18 bar (261 psi)
Mechanical life		3 x 10^6 operating cycles
Cable entry for terminal models		1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm
Vacuum switch type		Diaphragm

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLCM02V2S12** becomes **XMLCM02V2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: ± 0.02 bar (± 0.29 psi).

Operating curves





1 Maximum differential
2 Minimum differential
— Adjustable value

Connection

Terminal model



Other versions

For vacuum switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical vacuum switches

OsiSense XML

Size - 1 bar (- 14.5 psi)
Dual stage, fixed differential, for detection at each threshold
Switches with 2 CO single-pole contacts

OsiSense XMLD vacuum switches		Without setting scale



Adjustable range of each switching point (Falling pressure)	2nd stage switching point (PB2)	**- 0.12…- 1 bar (- 1.74…- 14.5 psi)**
	1st stage switching point (PB1)	**- 0.10…- 0.98 bar (- 1.45…- 14.21 psi)**
Spread between 2 stages (PB2 - PB1)		**0.02…0.88 bar (0.29…12.76 psi)**
Electrical connection		Terminals
Fluid connection		G 1/4 (female)

References *(1)*

Fluids controlled *(2)*	Hydraulic oils, fresh water, air, up to + 70 °C	**XMLDM02V1S12**
	Hydraulic oils, fresh water, air, corrosive fluids, up to + 160 °C Sea water, up to + 30 °C	**XMLDM02T1S12**
Weight (kg)		1.015

Complementary characteristics not shown under general characteristics (page 17)

Natural differential (add to PB1/PB2 to give PH1/PH2)	At low setting *(3)*	0.1 bar (1.45 psi)
	At high setting *(4)*	0.1 bar (1.45 psi)
Maximum permissible pressure	Per cycle	5 bar (72.5 psi)
	Accidental	9 bar (130.5 psi)
Destruction pressure		18 bar (261 psi)
Mechanical life		3 x 10^6 operating cycles
Cable entry for terminal models		1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm
Vacuum switch type		Diaphragm

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLDM02V1S12** becomes **XMLDM02V1S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: ± 0.035 bar (± 0.51 psi)
(4) Deviation of the differential at high setting point for switches of the same size: ± 0.02 bar (± 0.29 psi).

Operating curves

High setting tripping points of contacts 1 and 2



1 Maximum differential
2 Minimum differential

Natural differential of contacts 1 and 2



EF Contact 1 (stage 1)
GH Contact 2 (stage 2)



— Adjustable value
--- Non adjustable value

Connection

Terminal model



Other versions	For vacuum switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical vacuum switches

OsiSense XML

Size - 200 mbar (- 2.9 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 1 CO single-pole contact

OsiSense XMLB vacuum switches	**With setting scale**	
		
Adjustable range of switching point (PB) (Falling pressure)	**- 20…- 200 mbar (- 0.29…- 2.9 psi)**	
Electrical connection	Terminals	
Fluid connection	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*		
Fluids controlled *(2)* Hydraulic oils, air, up to + 160 °C	**XMLBM03R2S12**	**XMLBM03R2S13**
Weight (kg)	3.310	3.310

Complementary characteristics not shown under general characteristics (page 17)

Possible differential (add to PB to give PH)	Min. at low setting *(3)*	18 mbar (0.26 psi)	
	Min. at high setting *(3)*	18 mbar (0.26 psi)	
	Max. at high setting	180 mbar (2.6 psi)	
Maximum permissible pressure	Per cycle	1 bar (14.5 psi)	
	Accidental	2 bar (29 psi)	
Destruction pressure		3.5 bar (50.75 psi)	
Mechanical life		3 x 10^6 operating cycles	
Cable entry for terminal models		1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Vacuum switch type		Diaphragm	

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLBM03R2S12** becomes **XMLBM03R2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: ± 2 mbar (± 0.29 psi).

Operating curves





1 Maximum differential
2 Minimum differential

— Adjustable value

Connection

Terminal model



Other versions

For vacuum switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical pressure switches
OsiSense XML
Size 50 mbar (0.72 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 1 CO single-pole contact

OsiSense XMLB pressure switches	**With setting scale**



Adjustable range of switching point (PH) (Rising pressure)	**2.6…50 mbar (0.038…0,72 psi)**
Electrical connection	Terminals
Fluid connection	G 1/4 (female)

References *(1)*

Fluids controlled *(2)*	Hydraulic oils, air, up to + 160 °C	**XMLBL05R2S12**
	Fresh water, corrosive fluids, up to + 160 °C	**XMLBL05S2S12**
Weight (kg)		2.420

Complementary characteristics not shown under general characteristics (page 17)

Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	1.4 mbar (0.02 psi)
	Min. at high setting *(4)*	4 mbar (0.06 psi)
	Max. at high setting	40 mbar (0.58 psi)
Maximum permissible pressure	Per cycle	62.5 mbar (0.90 psi)
	Accidental	112.5 mbar (1.63 psi)
Destruction pressure		225 mbar (3.26 psi)
Mechanical life		6 x 10^6 operating cycles
Cable entry for terminal models		1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLBL05R2S12** becomes **XMLBL05R2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: - 0.8 mbar, + 1.1 mbar (- 0.01 psi, + 0.02 psi).
(4) Deviation of the differential at high setting point for switches of the same size: ± 1.4 mbar, (+ 0.02 psi).

Operating curves



1 Maximum differential
2 Minimum differential



— Adjustable value

Connection

Terminal model



Other versions	For pressure switches with EN 175301-803-A (ex-DIN 43650A) connector or with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical vacu-pressure switches

OsiSense XML. Size 5 bar (72.5 psi)

Adjustable differential, for regulation between 2 thresholds
Switches with 1 CO single-pole contact

OsiSense XMLB vacu-pressure switches		**With setting scale**		
				
Adjustable range of switching point (PH) (Rising pressure)		**- 0.5…5 bar (- 7.25…72.5 psi)**		
Electrical connection		DIN connector	Terminals	
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*				
Fluids controlled *(2)*	Hydraulic oils, fresh water, air, up to + 70 °C	**XMLBM05A2C11**	**XMLBM05A2S12**	**XMLBM05A2S13**
	Hydraulic oils, fresh water, air, up to + 160 °C	**XMLBM05B2C11**	**XMLBM05B2S12**	–
	Corrosive fluids, up to + 160 °C	**XMLBM05C2C11**	**XMLBM05C2S12**	–
	Viscous products, up to + 160 °C (G 1¼" fluid connection)	**XMLBM05P2C11**	**XMLBM05P2S12**	–
Weight (kg)		0.715	0.685	0.685
Complementary characteristics not shown under general characteristics (page 17)				
Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	0.5 bar (7.25 psi)		
	Min. at high setting *(3)*	0.5 bar (7.25 psi)		
	Max. at high setting	6 bar (87 psi)		
Maximum permissible pressure	Per cycle	6.25 bar (90.62 psi)		
	Accidental	11.25 bar (163.12 psi)		
Destruction pressure		23 bar (333.5 psi)		
Mechanical life		3 x 10^6 operating cycles		
Connection		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Vacu-pressure switch type		Diaphragm		

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLBM05A2S12** becomes **XMLBM05A2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: ± 0.05 bar (± 0.72 psi).

Operating curves





1 Maximum differential
2 Minimum differential

— Adjustable value

Connection

Terminal model



Connector model

Vacu-pressure switch pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For vacu-pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical vacu-pressure switches

OsiSense XML. Size 5 bar (72.5 psi)

Adjustable differential, for regulation between 2 thresholds
Switches with 2 CO single-pole contacts

OsiSense XMLC vacu-pressure switches	**With setting scale**



Adjustable range of switching point (PH) (Rising pressure)	**- 0.55…5 bar (- 7.97…72.5 psi)**
Electrical connection	Terminals
Fluid connection	G 1/4 (female)

References *(1)*

Fluids controlled *(2)*	Hydraulic oils, fresh water, air, up to + 160 °C	**XMLCM05B2S12**
	Corrosive fluids, up to + 160 °C	**XMLCM05C2S12**
Weight (kg)		0.685

Complementary characteristics not shown under general characteristics (page 17)

Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	0.45 bar (6.52 psi)
	Min. at high setting *(3)*	0.45 bar (6.52 psi)
	Max. at high setting	6 bar (87 psi)
Maximum permissible pressure	Per cycle	6.25 bar (90.62 psi)
	Accidental	11.25 bar (163.12 psi)
Destruction pressure		23 bar (333.5 psi)
Mechanical life		3 x 10^6 operating cycles
Cable entry for terminal models		1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm
Vacu-pressure switch type		Diaphragm

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLCM05B2S12** becomes **XMLCM05B2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: ± 0.1 bar (± 1.45 psi).

Operating curves





1 Maximum differential
2 Minimum differential

— Adjustable value

Connection

Terminal model



Connector model

Vacu-pressure switch pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For vacu-pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches
OsiSense XML
Size 350 mbar (5.07 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 1 CO single-pole contact

OsiSense XMLB pressure switches | **With setting scale**



Adjustable range of switching point (PH) (Rising pressure)		**45…350 mbar (0.65…5.07 psi)**		
Electrical connection		DIN connector	Terminals	
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*				
Fluids controlled *(2)*	Hydraulic oils, air, up to + 160 °C	**XMLBL35R2C11**	**XMLBL35R2S12**	**XMLBL35R2S13**
	Fresh water, corrosive fluids, up to + 160 °C	**XMLBL35S2C11**	**XMLBL35S2S12**	–
	Viscous products, up to + 160 °C (G 1¼" fluid connection)	**XMLBL35P2C11**	**XMLBL35P2S12**	–
Weight (kg)		2.590	2.575	2.575

Complementary characteristics not shown under general characteristics (page 17)

Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	42 mbar (0.60 psi)
	Min. at high setting *(4)*	50 mbar (0.72 psi)
	Max. at high setting	300 mbar (4.35 psi)
Maximum permissible pressure	Per cycle	1.25 bar (18.12 psi)
	Accidental	2.25 bar (32.62 psi)
Destruction pressure		4.5 bar (65.25 psi)
Mechanical life		4 million operating cycles
Connection		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68 / 1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm / 1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLBL35R2S12** becomes **XMLBL35R2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: - 8 mbar, + 3 mbar (- 0.12 psi, + 0.04 psi).
(4) Deviation of the differential at high setting point for switches of the same size: ± 8 mbar (± 0.11 psi).

Operating curves





— Adjustable value

1 Maximum differential
2 Minimum differential

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical pressure switches
OsiSense XML
Size 350 mbar (5.07 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 1 CO single-pole contact

OsiSense XMLB pressure switches	**30 bar (435 psi) overpressure** **With setting scale**



Adjustable range of switching point (PH) (Rising pressure)	**42…330 mbar (0.61…4.78 psi)**
Electrical connection	Terminals
Fluid connection	G 1/4 (female)

References *(1)*

Fluids controlled *(2)*	Hydraulic oils, air, up to + 160 °C	**XMLBS35R2S12**
Weight (kg)		3.500

Complementary characteristics not shown under general characteristics (page 17)

Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	33 mbar (0.48 psi)
	Min. at high setting *(4)*	58 mbar (0.84 psi)
	Max. at high setting	250 mbar (3.62 psi)
Maximum permissible pressure	Per cycle	30 bar (435 psi)
	Accidental	37.5 bar (543.75 psi)
Destruction pressure		67.5 bar (978.75 psi)
Mechanical life		2 million operating cycles
Cable entry for terminal models		1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm
Connector type for connector models		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68
Pressure switch type		Diaphragm

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLBS35R1S12** becomes **XMLBS35R1S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: - 8 mbar, + 3 mbar (- 0.12 psi, + 0.04 psi).
(4) Deviation of the differential at high setting point for switches of the same size: ± 8 mbar (± 0.11 psi).

Operating curves





1 Maximum differential
2 Minimum differential

— Adjustable value

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches
OsiSense XML
Size 350 mbar (5.07 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 2 CO single-pole contacts

OsiSense XMLC pressure switches		With setting scale		30 bar (435 psi) overpressure With setting scale	
					
Adjustable range of switching point (PH) (Rising pressure)		**45…350 mbar (0.65…5.07 psi)**		**42…330 mbar (0.61…4.78 psi)**	
Electrical connection		Terminals		Terminals	
Fluid connection		G 1/4 (female)	1/4"-18 NPTF (female)	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*					
Fluids controlled *(2)*	Hydraulic oils, air, up to + 160 °C	**XMLCL35R2S12**	**–**	**XMLCS35R2S12**	**XMLCS35R2S13**
	Fresh water, corrosive fluids, up to + 160 °C	**XMLCL35S2S12**	**XMLCL35S2S13**	**–**	**–**
Weight (kg)		2.575	2.575	3.500	3.500
Complementary characteristics not shown under general characteristics (page 17)					
Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	20 mbar (0.29 psi)		40 mbar (0.58 psi)	
	Min. at high setting *(3)*	35 mbar (0.51 psi)		88 mbar (1.27 psi)	
	Max. at high setting	300 mbar (4.35 psi)		230 mbar (3.33 psi)	
Maximum permissible pressure	Per cycle	1.25 bar (18.12 psi)		30 bar (435 psi)	
	Accidental	2.25 bar (32.62 psi)		37.5 bar (543.75 psi)	
Destruction pressure		4.5 bar (65.25 psi)		67.5 bar (978.75 psi)	
Mechanical life		4 million operating cycles		2 million operating cycles	
Cable entry for terminal models		1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm			

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLCL35R2S12** becomes **XMLCL35R2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: ± 20 mbar (± 0.29 psi).

Operating curves





1 Maximum differential
2 Minimum differential

— Adjustable value

Connection

Terminal model



Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical pressure switches
OsiSense XML
Size 350 mbar (5.07 psi)
Dual stage, fixed differential, for detection at each threshold
Switches with 2 CO single-pole contacts

OsiSense XMLD pressure switches | **Without setting scale**



Adjustable range of each switching point (Rising pressure)	2nd stage switching point (PH2)	**58…350 mbar (0.84…5.07 psi)**
	1st stage switching point (PH1)	**33…325 mbar (0.48…4.71 psi)**
Spread between 2 stages (PH2 - PH1)		**25…310 mbar (0.36…4.50 psi)**
Electrical connection		Terminals
Fluid connection		G 1/4 (female)

References *(1)*

Fluids controlled *(2)*	Hydraulic oils, air, up to + 160 °C	**XMLDL35R1S12**
Weight (kg)		2.575

Complementary characteristics not shown under general characteristics (page 17)

Natural differential (subtract from PH1/PH2 to give PB1/PB2)	At low setting *(3)*	30 mbar (0.44 psi)
	At high setting *(4)*	30 mbar (0.44 psi)
Maximum permissible pressure	Per cycle	1.25 bar (18.12 psi)
	Accidental	2.25 bar (32.62 psi)
Destruction pressure		4.5 bar (65.25 psi)
Mechanical life		4 million operating cycles
Cable entry for terminal models		1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLDL35R1S12** becomes **XMLDL35R1S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: ± 10 mbar (± 0.15 psi).
(4) Deviation of the differential at high setting point for switches of the same size: ± 8 mbar (± 0.11 psi).

Operating curves

High setting tripping points of contacts 1 and 2



1 Maximum differential
2 Minimum differential

Natural differential of contacts 1 and 2



EF Contact 1 (stage 1)
GH Contact 2 (stage 2)



— Adjustable value
--- Non adjustable value

Connection

Terminal model



Other versions — For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches
OsiSense XML
Size 1 bar (14.5 psi)
Fixed differential, for detection of a single threshold
Switches with 1 CO single-pole contact

OsiSense XMLA pressure switches | **With setting scale**



Adjustable range of switching point (PH) (Rising pressure)		**0.03…1 bar (0.435…14.5 psi)**		
Electrical connection		DIN connector	Terminals	
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*				
Fluids controlled *(2)*	Hydraulic oils, air, up to + 160 °C	**XMLA001R2C11**	**XMLA001R2S12**	–
	Fresh water, corrosive fluids, up to + 160 °C	**XMLA001S2C11**	**XMLA001S2S12**	**XMLA001S2S13**
Weight (kg)		2.570	2.555	2.555
Complementary characteristics not shown under general characteristics (page 17)				
Natural differential (subtract from PH to give PB)	At low setting *(3)*	0.02 bar (0.29 psi)		
	At high setting *(3)*	0.04 bar (0.58 psi)		
Maximum permissible pressure	Per cycle	1.25 bar (18.12 psi)		
	Accidental	2.25 bar (32.62 psi)		
Destruction pressure		4.5 bar (65.25 psi)		
Mechanical life		4 x 10^6 operating cycles		
Connection		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm		

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLA001R2S12** becomes **XMLA001R2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: ± 0.01 bar (± 0.14 psi)

Operating curves





— Adjustable value
--- Non adjustable value

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical pressure switches

OsiSense XML

Size 1 bar (14.5 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 1 CO single-pole contact

OsiSense XMLB pressure switches | **With setting scale**



Adjustable range of switching point (PH) (Rising pressure)		**0.05…1 bar (0.72…14.5 psi)**		
Electrical connection		DIN connector	Terminals	
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*				
Fluids controlled *(2)*	Hydraulic oils, air, up to + 160 °C	**XMLB001R2C11**	**XMLB001R2S12**	**XMLB001R2S13**
	Fresh water, corrosive fluids, up to + 160 °C	**XMLB001S2C11**	**XMLB001S2S12**	**XMLB001S2S13**
	Viscous products, up to + 160 °C (G 1¼" fluid connection)	**–**	**XMLB001P2S12**	**–**
Weight (kg)		2.590	2.575	2.575
Complementary characteristics not shown under general characteristics (page 17)				
Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	0.04 bar (0.58 psi)		
	Min. at high setting *(4)*	0.06 bar (0.87 psi)		
	Max. at high setting	0.75 bar (10.87 psi)		
Maximum permissible pressure	Per cycle	1.25 bar (18.12 psi)		
	Accidental	2.25 bar (32.62 psi)		
Destruction pressure		4.5 bar (65.25 psi)		
Mechanical life		4 x 10^6 operating cycles		
Connection		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm		

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLB001R2S12** becomes **XMLB001R2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: ± 10 mbar (± 0.14 psi).
(4) Deviation of the differential at high setting point for switches of the same size: ± 20 mbar (± 0.29 psi).

Operating curves





1 Maximum differential
2 Minimum differential

— Adjustable value

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches
OsiSense XML
Size 1 bar (14.5 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 2 CO single-pole contacts

OsiSense XMLC pressure switches	**With setting scale**	



Adjustable range of switching point (PH) (Rising pressure)		**0.05…1 bar (0.725…14.5 psi)**	
Electrical connection		Terminals	
Fluid connection		G 1/4 (female)	1/4”-18 NPTF (female)
References *(1)*			
Fluids controlled *(2)*	Hydraulic oils, air, up to + 160 °C	**XMLC001R2S12**	**XMLC001R2S13**
	Fresh water, corrosive fluids, up to + 160 °C	**XMLC001S2S12**	**XMLC001S2S13**
Weight (kg)		2.555	2.555
Complementary characteristics not shown under general characteristics (page 17)			
Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	0.03 bar (0.43 psi)	
	Min. at high setting *(4)*	0.04 bar (0.58 psi)	
	Max. at high setting	0.8 bar (11.6 psi)	
Maximum permissible pressure	Per cycle	1.25 bar (18.12 psi)	
	Accidental	2.25 bar (32.62 psi)	
Destruction pressure		4.5 bar (65.25 psi)	
Mechanical life		4 x 10^6 operating cycles	
Cable entry for terminal models		1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2”-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm	

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLC001R2S12** becomes **XMLC001R2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: ± 0.01 bar (± 0.14 psi)
(4) Deviation of the differential at high setting point for switches of the same size: ± 0.03 bar (± 0.43 psi)

Operating curves





1 Maximum differential
2 Minimum differential

— Adjustable value

Connection
Terminal model



Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical pressure switches

OsiSense XML

Size 2.5 bar (36.25 psi)
Fixed differential, for detection of a single threshold
Switches with 1 CO single-pole contact

OsiSense XMLA pressure switches		With setting scale		
				
Adjustable range of switching point (PH) (Rising pressure)		**0.15…2.5 bar (2.17…36.25 psi)**		
Electrical connection		DIN connector	Terminals	
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*				
Fluids controlled *(2)*	Hydraulic oils, fresh water, air, up to + 70 °C	**XMLA002A2C11**	**XMLA002A2S12**	**XMLA002A2S13**
	Hydraulic oils, fresh water, air, up to + 160 °C	**XMLA002B2C11**	**XMLA002B2S12**	**–**
	Corrosive fluids, up to + 160 °C	**XMLA002C2C11**	**XMLA002C2S12**	**–**
Weight (kg)		1.010	0.995	0.995
Complementary characteristics not shown under general characteristics (page 17)				
Natural differential (subtract from PH to give PB)	At low setting *(3)*	0.13 bar (1.88 psi)		
	At high setting *(3)*	0.13 bar (1.88 psi)		
Maximum permissible pressure	Per cycle	5 bar (72.5 psi)		
	Accidental	9 bar (130.5 psi)		
Destruction pressure		18 bar (261 psi)		
Mechanical life		8 x 10^6 operating cycles		
Connection		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm		

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLA002A2S12** becomes **XMLA002A2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: ± 0.03 bar (± 0.43 psi).

Operating curves





— Adjustable value
--- Non adjustable value

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches

OsiSense XML

Size 2.5 bar (36.25 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 1 CO single-pole contact

OsiSense XMLB pressure switches	**With setting scale**			**30 bar (435 psi) overpressure With setting scale**
				
Adjustable range of switching point (PH) (Rising pressure)	**0.3…2.5 bar (4.35…36.25 psi)**			
Electrical connection	DIN connector	Terminals		
Fluid connection	G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)	G 1/4 (female)
References *(1)*				
Fluids controlled *(2)* — Hydraulic oils, fresh water, air, up to + 70 °C	**XMLB002A2C11**	**XMLB002A2S12**	**XMLB002A2S13**	**–**
Hydraulic oils, fresh water, air, up to + 160 °C	**XMLB002B2C11**	**XMLB002B2S12**	**–**	**XMLBS02B2S12**
Corrosive fluids, up to + 160 °C	**XMLB002C2C11**	**XMLB002C2S12**	**–**	**–**
Weight (kg)	1.030	1.015	1.015	3.500
Complementary characteristics not shown under general characteristics (page 17)				
Possible differential (subtract from PH to give PB) — Min. at low setting *(3)*	0.16 bar (2.32 psi)			0.1 bar (1.45 psi)
Min. at high setting *(3)*	0.21 bar (3.04 psi)			0.22 bar (3.19 psi)
Max. at high setting	1.75 bar (25.37 psi)			1.45 bar (21 psi)
Maximum permissible pressure — Per cycle	5 bar (72.5 psi)			30 bar (435 psi)
Accidental	9 bar (130.5 psi)			37.5 bar (543.75 psi)
Destruction pressure	18 bar (261 psi)			67.5 bar (978.75 psi)
Mechanical life	8 x 10^6 operating cycles			2 x 10^6 operating cycles
Connection	EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm
Pressure switch type	Diaphragm			

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLB002A2S12** becomes **XMLB002A2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: - 0.03 bar, + 0.05 bar (- 0.43 psi, + 0.72 psi).

Operating curves





1 Maximum differential
2 Minimum differential

— Adjustable value

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions — For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches

OsiSense XML

Size 2.5 bar (36.25 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 2 CO single-pole contacts

OsiSense XMLC pressure switches	With setting scale		30 bar (435 psi) overpressure With setting scale	
				
Adjustable range of switching point (PH) (Rising pressure)	**0.3…2.5 bar (4.35…36.25 psi)**			
Electrical connection	Terminals			
Fluid connection	G 1/4 (female)	1/4"-18 NPTF (female)	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*				
Fluids controlled *(2)* — Hydraulic oils, fresh water, air, up to + 160 °C	**XMLC002B2S12**	**XMLC002B2S13**	**XMLCS02B2S12**	**XMLCS02B2S13**
Weight (kg)	0.995	0.995	3.500	3.500
Complementary characteristics not shown under general characteristics (page 17)				
Possible differential (subtract from PH to give PB) — Min. at low setting *(3)*	0.13 bar (1.89 psi)		0.1 bar (1.45 psi)	
Min. at high setting *(4)*	0.17 bar (2.47 psi)		0.18 bar (2.61 psi)	
Max. at high setting	2 bar (29 psi)		1.25 bar (18.12 psi)	
Maximum permissible pressure — Per cycle	5 bar (72.5 psi)		30 bar (435 psi)	
Accidental	9 bar (130.5 psi)		37.5 bar (543.75 psi)	
Destruction pressure	18 bar (261 psi)		67.5 bar (978.75 psi)	
Mechanical life	8 x 10^6 operating cycles		2 x 10^6 operating cycles	
Cable entry for terminal models	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type	Diaphragm			

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLC002B2S12** becomes **XMLC002B2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: ± 0.02 bar (± 0.29 psi)
(4) Deviation of the differential at high setting point for switches of the same size: ± 0.03 bar (± 0.43 psi)

Operating curves





1 Maximum differential
2 Minimum differential
— Adjustable value

Connection

Terminal model



Other versions — For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches

OsiSense XML

Size 4 bar (58 psi)
Fixed differential, for detection of a single threshold
Switches with 1 CO single-pole contact

OsiSense XMLA pressure switches		With setting scale		
				
Adjustable range of switching point (PH) (Rising pressure)		**0.4…4 bar (5.8…58 psi)**		
Electrical connection		DIN connector	Terminals	
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*				
Fluids controlled *(2)*	Hydraulic oils, fresh water, air, up to + 70 °C	**XMLA004A2C11**	**XMLA004A2S12**	**XMLA004A2S13**
	Hydraulic oils, fresh water, air, up to + 160 °C	**XMLA004B2C11**	**XMLA004B2S12**	**–**
	Corrosive fluids, up to + 160 °C Sea water, up to + 30 °C	**XMLA004C2C11**	**XMLA004C2S12**	**–**
	Viscous products, up to + 160 °C (G 1¼" fluid connection)	**XMLA004P2C11**	**XMLA004P2S12**	**–**
Weight (kg)		0.715	0.685	0.685
Complementary characteristics not shown under general characteristics (page 17)				
Natural differential (subtract from PH to give PB)	At low setting *(3)*	0.35 bar (5.07 psi)		
	At high setting *(3)*	0.35 bar (5.07 psi)		
Maximum permissible pressure	Per cycle	5 bar (72.5 psi)		
	Accidental	9 bar (130.5 psi)		
Destruction pressure		18 bar (261 psi)		
Mechanical life		8 x 10^6 operating cycles		
Connection		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm		

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLA004A2S12** becomes **XMLA004A2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: ± 0.03 bar (± 0.43 psi)

Operating curves





— Adjustable value
--- Non adjustable value

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical pressure switches

OsiSense XML

Size 4 bar (58 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 1 CO single-pole contact

OsiSense XMLB pressure switches		With setting scale			30 bar (435 psi) overpressure With setting scale
					
Adjustable range of switching point (PH) (Rising pressure)		**0.25…4 bar (3.62…58 psi)**			
Electrical connection		DIN connector	Terminals		
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)	G 1/4 (female)
References *(1)*					
Fluids controlled *(2)*	Hydraulic oils, fresh water, air, up to + 70 °C	**XMLB004A2C11**	**XMLB004A2S12**	**XMLB004A2S13**	**–**
	Hydraulic oils, fresh water, air, up to + 160 °C	**XMLB004B2C11**	**XMLB004B2S12**	**–**	**XMLBS04B2S12**
	Corrosive fluids, up to + 160 °C	**XMLB004C2C11**	**XMLB004C2S12**	**–**	**–**
Weight (kg)		1.030	1.015	1.015	3.500
Complementary characteristics not shown under general characteristics (page 17)					
Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	0.2 bar (2.9 psi)			0.15 bar (2.18 psi)
	Min. at high setting *(4)*	0.25 bar (3.62 psi)			0.34 bar (4.93 psi)
	Max. at high setting	2.4 bar (34.8 psi)			2.46 bar (35.67 psi)
Maximum permissible pressure	Per cycle	5 bar (72.5 psi)			30 bar (435 psi)
	Accidental	9 bar (130.5 psi)			37.5 bar (543.75 psi)
Destruction pressure		18 bar (261 psi)			67.5 bar (978.75 psi)
Mechanical life		8 x 10^6 operating cycles			2 x 10^6 operating cycles
Connection		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm			

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLB004A2S12** becomes **XMLB004A2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: ± 0.01 bar (± 0.14 psi).
(4) Deviation of the differential at high setting point for switches of the same size: - 0.03 bar, + 0.05 bar (- 0.43 psi, + 0.72 psi).

Operating curves





1 Maximum differential
2 Minimum differential

— Adjustable value

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches

OsiSense XML

Size 4 bar (58 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 2 CO single-pole contacts

OsiSense XMLC pressure switches	With setting scale		30 bar (435 psi) overpressure With setting scale
			
Adjustable range of switching point (PH) (Rising pressure)	**0.3…4 bar (4.35…58 psi)**		
Electrical connection	Terminals		
Fluid connection	G 1/4 (female)	1/4"-18 NPTF (female)	G 1/4 (female)
References *(1)*			
Fluids controlled *(2)* — Hydraulic oils, fresh water, air, up to + 160 °C	**XMLC004B2S12**	**XMLC004B2S13**	**XMLCS04B2S12**
Corrosive fluids, up to + 160 °C	**XMLC004C2S12**	**XMLC004C2S13**	**–**
Weight (kg)	0.685	0.685	3.500
Complementary characteristics not shown under general characteristics (page 17)			
Possible differential (subtract from PH to give PB) — Min. at low setting *(3)*	0.15 bar (2.18 psi)		0.1 bar (1.45 psi)
Min. at high setting *(3)*	0.17 bar (2.47 psi)		0.25 bar (3.62 psi)
Max. at high setting	2.5 bar (36.25 psi)		2.20 bar (31.9 psi)
Maximum permissible pressure — Per cycle	5 bar (72.5 psi)		30 bar (435 psi)
Accidental	9 bar (130.5 psi)		37.5 bar (543.75 psi)
Destruction pressure	18 bar (261 psi)		67.5 bar (978.75 psi)
Mechanical life	8 x 10^6 operating cycles		2 x 10^6 operating cycles
Cable entry for terminal models	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm
Pressure switch type	Diaphragm		

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLC004B2S12** becomes **XMLC004B2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: ± 0.02 bar (± 0.29 psi).

Operating curves





1 Maximum differential
2 Minimum differential
— Adjustable value

Connection

Terminal model



Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical pressure switches

OsiSense XML

Size 4 bar (58 psi)
Dual stage, fixed differential, for detection at each threshold
Switches with 2 CO single-pole contacts

OsiSense XMLD pressure switches | **Without setting scale**



Adjustable range of each switching point (Rising pressure)	2nd stage switching point (PH2)	**0.40…4 bar (5.8…58 psi)**
	1st stage switching point (PH1)	**0.19…3.79 bar (2.76…54.96 psi)**
Spread between 2 stages (PH2 - PH1)		**0.21…2.18 bar (3.05…31.61 psi)**
Electrical connection		Terminals
Fluid connection		G 1/4 (female)

References *(1)*

Fluids controlled *(2)*	Hydraulic oils, fresh water, air, up to + 160 °C	**XMLD004B1S12**
Weight (kg)		1.015

Complementary characteristics not shown under general characteristics (page 17)

Natural differential (subtract from PH1/PH2 to give PB1/PB2)	At low setting *(3)*	0.15 bar (2.18 psi)
	At high setting *(3)*	0.19 bar (2.76 psi)
Maximum permissible pressure	Per cycle	5 bar (72.5 psi)
	Accidental	9 bar (130.5 psi)
Destruction pressure		18 bar (261 psi)
Mechanical life		8 x 10^6 operating cycles
Cable entry for terminal models		1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLD004B1S12** becomes **XMLD004B1S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: ± 0.03 bar (± 0.43 psi).

Operating curves

High setting tripping points of contacts 1 and 2



1 Maximum differential
2 Minimum differential

Natural differential of contacts 1 and 2



EF Contact 1 (stage 1)
GH Contact 2 (stage 2)



— Adjustable value
--- Non adjustable value

Connection

Terminal model



Other versions — For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches

OsiSense XML

Size 10 bar (145 psi)
Fixed differential, for detection of a single threshold
Switches with 1 CO single-pole contact

OsiSense XMLA pressure switches	With setting scale		
			
Adjustable range of switching point (PH) (Rising pressure)	**0.6…10 bar (8.7…145 psi)**		
Electrical connection	DIN connector	Terminals	Terminals
Fluid connection	G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)

References *(1)*

Fluids controlled *(2)*	Hydraulic oils, fresh water, air, up to + 70 °C	**XMLA010A2C11**	**XMLA010A2S12**	**XMLA010A2S13**
	Hydraulic oils, fresh water, air, up to + 160 °C	**XMLA010B2C11**	**XMLA010B2S12**	**–**
	Corrosive fluids, up to + 160 °C Sea water, up to + 30 °C	**XMLA010C2C11**	**XMLA010C2S12**	**XMLA010C2S13**
	Viscous products, up to + 160 °C (G 1¼" fluid connection)	**XMLA010P2C11**	**XMLA010P2S12**	**–**
Weight (kg)		0.715	0.685	0.685

Complementary characteristics not shown under general characteristics (page 17)

Natural differential (subtract from PH to give PB)	At low setting *(3)*	0.5 bar (7.25 psi)		
	At high setting *(3)*	0.5 bar (7.25 psi)		
Maximum permissible pressure	Per cycle	12.5 bar (181.25 psi)		
	Accidental	22.5 bar (326.25 psi)		
Destruction pressure		45 bar (652.5 psi)		
Mechanical life		5 x 10^6 operating cycles		
Connection		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm		

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLA010A2S12** becomes **XMLA010A2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: ± 0.05 bar (± 0.72 psi)

Operating curves





— Adjustable value
--- Non adjustable value

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical pressure switches

OsiSense XML

Size 10 bar (145 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 1 CO single-pole contact

OsiSense XMLB pressure switches		With setting scale			30 bar (435 psi) overpressure With setting scale
					
Adjustable range of switching point (PH) (Rising pressure)		**0.7…10 bar (10.15…145 psi)**			
Electrical connection		DIN connector	Terminals	Terminals	Terminals
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)	G 1/4 (female)
References *(1)*					
Fluids controlled *(2)*	Hydraulic oils, fresh water, air, up to + 70 °C	**XMLB010A2C11**	**XMLB010A2S12**	**XMLB010A2S13**	**XMLBS10A2S12**
	Hydraulic oils, fresh water, air, up to + 160 °C	**XMLB010B2C11**	**XMLB010B2S12**	**XMLB010B2S13**	**–**
	Corrosive fluids, up to + 160 °C Sea water, up to + 30 °C	**XMLB010C2C11**	**XMLB010C2S12**	**XMLB010C2S13**	**–**
	Viscous products, up to + 160 °C (G 1¼" fluid connection)	**XMLB010P2C11**	**XMLB010P2S12**	**–**	**–**
Weight (kg)		0.735	0.705	0.705	3.500
Complementary characteristics not shown under general characteristics (page 17)					
Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	0.57 bar (8.26 psi)			0.45 bar (6.52 psi)
	Min. at high setting *(4)*	0.85 bar (12.32 psi)			0.85 bar (12.32 psi)
	Max. at high setting	7.5 bar (108.75 psi)			6.25 bar (90.62 psi)
Maximum permissible pressure	Per cycle	12.5 bar (181.25 psi)			30 bar (435 psi)
	Accidental	22.5 bar (326.25 psi)			37.5 bar (543.75 psi)
Destruction pressure		45 bar (652.5 psi)			67.5 bar (978.75 psi)
Mechanical life		5 x 10^6 operating cycles			2 x 10^6 operating cycles
Connection		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm			

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLB010A2S12** becomes **XMLB010A2S11**.*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: ± 0.05 bar (± 0.72 psi).
(4) Deviation of the differential at high setting point for switches of the same size: - 0.1 bar, + 0.15 bar (- 1.45 psi, + 2.17 psi).

Operating curves



1 Maximum differential
2 Minimum differential



— Adjustable value

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Electromechanical pressure switches

OsiSense XML

Size 10 bar (145 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 2 CO single-pole contacts

OsiSense XMLC pressure switches		With setting scale		30 bar (435 psi) overpressure With setting scale
				
Adjustable range of switching point (PH) (Rising pressure)		**0.7…10 bar (10.15…145 psi)**		
Electrical connection		Terminals		
Fluid connection		G 1/4 (female)	1/4"-18 NPTF (female)	G 1/4 (female)
References *(1)*				
Fluids controlled *(2)*	Hydraulic oils, fresh water, air, up to + 70 °C	–	–	**XMLCS10A2S12**
	Hydraulic oils, fresh water, air, up to + 160 °C	**XMLC010B2S12**	**XMLC010B2S13**	–
	Corrosive fluids, up to + 160 °C Sea water, up to + 30 °C	**XMLC010C2S12**	**XMLC010C2S13**	–
Weight (kg)		0.685	0.685	3.500
Complementary characteristics not shown under general characteristics (page 17)				
Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	0.45 bar (6.53 psi)		0.25 bar (3.62 psi)
	Min. at high setting *(4)*	0.70 bar (10.15 psi)		0.65 bar (9.42 psi)
	Max. at high setting	8 bar (116 psi)		5.6 bar (81.2 psi)
Maximum permissible pressure	Per cycle	12.5 bar (181.25 psi)		30 bar (435 psi)
	Accidental	22.5 bar (326.25 psi)		37.5 bar (543.75 psi)
Destruction pressure		45 bar (652.5 psi)		67.5 bar (978.75 psi)
Mechanical life		5 x 10^6 operating cycles		2 x 10^6 operating cycles
Cable entry for terminal models		1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm		

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLC010B2S12** becomes **XMLC010B2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: ± 0.05 bar (± 0.72 psi)
(4) Deviation of the differential at high setting point for switches of the same size: ± 0.01 bar (± 1.45 psi)

Operating curves





1 Maximum differential
2 Minimum differential

— Adjustable value

Connection

Terminal model



Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical pressure switches

OsiSense XML

Size 10 bar (145 psi)
Dual stage, fixed differential, for detection at each threshold
Switches with 2 CO single-pole contacts

OsiSense XMLD pressure switches | **Without setting scale**



Adjustable range of each switching point (Rising pressure)	2nd stage switching point (PH2)	**1.2…10 bar (17.4…145 psi)**
	1st stage switching point (PH1)	**0.52…9.32 bar (7.54…135.14 psi)**
Spread between 2 stages (PH2 - PH1)		**0.68…5.8 bar (9.86…84.1 psi)**
Fluid connection		G 1/4 (female)
Electrical connection		Terminals

References

Fluids controlled *(1)*	Hydraulic oils, fresh water, air, up to + 160 °C	**XMLD010B1S11**	**XMLD010B1S12**
	Corrosive fluids, up to + 160 °C Sea water, up to + 30 °C	**XMLD010C1S11**	–
Weight (kg)		0.705	0.705

Complementary characteristics not shown under general characteristics (page 17)

Natural differential (subtract from PH1/PH2 to give PB1/PB2)	At low setting *(2)*	0.45 bar (6.53 psi)	
	At high setting *(3)*	0.6 bar (8.7 psi)	
Maximum permissible pressure	Per cycle	12.5 bar (181.25 psi)	
	Accidental	22.5 bar (326.25 psi)	
Destruction pressure		45 bar (652.5 psi)	
Mechanical life		5 x 10^6 operating cycles	
Cable entry for terminal models		1 entry tapped for no. 13 cable gland	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm	

(1) For component materials of units in contact with the fluid, see pages 72 and 73.
(2) Deviation of the differential at low setting point for switches of the same size: ± 0.05 bar (± 0.72 psi)
(3) Deviation of the differential at high setting point for switches of the same size: ± 0.1 bar (± 1.45 psi)

Operating curves

High setting tripping points of contacts 1 and 2



1 Maximum differential
2 Minimum differential

Natural differential of contacts 1 and 2



EF Contact 1 (stage 1)
GH Contact 2 (stage 2)



— Adjustable value
--- Non adjustable value

Connection

Terminal model



Other versions — For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches

OsiSense XML

Size 20 bar (290 psi)
Fixed differential, for detection of a single threshold
Switches with 1 CO single-pole contact

OsiSense XMLA pressure switches		With setting scale		
				
Adjustable range of switching point (PH) (Rising pressure)		**1…20 bar (14.5…290 psi)**		
Electrical connection		DIN connector	Terminals	
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*				
Fluids controlled *(2)*	Hydraulic oils, fresh water, air, up to + 70 °C	**XMLA020A2C11**	**XMLA020A2S12**	**XMLA020A2S13**
	Hydraulic oils, fresh water, air, up to + 160 °C	**XMLA020B2C11**	**XMLA020B2S12**	**–**
	Corrosive fluids, up to + 160 °C Sea water, up to + 30 °C	**XMLA020C2C11**	**XMLA020C2S12**	**–**
	Viscous products, up to + 160 °C (G 1¼" fluid connection)	**XMLA020P2C11**	**XMLA020P2S12**	**–**
Weight (kg)		0.715	0.685	0.685
Complementary characteristics not shown under general characteristics (page 17)				
Natural differential (subtract from PH to give PB)	At low setting *(3)*	0.4 bar (5.8 psi)		
	At high setting *(3)*	1 bar (14.5 psi)		
Maximum permissible pressure	Per cycle	25 bar (362.5 psi)		
	Accidental	45 bar (652.5 psi)		
Destruction pressure		90 bar (1305 psi)		
Mechanical life		5 x 10^6 operating cycles		
Connection		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm		

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLA020A2S12** becomes **XMLA020A2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at high setting point for switches of the same size: ± 0.1 bar (± 1.45 psi)
Deviation of the differential at low setting point: ± 0.2 bar (± 2.9 psi)

Operating curves





— Adjustable value
--- Non adjustable value

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical pressure switches

OsiSense XML

Size 20 bar (290 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 1 CO single-pole contact

OsiSense XMLB pressure switches		With setting scale			30 bar (435 psi) overpressure With setting scale
					
Adjustable range of switching point (PH) (Rising pressure)		**1.3…20 bar (18.9…290 psi)**			
Electrical connection		DIN connector	Terminals		
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)	G 1/4 (female)
References *(1)*					
Fluids controlled *(2)*	Hydraulic oils, fresh water, air, up to + 70 °C	**XMLB020A2C11**	**XMLB020A2S12**	**XMLB020A2S13**	**XMLBS20A2S12**
	Hydraulic oils, fresh water, air, up to + 160 °C	**XMLB020B2C11**	**XMLB020B2S12**	**XMLB020B2S13**	**–**
	Corrosive fluids, up to + 160 °C Sea water, up to + 30 °C	**XMLB020C2C11**	**XMLB020C2S12**	**–**	**–**
	Viscous products, up to + 160 °C (G 1¼" fluid connection)	**XMLB020P2C11**	**XMLB020P2S12**	**–**	**–**
Weight (kg)		0.735	0.705	0.705	3.500
Complementary characteristics not shown under general characteristics (page 17)					
Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	1 bar (14.5 psi)			0.95 bar (13.78 psi)
	Min. at high setting *(3)*	1.6 bar (23.20 psi)			1.45 bar (21.03 psi)
	Max. at high setting	11 bar (159.5 psi)			12.6 bar (182.7 psi)
Maximum permissible pressure	Per cycle	25 bar (362.5 psi)			30 bar (435 psi)
	Accidental	45 bar (652.5 psi)			37.5 bar (543.75 psi)
Destruction pressure		90 bar (1305 psi)			67.5 bar (978.75 psi)
Mechanical life		5 x 10^6 operating cycles			2 x 10^6 operating cycles
Connection		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm			

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLB020A2S12** becomes **XMLB020A2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: ± 0.25 bar (± 3.63 psi)

Operating curves





1 Maximum differential
2 Minimum differential

— Adjustable value

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions	For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches

OsiSense XML

Size 20 bar (290 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 2 CO single-pole contacts

OsiSense XMLC pressure switches	With setting scale		30 bar (435 psi) overpressure With setting scale
			
Adjustable range of switching point (PH) (Rising pressure)	**1.3…20 bar (18.85…290 psi)**		
Electrical connection	Terminals		
Fluid connection	G 1/4 (female)	1/4"-18 NPTF (female)	G 1/4 (female)
References *(1)*			
Fluids controlled *(2)* — Hydraulic oils, fresh water, air, up to + 70 °C	–	–	**XMLCS20A2S12**
Hydraulic oils, fresh water, air, up to + 160 °C	**XMLC020B2S12**	**XMLC020B2S13**	–
Corrosive fluids, up to + 160 °C Sea water, up to + 30 °C	**XMLC020C2S12**	**XMLC020C2S13**	–
Weight (kg)	0.685	0.685	3.500
Complementary characteristics not shown under general characteristics (page 17)			
Possible differential (subtract from PH to give PB) — Min. at low setting *(3)*	0.7 bar (10.15 psi)		0.7 bar (10.15 psi)
Min. at high setting *(3)*	1 bar (14.5 psi)		1.15 bar (16.67 psi)
Max. at high setting	11 bar (159.5 psi)		11.70 bar (169.6 psi)
Maximum permissible pressure — Per cycle	25 bar (362.5 psi)		30 bar (435 psi)
Accidental	45 bar (652.5 psi)		37.5 bar (543.75 psi)
Destruction pressure	90 bar (1305 psi)		67.5 bar (978.75 psi)
Mechanical life	5 x 10^6 operating cycles		2 x 10^6 operating cycles
Cable entry for terminal models	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm
Pressure switch type	Diaphragm		

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLC020B2S12** becomes **XMLC020B2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: ± 0.2 bar (± 2.9 psi)

Operating curves





1 Maximum differential
2 Minimum differential

— Adjustable value

Connection

Terminal model



Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical pressure switches

OsiSense XML

Size 20 bar (290 psi)
Dual stage, fixed differential, for detection at each threshold
Switches with 2 CO single-pole contacts

OsiSense XMLD pressure switches | **Without setting scale**



Adjustable range of each switching point (Rising pressure)	2nd stage switching point (PH2)	**2.14…20 bar (31.03…290 psi)**	
	1st stage switching point (PH1)	**0.9…18.76 bar (13.05…272.02 psi)**	
Spread between 2 stages (PH2 - PH1)		**1.24…9.55 bar (17.98…138.48 psi)**	
Electrical connection		Terminals	
Fluid connection		G 1/4 (female)	1/4"-18 NPTF (female)

References *(1)*

Fluids controlled *(2)*	Hydraulic oils, fresh water, air, up to + 160 °C	**XMLD020B1S12**	**XMLD020B1S13**
	Corrosive fluids, up to + 160 °C Sea water, up to + 30 °C	**XMLD020C1S12**	**–**
Weight (kg)		0.705	0.705

Complementary characteristics not shown under general characteristics (page 17)

Natural differential (subtract from PH1/PH2 to give PB1/PB2)	At low setting *(3)*	0.7 bar (10.15 psi)	
	At high setting *(4)*	1.3 bar (18.85 psi)	
Maximum permissible pressure	Per cycle	25 bar (362.5 psi)	
	Accidental	45 bar (652.5 psi)	
Destruction pressure		90 bar (1305 psi)	
Mechanical life		5 x 10^6 operating cycles	
Cable entry for terminal models		1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm	

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLD020B1S12** becomes **XMLD020B1S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: ± 0.15 bar (± 2.18 psi)
(4) Deviation of the differential at high setting point for switches of the same size: ± 0.3 bar (± 4.35 psi)

Operating curves

High setting tripping points of contacts 1 and 2



1 Maximum differential
2 Minimum differential

Natural differential of contacts 1 and 2



EF Contact 1 (stage 1)
GH Contact 2 (stage 2)



— Adjustable value
--- Non adjustable value

Connection model

Terminal model



Other versions — For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches

OsiSense XML

Size 35 bar (507.5 psi)
Fixed differential, for detection of a single threshold
Switches with 1 CO single-pole contact

OsiSense XMLA pressure switches | **With setting scale**





Adjustable range of switching point (PH) (Rising pressure)		**1.5…35 bar (21.75…507.5 psi)**		
Electrical connection		DIN connector	Terminals	
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*				
Fluids controlled *(2)*	Hydraulic oils, fresh water, air, up to + 70 °C	**XMLA035A2C11**	**XMLA035A2S12**	**XMLA035A2S13**
	Hydraulic oils, fresh water, air, up to + 160 °C	**XMLA035B2C11**	**XMLA035B2S12**	**–**
	Corrosive fluids, up to + 160 °C Sea water, up to + 30 °C	**XMLA035C2C11**	**XMLA035C2S12**	**–**
	Viscous products, up to + 160 °C (G 1¼" fluid connection)	**XMLA035P2C11**	**XMLA035P2S12**	**–**
Weight (kg)		0.725	0.695	0.695
Complementary characteristics not shown under general characteristics (page 17)				
Natural differential (subtract from PH to give PB)	At low setting *(3)*	1.25 bar (18.12 psi)		
	At high setting *(3)*	1.25 bar (18.12 psi)		
Maximum permissible pressure	Per cycle	45 bar (652.5 psi)		
	Accidental	80 bar (1160 psi)		
Destruction pressure		160 bar (2320 psi)		
Mechanical life		5 x 10^6 operating cycles		
Connection		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm		

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLA035A2S12** becomes **XMLA035A2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: ± 0.25 bar (± 3.62 psi)

Operating curves





— Adjustable value
--- Non adjustable value

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches

OsiSense XML

Size 35 bar (507.5 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 1 CO single-pole contact

OsiSense XMLB pressure switches | **With setting scale**





Adjustable range of switching point (PH) (Rising pressure)		**3.5…35 bar (50.75…507.5 psi)**		
Electrical connection		DIN connector	Terminals	
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*				
Fluids controlled *(2)*	Hydraulic oils, fresh water, air, up to + 70 °C	**XMLB035A2C11**	**XMLB035A2S12**	**XMLB035A2S13**
	Hydraulic oils, fresh water, air, up to + 160 °C	**XMLB035B2C11**	**XMLB035B2S12**	**–**
	Corrosive fluids, up to + 160 °C Sea water, up to + 30 °C	**XMLB035C2C11**	**XMLB035C2S12**	**–**
	Viscous products, up to + 160 °C (G 1¼" fluid connection)	**–**	**XMLB035P2S12**	**–**
Weight (kg)		0.745	0.715	0.715
Complementary characteristics not shown under general characteristics (page 17)				
Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	1.7 bar (24.65 psi)		
	Min. at high setting *(3)*	2.55 bar (36.97 psi)		
	Max. at high setting	20 bar (290 psi)		
Maximum permissible pressure	Per cycle	45 bar (652.5 psi)		
	Accidental	80 bar (1160 psi)		
Destruction pressure		160 bar (2320 psi)		
Mechanical life		5 x 10^6 operating cycles		
Connection		EN 175301-803-A connector (ex-DIN 43650A), 4-pin male. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm		

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLB035A2S12** becomes **XMLB035A2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: - 0.5 bar, + 0.7 bar (- 7.25 psi, + 10.15 psi).

Operating curves





1 Maximum differential
2 Minimum differential

— Adjustable value

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches

OsiSense XML

Size 35 bar (507.5 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 2 CO single-pole contacts

OsiSense XMLC pressure switches	**With setting scale**	
		
Adjustable range of switching point (PH) (Rising pressure)	**3.5…35 bar (50.75…507.5 psi)**	
Electrical connection	Terminals	
Fluid connection	G 1/4 (female)	1/4”-18 NPTF (female)

References *(1)*

Fluids controlled *(2)*	Hydraulic oils, fresh water, air, up to + 160 °C	**XMLC035B2S12**	**XMLC035B2S13**
	Corrosive fluids, up to + 160 °C Sea water, up to + 30 °C	**XMLC035C2S12**	**XMLC035C2S13**
Weight (kg)		0.695	0.695

Complementary characteristics not shown under general characteristics (page 17)

Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	1 bar (14.5 psi)	
	Min. at high setting *(4)*	1.5 bar (21.75 psi)	
	Max. at high setting	22 bar (319 psi)	
Maximum permissible pressure	Per cycle	45 bar (652.5 psi)	
	Accidental	80 bar (1160 psi)	
Destruction pressure		160 bar (2320 psi)	
Mechanical life		5 x 10^6 operating cycles	
Cable entry for terminal models		1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2”-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm	

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLC035B2S12** becomes **XMLC035B2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: ± 0.2 bar (± 2.9 psi)
(4) Deviation of the differential at high setting point for switches of the same size: ± 0.5 bar (± 7.25 psi)

Operating curves





1 Maximum differential
2 Minimum differential

— Adjustable value

Connection

Terminal model



Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical pressure switches

OsiSense XML

Size 35 bar (507.5 psi)
Dual stage, fixed differential, for detection at each threshold
Switches with 2 CO single-pole contacts

OsiSense XMLD pressure switches | **Without setting scale**



Adjustable range of each switching point (Rising pressure)	2nd stage switching point (PH2)	**4.4…35 bar (63.8…507.5 psi)**
	1st stage switching point (PH1)	**1.9…32.5 bar (27.55…471.25 psi)**
Spread between 2 stages (PH2 - PH1)		**2.5…20.4 bar (36.25…295.8 psi)**
Electrical connection		Terminals
Fluid connection		G 1/4 (female)

References *(1)*

Fluids controlled *(2)*	Hydraulic oils, fresh water, air, up to + 160 °C	**XMLD035B1S12**
Weight (kg)		0.715

Complementary characteristics not shown under general characteristics (page 17)

Natural differential (subtract from PH1/PH2 to give PB1/PB2)	At low setting *(3)*	1.5 bar (21.75 psi)
	At high setting *(4)*	2.6 bar (37.7 psi)
Maximum permissible pressure	Per cycle	45 bar (652.5 psi)
	Accidental	80 bar (1160 psi)
Destruction pressure		160 bar (2320 psi)
Mechanical life		5 x 10^6 operating cycles
Cable entry for terminal models		1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Diaphragm

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLD035B1S12** becomes **XMLD035B1S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: ± 0.3 bar (± 4.35 psi)
(4) Deviation of the differential at high setting point for switches of the same size: ± 0.7 bar (± 10.15 psi)

Operating curves

High setting tripping points of contacts 1 and 2



1 Maximum differential
2 Minimum differential

Natural differential of contacts 1 and 2



EF Contact 1 (stage 1)
GH Contact 2 (stage 2)



— Adjustable value
--- Non adjustable value

Connection

Terminal model



Other versions — For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches

OsiSense XML

Size 70 bar (1015 psi)
Fixed differential, for detection of a single threshold
Switches with 1 CO single-pole contact

OsiSense XMLA pressure switches		With setting scale		
				
Adjustable range of switching point (PH) (Rising pressure)		**5…70 bar (72.5…1015 psi)**		
Electrical connection		DIN connector	Terminals	
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*				
Fluids controlled *(2)*	Hydraulic oils, up to + 160 °C	**XMLA070D2C11**	**XMLA070D2S12**	**XMLA070D2S13**
	Fresh water, up to + 160 °C	**XMLA070E2C11**	**XMLA070E2S12**	**XMLA070E2S13**
	Corrosive fluids, air, up to + 160 °C	**XMLA070N2C11**	**XMLA070N2S12**	**–**
Weight (kg)		0.725	0.695	0.695
Complementary characteristics not shown under general characteristics (page 17)				
Natural differential (subtract from PH to give PB)	At low setting *(3)*	3 bar (43.5 psi)		
	At high setting *(3)*	9.5 bar (137.75 psi)		
Maximum permissible pressure	Per cycle	90 bar (1035 psi)		
	Accidental	160 bar (2320 psi)		
Destruction pressure		320 bar (4640 psi)		
Mechanical life		6 x 10^6 operating cycles		
Connection		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Piston		

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLA070D2S12** becomes **XMLA070D2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: ± 1 bar (± 14.5 psi)

Operating curves





— Adjustable value
--- Non adjustable value

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical pressure switches

OsiSense XML

Size 70 bar (1015 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 1 CO single-pole contact

OsiSense XMLB pressure switches | **With setting scale**





Adjustable range of switching point (PH) (Rising pressure)		**7…70 bar (101.5…1015 psi)**		
Electrical connection		DIN connector	Terminals	
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*				
Fluids controlled *(2)*	Hydraulic oils, up to + 160 °C	**XMLB070D2C11**	**XMLB070D2S12**	**XMLB070D2S13**
	Fresh water, up to + 160 °C	**XMLB070E2C11**	**XMLB070E2S12**	**–**
	Corrosive fluids, air, up to + 160 °C	**XMLB070N2C11**	**XMLB070N2S12**	**–**
Weight (kg)		0.745	0.715	0.715
Complementary characteristics not shown under general characteristics (page 17)				
Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	4.7 bar (68.15 psi)		
	Min. at high setting *(4)*	9.5 bar (137.75 psi)		
	Max. at high setting	50 bar (725 psi)		
Maximum permissible pressure	Per cycle	90 bar (1035 psi)		
	Accidental	160 bar (2320 psi)		
Destruction pressure		320 bar (4640 psi)		
Mechanical life		6 x 10^6 operating cycles		
Connection		EN 175301-803-A connector (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Piston		

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLB070D2S12** becomes **XMLB070D2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: - 0.4 bar, + 0.7 bar (- 5.8 psi, + 10.15 psi).
(4) Deviation of the differential at high setting point for switches of the same size: - 0.6 bar, + 0.8 bar (- 8.7 psi, + 11.6 psi).

Operating curves





1 Maximum differential
2 Minimum differential

— Adjustable value

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches

OsiSense XML

Size 70 bar (1015 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 2 CO single-pole contacts

OsiSense XMLC pressure switches	**With setting scale**	
		
Adjustable range of switching point (PH) (Rising pressure)	**7…70 bar (101.5…1015 psi)**	
Electrical connection	Terminals	
Fluid connection	G 1/4 (female)	1/4”-18 NPTF (female)

References *(1)*

Fluids controlled *(2)*	Hydraulic oils, up to + 160 °C	**XMLC070D2S12**	**XMLC070D2S13**
	Fresh water, up to + 160 °C	**XMLC070E2S12**	**–**
	Corrosive fluids, air, up to + 160 °C	**XMLC070N2S12**	**–**
Weight (kg)		0.695	0.695

Complementary characteristics not shown under general characteristics (page 17)

Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	4.5 bar (65.25 psi)	
	Min. at high setting *(3)*	9.5 bar (137.75 psi)	
	Max. at high setting	60 bar (870 psi)	
Maximum permissible pressure	Per cycle	90 bar (1035 psi)	
	Accidental	160 bar (2320 psi)	
Destruction pressure		320 bar (4640 psi)	
Mechanical life		6 x 10^6 operating cycles	
Cable entry for terminal models		1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2”-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Piston	

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLC070D2S12** becomes **XMLC070D2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: ± 0.8 bar (± 11.6 psi)

Operating curves





1 Maximum differential
2 Minimum differential

— Adjustable value

Connection

Terminal model



Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical pressure switches

OsiSense XML

Size 70 bar (1015 psi)
Dual stage, fixed differential, for detection at each threshold
Switches with 2 CO single-pole contacts

OsiSense XMLD pressure switches		Without setting scale	
Adjustable range of each switching point (Rising pressure)	2nd stage switching point (PH2)	**9.4…70 bar (136.3…1015 psi)**	
	1st stage switching point (PH1)	**6.6…67.2 bar (95.7…974.4 psi)**	
Spread between 2 stages (PH2 - PH1)		**2.8…46 bar (40.6…667 psi)**	
Electrical connection		Terminals	
Fluid connection		G 1/4 (female)	1/4"-18 NPTF (female)



References *(1)*

Fluids controlled *(2)*	Hydraulic oils, up to + 160 °C	**XMLD070D1S12**	**XMLD070D1S13**
	Corrosive fluids, air, up to + 160 °C	**XMLD070N1S12**	**–**
Weight (kg)		0.715	0.715

Complementary characteristics not shown under general characteristics (page 17)

Natural differential (subtract from PH1/PH2 to give PB1/PB2)	At low setting *(3)*	5 bar (72.5 psi)	
	At high setting *(4)*	9.5 bar (137.75 psi)	
Maximum permissible pressure	Per cycle	90 bar (1035 psi)	
	Accidental	160 bar (2320 psi)	
Destruction pressure		320 bar (4640 psi)	
Mechanical life		6 x 10^6 operating cycles	
Cable entry for terminal models		1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Piston	

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLD070D1S12** becomes **XMLD070D1S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: ± 1.5 bar (± 21.75 psi)
(4) Deviation of the differential at high setting point for switches of the same size: ± 2 bar *(± 29 psi)*

Operating curves

High setting tripping points of contacts 1 and 2



1 Maximum differential
2 Minimum differential

Natural differential of contacts 1 and 2



EF Contact 1 (stage 1)
GH Contact 2 (stage 2)



— Adjustable value
--- Non adjustable value

Connection

Terminal model



Other versions	For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches
OsiSense XML
Size 160 bar (2320 psi)
Fixed differential, for detection of a single threshold
Switches with 1 CO single-pole contact

OsiSense XMLA pressure switches		**With setting scale**		
				
Adjustable range of switching point (PH) (Rising pressure)		**10…160 bar (145…2320 psi)**		
Electrical connection		DIN connector	Terminals	
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*				
Fluids controlled *(2)*	Hydraulic oils, up to + 160 °C	**XMLA160D2C11**	**XMLA160D2S12**	**XMLA160D2S13**
	Fresh water, up to + 160 °C	**XMLA160E2C11**	**XMLA160E2S12**	**XMLA160E2S13**
	Corrosive fluids, air, up to + 160 °C	**XMLA160N2C11**	**XMLA160N2S12**	**–**
Weight (kg)		0.780	0.750	0.750
Complementary characteristics not shown under general characteristics (page 17)				
Natural differential (subtract from PH to give PB)	At low setting *(3)*	5.5 bar (79.75 psi)		
	At high setting *(4)*	18 bar (261 psi)		
Maximum permissible pressure	Per cycle	200 bar (2900 psi)		
	Accidental	360 bar (5220 psi)		
Destruction pressure		720 bar (10,440 psi)		
Mechanical life		6 x 10^6 operating cycles		
Connection		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Piston		

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLA160D2S12** becomes **XMLA160D2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: ± 1 bar (± 14.5 psi)
(4) Deviation of the differential at high setting point for switches of the same size: ± 3 bar (± 43.5 psi)

Operating curves





— Adjustable value
--- Non adjustable value

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical pressure switches
OsiSense XML
Size 160 bar (2320 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 1 CO single-pole contact

OsiSense XMLB pressure switches | **With setting scale**





Adjustable range of switching point (PH) (Rising pressure)		**10…160 bar (145…2320 psi)**		
Electrical connection		DIN connector	Terminals	
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*				
Fluids controlled *(2)*	Hydraulic oils, up to + 160 °C	**XMLB160D2C11**	**XMLB160D2S12**	**XMLB160D2S13**
	Fresh water, up to + 160 °C	**XMLB160E2C11**	**XMLB160E2S12**	**–**
	Corrosive fluids, air, up to + 160 °C	**XMLB160N2C11**	**XMLB160N2S12**	**–**
Weight (kg)		0.780	0.750	0.750
Complementary characteristics not shown under general characteristics (page 17)				
Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	9.3 bar (134.85 psi)		
	Min. at high setting *(4)*	20.8 bar (301.6 psi)		
	Max. at high setting	100 bar (1450 psi)		
Maximum permissible pressure	Per cycle	200 bar (2900 psi)		
	Accidental	360 bar (5220 psi)		
Destruction pressure		720 bar (10,440 psi)		
Mechanical life		6 x 10^6 operating cycles		
Connection		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Piston		

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLB160D2S12** becomes **XMLB160D2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: - 1.8 bar, + 1.5 bar (- 26.1 psi, + 21.75 psi).
(4) Deviation of the differential at high setting point for switches of the same size: - 1.9 bar, + 1.6 bar (- 27.55 psi, + 23.2 psi).

Operating curves





1 Maximum differential
2 Minimum differential
— Adjustable value

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches

OsiSense XML

Size 160 bar (2320 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 2 CO single-pole contacts

OsiSense XMLC pressure switches		**With setting scale**	
			
Adjustable range of switching point (PH) (Rising pressure)		**12…160 bar (174…2320 psi)**	
Electrical connection		Terminals	
Fluid connection		G 1/4 (female)	1/4”-18 NPTF (female)
References *(1)*			
Fluids controlled *(2)*	Hydraulic oils, up to + 160 °C	**XMLC160D2S12**	**XMLC160D2S13**
	Fresh water, up to + 160 °C	**XMLC160E2S12**	–
	Corrosive fluids, air, up to + 160 °C	**XMLC160N2S12**	–
Weight (kg)		0.750	0.750
Complementary characteristics not shown under general characteristics (page 17)			
Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	9 bar (130.5 psi)	
	Min. at high setting *(3)*	21 bar (304.5 psi)	
	Max. at high setting	110 bar (1590 psi)	
Maximum permissible pressure	Per cycle	200 bar (2900 psi)	
	Accidental	360 bar (5220 psi)	
Destruction pressure		720 bar (10 440 psi)	
Mechanical life		6 x 10^6 operating cycles	
Cable entry for terminal models		1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2”-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Piston	

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLC160D2S12** becomes **XMLC160D2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: ± 0.9 bar (± 13.05 psi)

Operating curves





Connection

Terminal model



1 Maximum differential
2 Minimum differential

— Adjustable value

Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical pressure switches

OsiSense XML

Size 160 bar (2320 psi)
Dual stage, fixed differential, for detection at each threshold
Switches with 2 CO single-pole contacts

OsiSense XMLD pressure switches		Without setting scale	
			
Adjustable range of each switching point (Rising pressure)	2nd stage switching point (PH2)	**16.5…160 bar (239.25…2320 psi)**	
	1st stage switching point (PH1)	**10.5…154 bar (152.25…2233 psi)**	
Spread between 2 stages (PH2 - PH1)		**6…83 bar (87…1203.5 psi)**	
Electrical connection		Terminals	
Fluid connection		G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*			
Fluids controlled *(2)*	Hydraulic oils, up to + 160 °C	**XMLD160D1S12**	**XMLD160D1S13**
	Fresh water, up to + 160 °C	**XMLD160E1S12**	–
Weight (kg)		0.750	0.750
Complementary characteristics not shown under general characteristics (page 17)			
Natural differential (subtract from PH1/PH2 to give PB1/PB2)	At low setting *(3)*	8.8 bar (127.6 psi)	
	At high setting *(4)*	20 bar (290 psi)	
Maximum permissible pressure	Per cycle	200 bar (2900 psi)	
	Accidental	360 bar (5220 psi)	
Destruction pressure		720 bar (10,440 psi)	
Mechanical life		6 x 10^6 operating cycles	
Cable entry for terminal models		1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Piston	

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLD160D1S12** becomes **XMLD160D1S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: ± 1.5 bar (± 21.75 psi)
(4) Deviation of the differential at high setting point for switches of the same size: ± 7 bar (± 101.5 psi)

Operating curves

High setting tripping points of contacts 1 and 2



1 Maximum differential
2 Minimum differential

Natural differential of contacts 1 and 2



EF Contact 1 (stage 1)
GH Contact 2 (stage 2)



— Adjustable value
--- Non adjustable value

Connection

Terminal model



Other versions — For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches
OsiSense XML
Size 300 bar (4350 psi)
Fixed differential, for detection of a single threshold
Switches with 1 CO single-pole contact

OsiSense XMLA pressure switches		With setting scale		
				
Adjustable range of switching point (PH) (Rising pressure)		**20…300 bar (290…4350 psi)**		
Electrical connection		DIN connector	Terminals	
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*				
Fluids controlled *(2) (5)*	Hydraulic oils, up to + 160 °C	**XMLA300D2C11**	**XMLA300D2S12**	**XMLA300D2S13**
	Fresh water, up to + 160 °C	**XMLA300E2C11**	**XMLA300E2S12**	**XMLA300E2S13**
	Corrosive fluids, air, up to + 160 °C	**XMLA300N2C11**	**XMLA300N2S12**	**–**
Weight (kg)		0.780	0.750	0.750
Complementary characteristics not shown under general characteristics (page 17)				
Natural differential (subtract from PH to give PB)	At low setting *(3)*	16.5 bar (239.25 psi)		
	At high setting *(4)*	35 bar (507.5 psi)		
Maximum permissible pressure	Per cycle	375 bar (5437.5 psi)		
	Accidental	675 bar (9787.5 psi)		
Destruction pressure		1350 bar (19 575 psi)		
Mechanical life		3 x 10^6 operating cycles		
Connection		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Piston		

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLA300D2S12** becomes **XMLA300D2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: ± 3 bar (± 43.5 psi)
(4) Deviation of the differential at high setting point for switches of the same size: ± 6 bar (± 87 psi)
(5) Only for control of group 2 fluids, in accordance with directive 97/23/EEC.

Operating curves





— Adjustable value
--- Non adjustable value

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical pressure switches
OsiSense XML
Size 300 bar (4350 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 1 CO single-pole contact

OsiSense XMLB pressure switches | **With setting scale**





Adjustable range of switching point (PH) (Rising pressure)		**22…300 bar (319…4350 psi)**		
Electrical connection		DIN connector	Terminals	
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*				
Fluids controlled *(2)(5)*	Hydraulic oils, up to + 160 °C	**XMLB300D2C11**	**XMLB300D2S12**	**XMLB300D2S13**
	Fresh water, up to + 160 °C	**XMLB300E2C11**	**XMLB300E2S12**	**–**
	Corrosive fluids, air, up to + 160 °C	**XMLB300N2C11**	**XMLB300N2S12**	**–**
Weight (kg)		0.780	0.750	0.750
Complementary characteristics not shown under general characteristics (page 17)				
Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	19.4 bar (281.3 psi)		
	Min. at high setting *(4)*	37 bar (536.5 psi)		
	Max. at high setting	200 bar (2900 psi)		
Maximum permissible pressure	Per cycle	375 bar (5437.5 psi)		
	Accidental	675 bar (9787.5 psi)		
Destruction pressure		1350 bar (19,575 psi)		
Mechanical life		3 x 10^6 operating cycles		
Connection		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Piston		

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLB300D2S12** becomes **XMLB300D2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: - 1.5 bar, + 1.7 bar (- 21.75 psi, + 24.65 psi).
(4) Deviation of the differential at high setting point for switches of the same size: - 1 bar, + 4 bar (- 14.5 psi, + 58 psi).
(5) Only for control of group 2 fluids, in accordance with directive 97/23/EEC.

Operating curves





1 Maximum differential
2 Minimum differential
— Adjustable value

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches
OsiSense XML
Size 300 bar (4350 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 2 CO single-pole contacts

OsiSense XMLC pressure switches	**With setting scale**



Adjustable range of switching point (PH) (Rising pressure)		**22…300 bar (319…4350 psi)**
Electrical connection		Terminals
Fluid connection		G 1/4 (female)

References *(1)*

Fluids controlled *(2) (4)*	Hydraulic oils, up to + 160 °C	**XMLC300D2S12**
	Fresh water, up to + 160 °C	**XMLC300E2S12**
	Corrosive fluids, air, up to + 160 °C	**XMLC300N2S12**
Weight (kg)		0.750

Complementary characteristics not shown under general characteristics (page 17)

Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	16 bar (232 psi)
	Min. at high setting *(3)*	35 bar (507.5 psi)
	Max. at high setting	240 bar (3480 psi)
Maximum permissible pressure	Per cycle	375 bar (5437.5 psi)
	Accidental	675 bar (9787.5 psi)
Destruction pressure		1350 bar (19 575 psi)
Mechanical life		3 x 10^6 operating cycles
Cable entry for terminal models		1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Piston

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLC300D2S12** becomes **XMLC300D2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: ± 0.9 bar (± 13.05 psi)
(4) Only for control of group 2 fluids, in accordance with directive 97/23/EEC.

Operating curves





1 Maximum differential
2 Minimum differential

— Adjustable value

Connection

Terminal model



Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical pressure switches
OsiSense XML
Size 300 bar (4350 psi)
Dual stage, fixed differential, for detection at each threshold
Switches with 2 CO single-pole contacts

OsiSense XMLD pressure switches		**Without setting scale**	
			
Adjustable range of each switching point (Rising pressure)	2nd stage switching point (PH2)	**36…300 bar (522…4350 psi)**	
	1st stage switching point (PH1)	**25…289 bar (362.5…4190.5 psi)**	
Spread between 2 stages (PH2 - PH1)		**11…189 bar (159.5…2740.5 psi)**	
Electrical connection		Terminals	
Fluid connection		G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*			
Fluids controlled *(2) (5)*	Hydraulic oils, up to + 160 °C	**XMLD300D1S12**	**XMLD300D1S13**
	Fresh water, up to + 160 °C	**XMLD300E1S12**	–
	Corrosive fluids, air, up to + 160 °C	**XMLD300N1S12**	–
Weight (kg)		0.750	0.750
Complementary characteristics not shown under general characteristics (page 17)			
Natural differential (subtract from PH1/PH2 to give PB1/PB2)	At low setting *(3)*	17 bar (246.5 psi)	
	At high setting *(4)*	42 bar (609 psi)	
Maximum permissible pressure	Per cycle	375 bar (5437.5 psi)	
	Accidental	675 bar (9787.5 psi)	
Destruction pressure		1350 bar (19,575 psi)	
Mechanical life		3 x 10^6 operating cycles	
Cable entry for terminal models		1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Piston	

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLD300D1S12** beomes **XMLD300D1S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: ± 2.5 bar (± 36.25 psi)
(4) Deviation of the differential at high setting point for switches of the same size: ± 9 bar (± 130.5 psi)
(5) Only for control of group 2 fluids, in accordance with directive 97/23/EEC.

Operating curves

High setting tripping points of contacts 1 and 2



1 Maximum differential
2 Minimum differential

Natural differential of contacts 1 and 2



EF Contact 1 (stage 1)
GH Contact 2 (stage 2)



— Adjustable value
--- Non adjustable value

Connection

Terminal model



Other versions — For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches
OsiSense XML
Size 500 bar (7250 psi)
Fixed differential, for detection of a single threshold
Switches with 1 CO single-pole contact

OsiSense XMLA pressure switches		**With setting scale**		
				
Adjustable range of switching point (PH) (Rising pressure)		**30…500 bar (435…7250 psi)**		
Electrical connection		DIN connector	Terminals	
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*				
Fluids controlled *(2) (5)*	Hydraulic oils, up to + 160 °C	**XMLA500D2C11**	**XMLA500D2S12**	**XMLA500D2S13**
	Fresh water, up to + 160 °C	**XMLA500E2C11**	**XMLA500E2S12**	**XMLA500E2S13**
	Corrosive fluids, air, up to + 160 °C	**XMLA500N2C11**	**XMLA500N2S12**	**–**
Weight (kg)		0.780	0.750	0.750
Complementary characteristics not shown under general characteristics (page 17)				
Natural differential (subtract from PH to give PB)	At low setting *(3)*	20 bar (290 psi)		
	At high setting *(4)*	45 bar (652.5 psi)		
Maximum permissible pressure	Per cycle	625 bar (9062.5 psi)		
	Accidental	1125 bar (16,312.5 psi)		
Destruction pressure		2250 bar (32,625 psi)		
Mechanical life		3 x 10^6 operating cycles		
Connection		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Piston		

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLA500D2S12** becomes **XMLA500D2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: ± 6 bar (± 87 psi)
(4) Deviation of the differential at high setting point for switches of the same size: ± 10 bar (± 145 psi)
(5) Only for control of group 2 fluids, in accordance with directive 97/23/EEC.

Operating curves





— Adjustable value
--- Non adjustable value

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical pressure switches
OsiSense XML
Size 500 bar (7250 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 1 CO single-pole contact

OsiSense XMLB pressure switches | **With setting scale**





Adjustable range of switching point (PH) (Rising pressure)		**30…500 bar (435…7250 psi)**		
Electrical connection		DIN connector	Terminals	
Fluid connection		G 1/4 (female)	G 1/4 (female)	1/4"-18 NPTF (female)
References *(1)*				
Fluids controlled *(2) (5)*	Hydraulic oils, up to + 160 °C	**XMLB500D2C11**	**XMLB500D2S12**	**XMLB500D2S13**
	Fresh water, up to + 160 °C	**XMLB500E2C11**	**XMLB500E2S12**	**–**
	Corrosive fluids, air, up to + 160 °C	**XMLB500N2C11**	**XMLB500N2S12**	**–**
Weight (kg)		0.780	0.750	0.750
Complementary characteristics not shown under general characteristics (page 17)				
Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	23 bar (333.5 psi)		
	Min. at high setting *(4)*	52.6 bar (762.7 psi)		
	Max. at high setting	300 bar (4350 psi)		
Maximum permissible pressure	Per cycle	625 bar (9062.5 psi)		
	Accidental	1125 bar (16,312.5 psi)		
Destruction pressure		2250 bar (32,625 psi)		
Mechanical life		3 x 10^6 operating cycles		
Connection		EN 175301-803-A (ex-DIN 43650A), 4-pin male connector. For suitable female connector, see page 68	1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm	1 entry tapped 1/2"-14 NPT for cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Piston		

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLB500D2S12** becomes **XMLB500D2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: - 2.6 bar, + 3.8 bar (- 37.7 psi, + 55.1 psi).
(4) Deviation of the differential at high setting point for switches of the same size: - 14.8 bar, + 11.2 bar (- 214.6 psi, + 162.4 psi).
(5) Only for control of group 2 fluids, in accordance with directive 97/23/EEC.

Operating curves





1 Maximum differential
2 Minimum differential

— Adjustable value

Connection

Terminal model



Connector model

Pressure switch connector pin view



1 → 11 and 13
2 → 12
3 → 14

Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure switches
OsiSense XML
Size 500 bar (7250 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 2 CO single-pole contacts

OsiSense XMLC pressure switches	With setting scale



Adjustable range of switching point (PH) (Rising pressure)		**30…500 bar (435…7250 psi)**
Electrical connection		Terminals
Fluid connection		G 1/4 (female)

References *(1)*

Fluids controlled *(2) (4)*	Hydraulic oils, up to + 160 °C	**XMLC500D2S12**
	Corrosive fluids, air, up to + 160 °C	**XMLC500N2S12**
Weight (kg)		0.750

Complementary characteristics not shown under general characteristics (page 17)

Possible differential (subtract from PH to give PB)	Min. at low setting *(3)*	19 bar (275.5 psi)
	Min. at high setting *(3)*	52 bar (754 psi)
	Max. at high setting	340 bar (4930 psi)
Maximum permissible pressure	Per cycle	625 bar (9062.5 psi)
	Accidental	1125 bar (16 312.5 psi)
Destruction pressure		2250 bar (32 625 psi)
Mechanical life		3 x 10^6 operating cycles
Cable entry for terminal models		1 entry tappedJe préfère acheter des.5 mm for ISO cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Piston

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLC500D2S12** becomes **XMLC500D2S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low and high setting points for switches of the same size: ± 0.9 bar (± 13.05 psi)
(4) Only for control of group 2 fluids, in accordance with directive 97/23/EEC.

Operating curves





1 Maximum differential
2 Minimum differential

— Adjustable value

Connection

Terminal model



Other versions

For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Accessories: page 68
Dimensions: pages 69 to 71

Electromechanical pressure switches
OsiSense XML
Size 500 bar (7250 psi)
Dual stage, fixed differential, for detection at each threshold
Switches with 2 CO single-pole contacts

OsiSense XMLD pressure switches		**Without setting scale**



Adjustable range of each switching point (Rising pressure)	2nd stage switching point (PH2)	**41…500 bar (594.5…7250 psi)**
	1st stage switching point (PH1)	**25…484 bar (362.5…7018 psi)**
Spread between 2 stages (PH2 - PH1)		**16…244 bar (232…3538 psi)**
Electrical connection		Terminals
Fluid connection		G 1/4 (female)

References *(1)*

Fluids controlled *(2) (5)*	Hydraulic oils, up to + 160 °C	**XMLD500D1S12**
Weight (kg)		0.750

Complementary characteristics not shown under general characteristics (page 17)

Natural differential (subtract from PH1/PH2 to give PB1/PB2)	At low setting *(3)*	21 bar (304.5 psi)
	At high setting *(4)*	65 bar (942.5 psi)
Maximum permissible pressure	Per cycle	625 bar (9062.5 psi)
	Accidental	1125 bar (16,312.5 psi)
Destruction pressure		2250 bar (32,625 psi)
Mechanical life		3 x 10^6 operating cycles
Cable entry for terminal models		1 entry tapped M20 x 1.5 mm for ISO cable gland, clamping capacity 7 to 13 mm
Pressure switch type		Piston

*(1) For 1 entry tapped for no. 13 cable gland, replace **S12** with **S11** (for example, **XMLD500D1S12** becomes **XMLD500D1S11**).*
(2) For component materials of units in contact with the fluid, see pages 72 and 73.
(3) Deviation of the differential at low setting point for switches of the same size: ± 3 bar (± 43.5 psi)
(4) Deviation of the differential at high setting point for switches of the same size: ± 10 bar (± 145 psi)
(5) Only for control of group 2 fluids, in accordance with directive 97/23/EEC.

Operating curves

High setting tripping points of contacts 1 and 2



1 Maximum differential
2 Minimum differential

Natural differential of contacts 1 and 2



EF Contact 1 (stage 1)
GH Contact 2 (stage 2)



— Adjustable value
--- Non adjustable value

Connection

Terminal model



Other versions	For pressure switches with alternative tapped cable entries, such as NPT, etc. please consult our Customer Care Centre.

Electromechanical pressure and vacuum switches

OsiSense XMLA, XMLB, XMLC and XMLD

Accessories and replacement parts



XMLZL006



XMLZL002



XMLZL003



XMLZL004



XMLZL001



XMLZL011



XMLZL005



XMLZA●●●,
XMLZB●●●



XMLZL010

XZCC43FCP40B

Accessories for pressure switches and vacuum switches

Description		Specific characteristics	For use with switches	Unit reference	Weight kg
Rear fixing bracket for vibrations > 2 gn		–	XML●L35 XML●001	**XMLZL006**	0.230
Additional top support bracket for vibrations > 4 gn		–	XMLAM01 XML●M05 XMLA004 XML●010… XML●500	**XMLZL002**	0.020
Knurled adjustment knob, Ø 36 mm fits over adjustment screws to facilitate setting		–	All models	**XMLZL003**	0.010
Fixing plate for replacing an XMJA or XMGB switch with an XML switch		–	XMLAM01 XML●M05 XMLA004 XML●010… XML●500	**XMLZL004**	0.110
Lead sealable protective cover to prevent unauthorised access to adjustment screws and fixing screw of switch cover		–	XMLA XMLB	**XMLZL001**	0.035
Lead sealable protective cover to prevent unauthorised access to adjustment screws		–	All types	**XMLZL011**	0.030
Indicator modules and associated covers, 2 LEDs (orange and green)	Without setting scale	∿ or ⎓ 24/48 V	XMLA/B	**XMLZZ024**	0.090
		∿ 110/240 V	XMLA/B	**XMLZZ120**	0.090
	With setting scale	∿ or ⎓ 24/48 V	XMLA	**XMLZA024**	0.090
			XMLB	**XMLZB024**	0.090
		∿ 110/240 V	XMLA	**XMLZA120**	0.090
			XMLB	**XMLZB120**	0.090
Hydraulic block for base mounting directly onto fluid manifold		–	All types	**XMLZL005**	0.240
Female EN 175301-803-A connector (ex-DIN 43650A)		–	XML●●●●●●C11	**XZCC43FCP40B**	0.035
Adaptor, G 1/4"/G 3/8" male/female		–	All types	**XMLZL012**	0.130

Replacement parts

Sealing gasket (pack of 10 gaskets)		For sizes ≥ 300 bar (XMLA/B/C/D)		**XMLZL010**	0.015
Diaphragms		–	XML●S35	**XMLZL013**	0.060
			XML●S02	**XMLZL014**	0.040
			XML●S04	**XMLZL015**	0.030

Electromechanical pressure and vacuum switches
OsiSense XMLA, XMLB, XMLC and XMLD

XML●L35, XML●001, XML●S



(1) 1 fluid entry, tapped G 1/4 (female) or 1/4"-18 NPTF (female)
(2) 1 electrical connections entry, tapped M20 x 1.5 mm or Pg 13.5 or 1/2"-14 NPT

XMLBM03, XMLBL05



(1) 1 fluid entry, tapped G 1/4 (female) or 1/4"-18 NPTF (female)
(2) 1 electrical connections entry, tapped M20 x 1.5 mm or Pg 13.5 or 1/2"-14 NPT
(3) 2 elongated holes Ø 10.2 x 5.2
(4) 1 elongated hole Ø 15.2 x 5.2

XML	Øa	c1	c2
BM03	150	155.5	80.5
BL05	200	204	104
●L35, ●001	110	–	–
●S35, ●S02, ●S04	110	–	–
●S10, ●S20	86	–	–

XMLAM01, XMLBM05, XMLCM05, XMLA004, XML●010…500



(1) 1 fluid entry, tapped G 1/4 (female) or 1/4"-18 NPTF (female)
(2) 1 electrical connections entry, tapped M20 x 1.5 mm or Pg 13.5 or 1/2"-14 NPT
Ø: 2 elongated holes Ø 5.2 x 6.7

XML●M02, XML●002, XMLB004, XMLC004, XMLD004



(1) 1 fluid entry, tapped G 1/4 (female) or 1/4"-18 NPTF (female)
(2) 1 electrical connections entry, tapped M20 x 1.5 mm or Pg 13.5 or 1/2"-14 NPT
Ø: 2 elongated holes Ø 10.2 x 5.2

Characteristics:
pages 17 to 67

References:
pages 18 to 67

XMLBL35P, XMLB001P



(1) 1 fluid entry, tapped G 1¼ (female)
(2) 1 electrical connections entry, tapped M20 x 1.5 mm or Pg 13.5

XMLBM05P, XMLA004P, XML●010P, XML●020P, XML●035P



(1) 1 fluid entry, tapped G 1¼ (female)
(2) 1 electrical connections entry, tapped M20 x 1.5 mm or Pg 13.5

Component materials of units in contact with fluid

This information will assist in checking the corrosion resistance of the pressure or vacuum switches in relation to the fluids controlled

Electromechanical pressure and vacuum switches

OsiSense XML

Pressure or vacuum switch reference	Component materials in contact with fluid							
	Zinc alloy	Stainless steel	Brass	Steel	Nitrile	PTFE	FPM, FKM	Aluminium
XMLAM01V●●●●, XML●M02V●●●●	■	*(1)*			■			
XMLAM01T●●●●, XML●M02T●●●●		*(2)*				■		
XMLBM03R●●●●				■			■	■
XMLBM03S●●●●		*(3)*				■		■
XML●M05A●●●●	■	*(1)*			■			
XML●M05B●●●●		*(1)*	■				■	
XML●M05C●●●●		*(1)*				■		
XMLBM05P●●●●		*(1)*		■			■	
XMLBL05R●●●●							■	■
XMLBL05S●●●●		*(3)*				■		
XML●L35R●●●●, XML●S35R●●●●		*(1)*		■			■	
XML●L35S●●●●		*(3)*				■		
XMLBL35P●●●●		*(1)*		■			■	
XML●001R●●●●		*(1)*		■			■	
XML●001S●●●●		*(3)*				■		
XMLB001P●●●●		*(1)*		■			■	
XML●002A●●●●	■				■			
XML●002B●●●●, XML●S02B●●●●				■			■	
XML●002C●●●●		*(3)*				■		
XMLA004A●●●●	■						■	
XMLA004B●●●●			■				■	
XMLA004C●●●●		*(2)*				■		
XMLA004P●●●●				■			■	

■ Component materials in contact with fluid

(1) 1.4307 (AISI 304L)
(2) 1.4404 (AISI 316L)
(3) 1.4305 (AISI 303)

Component materials of units in contact with fluid

This information will assist in checking the corrosion resistance of the pressure or vacuum switches in relation to the fluids controlled

Electromechanical pressure and vacuum switches

OsiSense XML

Pressure switch reference	Component materials in contact with fluid							
	Zinc alloy	Stainless steel	Brass	Steel	Nitrile	PTFE	FPM, FKM	Aluminium
XMLB004A●●●●	■				■			
XML●004B●●●●, XML●S04B●●●●				■			■	
XML●004C●●●●		*(3)*				■		
XML●010A●●●●	■						■	
XML●010B●●●●			■				■	
XML●010C●●●●		*(2)*				■		
XML●010P●●●●, XML●S10A●●●●				■			■	
XML●020A●●●●, XML●035A●●●●	■		■		■			■
XML●020B●●●●, XML●035B●●●●			■				■	
XML●020C●●●●, XML●035C●●●●		*(2)*				■		
XML●020P●●●●, XML●035P●●●●, XML●S20A●●●●				■			■	
XML●070D●●●●, XML●160D●●●●			■	■		■	■	
XML●070E●●●●, XML●160E●●●●		*(4)*	■			■	■	
XML●070N●●●●, XML●160N●●●●		*(5)*				■	■	
XML●300D●●●●			■	■		■	■	
XML●300E●●●●		*(4)*	■			■	■	
XML●300N●●●●		*(5)*				■	■	
XML●500D●●●●		■	■	■		■	■	
XML●500E●●●●		■	■			■	■	
XML●500N●●●●4		*(5)*				■	■	

■ Component materials in contact with fluid

(2) 1.4404 (AISI 316L)
(3) 1.4305 (AISI 303)
(4) 1.4404 (AISI 316L) + 1.4462
(5) 1.4404 (AISI 316L) + 1.4305 (AISI 303)

Electromechanical pressure switches
OsiSense XM
For control circuits, OsiSense ACW and ADW

Presentation

Pressure switches OsiSense ACW and ADW are switches for control circuits, with an adjustable differential.
Pressure switches OsiSense ACW are used to control the pressure of air, oils and other non corrosive fluids, up to 131 bar.
Pressure switches OsiSense ADW are used to control the pressure of oils (including synthetic), up to 340 bar.

Setting, operating principle

Pressure switches OsiSense ACW



The switching point on falling pressure (low point - PB) is adjusted using screw **1**.

The switching point on rising pressure (high point - PH) is made by adjusting screw **2**. This sets the differential between the low and high points, giving a switching point on rising pressure of the displayed low point setting plus the differential setting.

The two adjustments are completely independent.



Contact block operation

When the rising pressure reaches the high point setting (low point setting + differential setting), contact B (1-2) opens and contact A (3-4) closes. The contacts remain actuated until the pressure falls back to the low point setting.

Pressure switches OsiSense ADW



The switching point on rising pressure (high point - PH) is adjusted using screw **1**.

The switching point on falling pressure (low point - PB) is made by adjusting screw **2**. This sets the differential between the high and low points, giving a switching point on falling pressure of the displayed high point setting minus the differential setting.

The two adjustments are completely independent.



Contact block operation

When the rising pressure reaches the high point setting, contact B (1-2) opens and contact A (3-4) closes. The contacts remain actuated until the pressure falls back to the low point setting (high point setting - differential setting).

Electromechanical pressure switches
OsiSense XM
For control circuits, OsiSense ACW and ADW

Environment characteristics

Pressure switch type			ACW (bellows operated)	ADW (piston operated)
Conformity to standards			CE, IEC/EN 60947-5-1	
Product certifications			CSA, UL (Recognized), EAC	
Protective treatment			"TC"	
Materials			Zinc alloy case Phosphor bronze bellows	Zinc alloy case Pressure switches with drainage hole: Buna N diaphragm, steel piston, cast iron cylinder Pressure switches with Quad-Ring piston seal: Buna N diaphragm, Teflon and Viton seal, stainless steel piston and cylinder
Ambient air temperature (for operation)		**°C**	- 56…+ 85	- 30…+ 85
Fluids controlled			Air, oils and other non corrosive fluids, from - 73 to + 125°C	Oils and other fluids, from - 25 to + 120°C (for **ADW5, ADW6, ADW7S1, ADW25** and **ADW26**) Oils (including synthetic) only, from - 30 to + 125°C (for **ADW3, ADW4, ADW7, ADW23, ADW24** and **ADW27**)
Degree of protection			IP 65 conforming to IEC/EN 60529	
Fluid connection			G 1/4 (BSP female) conforming to NF E 03-005, ISO 228	G 3/8 (BSP female) conforming to NF E 03-005, ISO 228
Electrical connection	Terminals		1 tapped entry M20 x 1.5 mm for ISO cable gland. **(for ACW•M119012, ACW••M119012, ADW•M119012** and **ADW••M119012).** 1 tapped entry for n° 13 (DIN Pg 13.5) cable gland **(for ACW•M129012, ACW••M129012, ADW•M129012** and **ADW••M129012).**	

Contact block characteristics

Rated operational current			**1 CO single-pole pressure switches**	**2 CO single-pole pressure switches**
	Category AC-15		Ue 24 V 110 V 220 V 500 V	Ie 5 A 5 A 3 A 1.4 A	Ie 3 A 3 A 1.5 A 0.7 A
	Category DC-13		Ue 24 V 110 V 220 V 500 V 600 V	Ie 5 A 0.5 A 0.25 A 0.10 A 0.06 A	Ie 1.5 A 0.25 A – – –
Short-circuit protection			10 A cartridge fuse type gG	
Connection			Screw terminals Minimum clamping capacity: 1 x 1 mm^2 Maximum clamping capacity: 2 x 2.5 mm^2	

References: pages 76 to 79
Dimensions: pages 80 and 81

References, characteristics, curves, connections

Electromechanical pressure switches

OsiSense XM

For control circuits, OsiSense ACW
Sizes 0.70 to 131 bar (10.15 to 1900 psi)
Adjustable differential, for regulation between 2 thresholds
Fluid connection G 1/4 (female)

Pressure switches OsiSense ACW	**Bellows operated**			
				
Adjustable range of switching point (PB) (Falling pressure)	**0.07…0.70 bar (1.01…10.15 psi)**	**0.07…1.4 bar (1.01…20.3 psi)**	**0.07…5.2 bar (1.01…75.4 psi)**	**0.07…7.6 bar (1.01…110.2 psi)**
References				
Switches with 1 CO single-pole contact				
Electrical connection With one tapped entry M20 x 1.5 mm for ISO cable gland	**ACW3M119012**	**ACW4M119012**	**ACW5M119012**	**ACW1M119012**
With one tapped entry for n° 13 cable gland	**ACW3M129012**	**ACW4M129012**	**ACW5M129012**	**ACW1M129012**
Weight (kg)	1.750		1.550	
Switches with 2 CO single-pole contacts				
Electrical connection With one tapped entry M20 x 1.5 mm for ISO cable gland	**ACW23M119012**	**ACW24M119012**	**ACW25M119012**	**ACW21M119012**
With one tapped entry for n° 13 cable gland	**ACW23M129012**	**ACW24M129012**	**ACW25M129012**	**ACW21M129012**
Weight (kg)	1.750		1.550	
Complementary characteristics not shown under general characteristics (page 75)				
Possible differential (add to PB to give PH) 1 CO switches Min.	0.04 bar (0.58 psi)	0.10 bar (1.45 psi)	0.30 bar (4.35 psi)	0.50 bar (7.25 psi)
Max.	0.34 bar (4.93 psi)	0.40 bar (5.8 psi)	1 bar (14.5 psi)	2 bar (29 psi)
2 CO switches Min.	0.05 bar (0.73 psi)	0.14 bar (2.03 psi)	0.41 bar (5.95 psi)	0.9 bar (13.05 psi)
Max.	0.48 bar (6.96 psi)	0.70 bar (10.15 psi)	1.4 bar (20.3 psi)	2.8 bar (40.6 psi)
Maximum permissible pressure	2 bar (29 psi)		7 bar (101.5 psi)	17 bar (246.5 psi)
Fluids controlled	Air, oils and other non corrosive fluids, from - 73 to + 125°C *(1)*			
Mechanical life	1 x 10^6 operating cycles (average value, depending on application)			
Cable entry, screw terminals ACW●M119012, ACW2●M119012	1 tapped entry M20 x 1.5 mm for ISO cable gland. Clamping capacity 7 to 13 mm			
ACW●M129012, ACW2●M129012	1 tapped entry for n° 13 cable gland, conforming to NF C 68-300 (DIN Pg 13.5). Clamping capacity 9 to 13 mm			

(1) See "Component materials of units in contact with the fluid", page 75.

Operating curve



— Adjustable value

Contact block connections



Other versions Pressure switches with alternative tapped cable entries: NPT, etc. Please consult our Customer Care Centre.

Dimensions: page 80

Bellows operated					
					
1.4…12 bar (20.3…174 psi)	**0.7…18 bar (10.15…261 psi)**	**0.7…21 bar (10.15…304.5 psi)**	**5.2…34 bar (75.4…493 psi)**	**10…69 bar (145…1000 psi)**	**24…131 bar (348…1900 psi)**
References					
Switches with 1 CO single-pole contact					
ACW8M119012	**ACW9M119012**	**ACW2M119012**	**ACW6M119012**	**ACW7M119012**	**ACW10M119012**
ACW8M129012	**ACW9M129012**	**ACW2M129012**	**ACW6M129012**	**ACW7M129012**	**ACW10M129012**
1.550		2.100			
Switches with 2 CO single-pole contacts					
ACW28M119012	**–**	**ACW22M119012**	**ACW26M119012**	**–**	**ACW20M119012**
ACW28M129012	**ACW29M129012**	**ACW22M129012**	**ACW26M129012**	**ACW27M129012**	**ACW20M129012**
1.550		2.100			
Complementary characteristics not shown under general characteristics (page 75)					
0.70 bar (10.15 psi)	1 bar (14.5 psi)	1.7 bar (24.7 psi)	3.4 bar (49.3 psi)	5.9 bar (85.6 psi)	11 bar (159.5 psi)
2 bar (29 psi)	1.7 bar (24.7 psi)	8.6 bar (124.7 psi)	8.3 bar (120.4 psi)	10 bar (145 psi)	21 bar (304.5 psi)
1 bar (14.5 psi)	1.6 bar (23.2 psi)	2.4 bar (34.8 psi)	5.9 bar (85.6 psi)	9.3 bar (134.9 psi)	17 bar (246.5 psi)
2.8 bar (40.6 psi)	2.4 bar (34.8 psi)	10 bar (145 psi)	11 bar (159.5 psi)	14 bar (203 psi)	24 bar (348 psi)
17 bar (246.5 psi)	20 bar (290 psi)	41 bar (549.5 psi)	140 bar (2030 psi)	140 bar (2030 psi)	175 bar (2538 psi)
Air, oils and other non corrosive fluids, from - 73 to + 125°C *(1)*					
1 x 10^6 operating cycles (average value, depending on application)					
1 tapped entry M20 x 1.5 mm for ISO cable gland. Clamping capacity 7 to 13 mm					
1 tapped entry for n° 13 cable gland, conforming to NF C 68-300 (DIN Pg 13.5). Clamping capacity 9 to 13 mm					

Other versions Pressure switches with alternative tapped cable entries: NPT, etc. Please consult our Customer Care Centre.

Dimensions: page 80

Electromechanical pressure switches

OsiSense XM
For control circuits, OsiSense ADW
Sizes 69 to 340 bar (1000 to 4930 psi)
Adjustable differential, for regulation between 2 thresholds
Fluid connection G 3/8 (female)

Pressure switches OsiSense ADW	**Piston operated, with drainage hole** *(1)*



Adjustable range of switching point (PH) (Rising pressure)			**9.3…69 bar (135…1000 psi)**	**28…210 bar (406…3045 psi)**	**38…340 bar (551…4930 psi)**
References					
Switches with 1 CO single-pole contact					
Electrical connection	With one tapped entry M20 x 1.5 mm for ISO cable gland		**ADW3M119012**	**ADW4M119012**	**ADW7M119012**
	With one tapped entry for n° 13 cable gland		**ADW3M129012**	**ADW4M129012**	**ADW7M129012**
Weight (kg)			1.880		
Switches with 2 CO single-pole contacts					
Electrical connection	With one tapped entry for n° 13 cable gland		**ADW23M129012**	**ADW24M129012**	**ADW27M129012**
Weight (kg)			1.880		
Complementary characteristics not shown under general characteristics (page 75)					
Possible differential (subtract from PH to give PB)	1 CO switches	Min.	2.4 bar (34.8 psi)	6.9 bar (100 psi)	8.6 bar (124.7 psi)
		Max.	9.3 bar (135 psi)	28 bar (406 psi)	38 bar (551 psi)
	2 CO switches	Min.	3.1 bar (45 psi)	8.6 bar (124.7 psi)	14 bar (203 psi)
		Max.	14 bar (203 psi)	34 bar (493 psi)	41 bar (594.5 psi)
Maximum permissible pressure			690 bar (10,000 psi)		
Fluids controlled			Oils (including synthetic) only, from - 30°C to + 125°C *(2) (3)*		
Mechanical life			1 x 10^6 operating cycles (average value, depending on application)		
Cable entry, screw terminals	ADW●M119012		1 tapped entry M20 x 1.5 mm for ISO cable gland. Clamping capacity 7 to 13 mm		
	ADW●M129012, ADW2●●M129012		1 tapped entry for n° 13 cable gland, conforming to NF C 68-300 (DIN Pg 13.5). Clamping capacity 9 to 13 mm		

(1) Since it is normal for piston type pressure switches (not incorporating a piston seal) to have a slight oil leakage past the piston, a drain hole through the cylinder wall is incorporated. To avoid back pressure, this hole should never be plugged. If for any reason this oil leakage is undesirable, use pressure switches incorporating a Quad-Ring piston seal.
(2) See "Component materials of units in contact with the fluid", page 75.
(3) Only for control of group 2 fluids, in accordance with directive 97/23/EEC.

Operating curve



— Adjustable value

Contact block connections



Other versions

Pressure switches with alternative tapped cable entries: NPT, etc. Please consult our Customer Care Centre.

Dimensions:
page 81

Pressure switches OsiSense ADW	**Piston operated, with Quad-Ring piston seal**



Adjustable range of switching point (PH) (Falling pressure)			**9.3…69 bar (135…1000 psi)**	**28…210 bar (406…3045 psi)**	**38…340 bar (551…4930 psi)**
References					
Switches with 1 CO single-pole contact					
Electrical connection	With one tapped entry M20 x 1.5 mm for ISO cable gland		**ADW5M119012**	**ADW6M119012**	**–**
	With one tapped entry for n° 13 cable gland		**ADW5M129012**	**ADW6M129012**	**ADW7S1M129012**
Weight (kg)			1.880		
Switches with 2 CO single-pole contacts					
Electrical connection	With one tapped entry for n° 13 cable gland		**ADW25M129012**	**ADW26M129012**	**–**
Weight (kg)			1.880		
Complementary characteristics not shown under general characteristics (page 75)					
Possible differential (subtract from PH to give PB)	1 CO switches	Min./max. at low setting	4.8/6.9 bar (69.6/100 psi)	14/21 bar (203/304.5 psi)	19/25 bar (275.5/362.5 psi)
		Min./max. at low setting	8.6/10 bar (124.7/145 psi)	28/34 bar (406/493 psi)	38/45 bar (551/652.5 psi)
	2 CO switches	Min./max. at low setting	6.2/7.9 bar (89.9/114.6 psi)	17/24 bar (246.5/348 psi)	22/28 bar (319/406 psi)
		Min./max. at high setting	10/12 bar (145/174 psi)	34/39 bar (493/565.5 psi)	44/50 bar (638/725 psi)
Maximum permissible pressure			690 bar (10,000 psi)		
Fluids controlled			Oils and other fluids, from - 25°C to + 120°C *(1) (2)*		
Mechanical life			1 x 10^6 operating cycles (average value, depending on application)		
Cable entry, screw terminals	ADW●M119012		1 tapped entry M20 x 1.5 mm for ISO cable gland. Clamping capacity 7 to 13 mm		
	ADW●M129012, ADW2●●M129012		1 tapped entry for n° 13 cable gland, conforming to NF C 68-300 (DIN Pg 13.5). Clamping capacity 9 to 13 mm		

(1) See "Component materials of units in contact with the fluid", page 75.
(2) Only for control of group 2 fluids, in accordance with directive 97/23/EEC.

Operating curve



— Adjustable value

Contact block connections



Other versions

Pressure switches with alternative tapped cable entries: NPT, etc. Please consult our Customer Care Centre.

Dimensions:
page 81

Electromechanical pressure switches
OsiSense XM
For control circuits, OsiSense ACW

ACW3, ACW4, ACW23 and **ACW24**



(1) Tapped entry for n° 13 or ISO M20 cable gland, depending on model
Ø: G 1/4 (female)

ACW1, ACW5, ACW8, ACW9, ACW21, ACW25, ACW28 and **ACW29**



(1) Tapped entry for n° 13 or ISO M20 cable gland, depending on model
Ø: G 1/4 (female)

ACW2 and **ACW22**



(1) Tapped entry for n° 13 or ISO M20 cable gland, depending on model
Ø: G 1/4 (female)

ACW6, ACW7, ACW10, ACW26, ACW27 and **ACW20**



(1) Tapped entry for n° 13 or ISO M20 cable gland, depending on model
Ø: G 1/4 (female)

Characteristics:
pages 75 to 77

References:
pages 76 and 77

Electromechanical pressure switches
OsiSense XM
For control circuits, OsiSense ADW

ADW3, ADW4, ADW7, ADW23, ADW24 and **ADW27**



(1) Tapped entry for n° 13 or ISO M20 cable gland, depending on model
(2) Drainage hole, tapped G 1/8 (female)
Ø: G 3/8 (female)

ADW5, ADW6, ADW7S1, ADW25 and **ADW26**



(1) Tapped entry for n° 13 or ISO M20 cable gland, depending on model
Ø: G 3/8 (female)

Characteristics:
pages 75 to 79

References:
pages 78 and 79

Electromechanical pressure switches
OsiSense XM
For control circuits, OsiSense XMX and XMA



Presentation

Pressure switches OsiSense XMX and XMA are switches for control circuits, with an adjustable differential.
They are used to control the pressure of water and air, up to 25 bar.

Equipment fitted to the various models

Location of setting screw

Pressure switches OsiSense XMX have an internal setting screw that is only accessible after removing the cover.
Pressure switches OsiSense XMA have an external setting screw that is accessible without removing the cover.

Case

Pressure switches OsiSense XMX have a black opaque case.
Pressure switches OsiSense XMA can have a transparent case or a black opaque case.

Setting

When setting pressure switches XMX or XMA, adjust the switching point on rising pressure (PH) first and then the switching point on falling pressure (PB).

Switching point on rising pressure
The switching point on rising pressure (PH) is set by adjusting screw-nut 1.

Switching point on falling pressure
The switching point on falling pressure (PB) is set by adjusting screw-nut 2.

References:
page 84

Dimensions:
page 87

Electromechanical pressure switches
OsiSense XM
For control circuits, OsiSense XMX and XMA

Environment characteristics

Conformity to standards			CE, IEC/EN 60947-5-1
Product certifications			UL, CSA, CCC, EAC
Protective treatment			"TC"
Ambient air temperature	For operation	**°C**	- 25…+ 70 for 6 and 25 bar versions - 25…+ 55 for 12 bar version
	For storage		- 40…+ 70
Fluids controlled		**°C**	Air, fresh water, sea water: 0…+ 70°C for 6 and 25 bar versions 0…+ 55°C for 12 bar version
Materials			Case: polycarbonate impregnated with Lexan 500R fibreglass (black opaque cover) or polycarbonate impregnated with Lexan 123 fibreglass (transparent cover) Component materials in contact with fluid: chromated zinc alloy (fluid entry), canvas covered nitrile (diaphragm)
Operating position			All positions
Electric shock protection			Class I conforming to IEC 536
Degree of protection			IP 54 conforming to IEC/EN 60529
Operating rate		**Op. cycles/h**	600
Repeat accuracy			< 3.5%
Fluid connection			G 1/4 or 4 x G 1/4 (BSP female) conforming to NF E 03-005, ISO 228
Electrical connection			Terminals 2 tapped entries for n° 13 (DIN Pg 13.5) cable gland

Contact block characteristics

Rated operational characteristics		~ AC-15, B300 (Ue = 240 V, Ie = 1.5 A; Ue = 120 V, Ie = 3 A) ⎓ DC-13, R300 (Ue = 250 V, Ie = 0.1 A)
Rated insulation voltage	**V**	Ui = 500 conforming to IEC/EN 60947-1
Rated impulse withstand voltage	**kV**	U imp = 6 conforming to IEC/EN 60947-1
Type of contacts		1 CO single-pole contact, snap action
Terminal referencing		Conforming to CENELEC EN 50013
Short-circuit protection		10 A cartridge fuse type gG (gl)
Connection		Screw clamp terminals Minimum clamping capacity: 1 x 1 mm^2 Maximum clamping capacity: 2 x 2.5 mm^2
Electrical durability		AC supply 50/60Hz, Ith = 10 A Inductive circuit, utilisation category AC-15, 3 A/240 V: 1 million operating cycles

References: page 84
Dimensions: page 87

Electromechanical pressure switches

OsiSense XMX for control circuits

Sizes 6 to 25 bar (87 to 362.5 psi)

Adjustable differential, for regulation between 2 thresholds

Switches with 1 CO single-pole contact

Pressure switches OsiSense XMX (internal setting screw)



Adjustable range of switching point (PH) (Rising pressure)		**1…6 bar (14.5…87 psi)**	**1.3…12 bar (18.85…174 psi)**	**3.5…25 bar (50.75…362.5 psi)**	**1…6 bar (14.5…87 psi)**	**1.3…12 bar (18.85…174 psi)**	**3.5…25 bar (50.75…362.5 psi)**
Fluid connection		G 1/4 (female)			4 x G 1/4 (female)		
References							
Switches with black opaque cover							
Fluids controlled	Air, fresh water, sea water *(1)*	**XMXA06L2135**	**XMXA12L2135**	**XMXA25L2135**	**XMXA06L2435**	**XMXA12L2435**	**XMXA25L2435**
Weight (kg)		0.430		0.650	0.430		0.650
Complementary characteristics not shown under general characteristics (page 83)							
Possible differential (subtract from PH to give PB)	Min. at low setting	0.8 bar (11.6 psi)	1 bar (14.5 psi)	3.4 bar (49.3 psi)	0.8 bar (11.6 psi)	1 bar (14.5 psi)	3.4 bar (49.3 psi)
	Min. at high setting	1.2 bar (17.4 psi)	1.7 bar (24.6 psi)	4.5 bar (65.2 psi)	1.2 bar (17.4 psi)	1.7 bar (24.6 psi)	4.5 bar (65.2 psi)
	Max. at high setting	4.2 bar (60.9 psi)	8.4 bar (121.8 psi)	20 bar (290 psi)	4.2 bar (60.9 psi)	8.4 bar (121.8 psi)	20 bar (290 psi)
Maximum permissible pressure	Per cycle	7.5 bar (108.7 psi)	15 bar (217.5 psi)	31.25 bar (453.1 psi)	7.5 bar (108.7 psi)	15 bar (217.5 psi)	31.25 bar (453.1 psi)
	Accidental	13.5 bar (195.7 psi)	27 bar (391.5 psi)	56.25 bar (815.6 psi)	13.5 bar (195.7 psi)	27 bar (391.5 psi)	56.25 bar (815.6 psi)
Destruction pressure		30 bar (435 psi)		100 bar (1450 psi)	30 bar (435 psi)		100 bar (1450 psi)
Mechanical life		1 x 10^6 operating cycles					
Cable entry		2 entries tapped for n° 13 cable gland, conforming to NF C 68-300 (DIN Pg 13.5)					
Pressure switch type		Diaphragm					

(1) Component materials of units in contact with the fluid, see page 83.

Operating curves

XMXA06●●●●●



XMXA12●●●●●



XMXA25●●●●●





— Adjustable value

1 Maximum differential
2 Minimum differential

1 Maximum differential
2 Minimum differential

1 Maximum differential
2 Minimum differential

Connections



Other versions

Pressure switches with alternative tapped cable entries: ISO, NPT, etc. Please consult our Customer Care Centre.

Accessories: page 86

Dimensions: page 87

Electromechanical pressure switches

OsiSense XMA for control circuits

Sizes 6 to 25 bar (87 to 362.5 psi)

Adjustable differential, for regulation between 2 thresholds
Switches with 1 CO single-pole contact

Pressure switches OsiSense XMA (external setting screw)



Adjustable range of switching point (PH) (Rising pressure)	**1…6 bar (14.5…87 psi)**	**1.3…12 bar (18.85…174 psi)**	**3.5…25 bar (50.75…362.5 psi)**	**1…6 bar (14.5…87 psi)**	**1.3…12 bar (18.85…174 psi)**	**3.5…25 bar (50.75…362.5 psi)**
Fluid connection	G 1/4 (female)			4 x G 1/4 (female)		

References

Switches with black opaque cover							
Fluids controlled	Air, fresh water, sea water *(1)*	**XMAH06L2135**	**XMAH12L2135**	**XMAH25L2135**	**XMAH06L2435**	**XMAH12L2435**	**XMAH25L2435**
Switches with transparent cover							
Fluids controlled	Air, fresh water, sea water *(1)*	**XMAV06L2135**	**XMAV12L2135**	**XMAV25L2135**	**XMAV06L2435**	**XMAV12L2435**	**XMAV25L2435**
Weight (kg)		0.430		0.650	0.430		0.650

Complementary characteristics not shown under general characteristics (page 83)

Possible differential (subtract from PH to give PB)	Min. at low setting	0.8 bar (11.6 psi)	1 bar (14.5 psi)	3.4 bar (49.3 psi)	0.8 bar (11.6 psi)	1 bar (14.5 psi)	3.4 bar (49.3 psi)
	Min. at high setting	1.2 bar (17.4 psi)	1.7 bar (24.6 psi)	4.5 bar (65.2 psi)	1.2 bar (17.4 psi)	1.7 bar (24.6 psi)	4.5 bar (65.2 psi)
	Max. at high setting	4.2 bar (60.9 psi)	8.4 bar (121.8 psi)	20 bar (290 psi)	4.2 bar (60.9 psi)	8.4 bar (121.8 psi)	20 bar (290 psi)
Maximum permissible pressure	Per cycle	7.5 bar (108.7 psi)	15 bar (217.5 psi)	31.25 bar (453.1 psi)	7.5 bar (108.7 psi)	15 bar (217.5 psi)	31.25 bar (453.1 psi)
	Accidental	13.5 bar (195.7 psi)	27 bar (391.5 psi)	56.25 bar (815.6 psi)	13.5 bar (195.7 psi)	27 bar (391.5 psi)	56.25 bar (815.6 psi)
Destruction pressure		30 bar (435 psi)		100 bar (1450 psi)	30 bar (435 psi)		100 bar (1450 psi)
Mechanical life		1 x 10^6 operating cycles					
Cable entry		2 entries tapped for n° 13 cable gland, conforming to NF C 68-300 (DIN Pg 13.5)					
Pressure switch type		Diaphragm					

(1) Component materials of units in contact with the fluid, see page 83.

Operating curves

XMA●06●●●●●



XMA●12●●●●●



XMA●25●●●●●





1 Maximum differential
2 Minimum differential

1 Maximum differential
2 Minimum differential

1 Maximum differential
2 Minimum differential

Connections



Other versions

Pressure switches with alternative tapped cable entries: ISO, NPT, etc. Please consult our Customer Care Centre.

Accessories: page 86
Dimensions: page 87

Electromechanical pressure switches
OsiSense XMX and XMA for control circuits
Accessories and replacement parts


XMAZL001


XMLZL003


DE9PM1201


DE9PM1202


XMPZ3●

References

Description		Reference	Weight kg
Fixing bracket		**XMAZL001**	0.035
Knurled adjustment knob, Ø 36 mm fits over adjustment screws to facilitate setting		**XMLZL003**	0.010
13P cable gland	With anti pull-out ring (for cable Ø 6…9 mm)	**DE9PM1201**	0.005
	Without anti pull-out ring (for cable Ø 6…9 mm)	**DE9PM1202**	0.005
	With anti pull-out ring (for cable Ø 9…12.5 mm)	**DE9PM1203**	0.005

Description	For pressure switch	Reference	Weight kg
Diaphragms	Size 6 bar	**XMPZ31**	0.005
	Size 25 bar	**XMPZ33**	0.005

Dimensions:
page 87

Dimensions

XMXA06L2135, XMXA12L2135
XMA●06L2135, XMA●12L2135



ØA = G 1/4 (female)

(1) 2 tapped entries for n° 13 cable gland

(2) Minimum clearance zone for screwing-on pressure switch at point A

XMXA06L2435, XMXA12L2435
XMA●06L2435, XMA●12L2435



ØA = ØB = ØC = ØD = G 1/4 (female)

(1) 2 tapped entries for n° 13 cable gland

(2) Minimum clearance zone for screwing-on pressure switch at point A

XMXA25L2135, XMXA25L2435
XMA●25L2135, XMA●25L2435



XM●●25L2135: ØA only = G 1/4 (female)

XM●●25L2435: ØA = ØB = ØC = ØD = G 1/4 (female)

Fixing bracket
XMAZL001



(1) 2 tapped entries for n° 13 cable gland

(2) Minimum clearance zone for screwing-on pressure switch at point A

Characteristics:
page 83

References:
page 84

Electromechanical pressure switches
OsiSense XM
For power circuits, OsiSense FTG, FSG and FYG

Presentation

Pressure switches OsiSense FTG, FSG and FYG are switches for power circuits. They are used to control the pressure of water, up to 10.5 bar.

2 types of product are available:
- pressure switches OsiSense FTG with fixed differential, for detection of a single threshold,
- pressure switches OsiSense FSG and FYG with an adjustable differential, for regulation between 2 thresholds.

For specific needs, these 2 types of product can be supplied in IP 65 versions, thus ensuring a higher degree of protection. They feature 2 cable entries, fitted with cable gland, and are referenced **F●G●NE**.



Setting

Pressure switches with fixed differential (FTG)

Only the switching point on rising pressure is adjustable.

Switching point on rising pressure
The switching point on rising pressure (PH) is set by adjusting screw-nut 1.

Switching point on falling pressure
The switching point on falling pressure (PB) is not adjustable.
The difference between the tripping and resetting points of the contact is the natural differential of the switch (contact differential, friction, etc.).



Pressure switches with adjustable differential (FSG and FYG)

When setting the pressure switch, adjust the switching point on rising pressure (PH) first and then the switching point on falling pressure (PB).

Switching point on rising pressure
The switching point on rising pressure (PH) is set by adjusting screw-nut 1.

Switching point on falling pressure
The switching point on falling pressure (PB) is set by adjusting screw-nut 2.

References:
pages 90 to 92

Dimensions:
page 93

Electromechanical pressure switches
OsiSense XM
For power circuits, OsiSense FTG, FSG and FYG

Environment characteristics

Pressure switch type			FTG● FTG●NE	FSG● and FYG● FSG●NE and FYG●NE
Conformity to standards			CE, IEC/EN 60730	
Protective treatment			Standard version: "TC"	
Ambient air temperature		**°C**	For operation: 0...+ 45. For storage: - 30...+ 80	
Fluids controlled			Fresh water, sea water (0…+ 70°C)	
Materials			Case: polystyrene, resistant to mechanical impact Component materials in contact with fluid: nylon 6/6, zinc plated steel, nitrile	
Operating position			All positions	
Electric shock protection			Class I conforming to IEC 536	
Degree of protection conforming to IEC/EN 60529	**FTG●, FSG● and FYG●**		IP 20	
	FTG●NE, FSG●NE and FYG●NE		IP 65	
Operating rate		**Op. cycles/h**	600	
Repeat accuracy			< 2%	
Fluid connection	**F●G 2, FYG●2**		G 1/4 (BSP female) conforming to NF E 03-005, ISO 228	
	F●G 9		R 1/4 (BSP male) conforming to NF E 03-004, ISO 7	
Electrical connection	**FTG●, FSG● and FYG●**		Terminals. 2 cable entries, with grommet	
	FTG●NE, FSG●NE and FYG●NE		Terminals. 2 entries incorporating 13P cable gland (DIN Pg 13.5)	

Contact block characteristics

Rated operational characteristics			Ie = 10 A, Ue = ~ 250 V conforming to EN 60730-1			
Power ratings of controlled motors	Voltage		~ 2-pole 1-phase	~ 2-pole 3-phase	~ 2-pole 1-phase	~ 2-pole 3-phase
	110 V		0.75 kW (1 HP)	1.1 kW (1.5 HP)	0.75 kW (1 HP)	1.1 kW (1.5 HP)
	230 V		1.1 kW (1.5 HP)	1.5 kW (2 HP)	1.5 kW (2 HP)	2.2 kW (3 HP)
	400 V		1.5 kW (2 HP)	1.5 kW (2 HP)	1.5 kW (2 HP)	2.2 kW (3 HP)
Rated insulation voltage conforming to IEC/EN 60947-1		**V**	Ui = 500			
Rated impulse withstand voltage conforming to IEC/EN 60947-1		**kV**	U imp = 6			
Type of contacts			1 2-pole 2 NC (4 terminal) contact, snap action			
Short-circuit protection			20 A cartridge fuse type gG			
Connection			Screw clamp terminals. Minimum clamping capacity: 1 x 1 mm^2, max: 2 x 2 mm^2			
Electrical durability at an operating rate of 600 operating cycles/hour		**Op. cycles**	40 000		100 000	

References: pages 90 to 92
Dimensions: page 93

Electromechanical pressure switches

OsiSense XM

For power circuits, OsiSense FTG
Size 4.6 bar (66.7 psi), fixed differential, for detection of a single threshold. Switches with 2-pole 2 NC contact.
Degree of protection IP 20 or IP 65

Fluid connection		**G 1/4 (female)**	**R 1/4 (male)**	**G 1/4 (female)**	**R 1/4 (male)**
					
Adjustable range of switching point (PH) (Rising pressure)		**1.4…4.6 bar (20.3…66.7 psi)**			
Degree of protection conforming to IEC/EN 60529		**IP 20**		**IP 65**	
References					
Fluids controlled	Fresh water, sea water, from 0°C to + 70°C *(1)*	**FTG2**	**FTG9**	**FTG2NE**	**FTG9NE**
Weight (kg)		0.340			
Complementary characteristics not shown under general characteristics (page 89)					
Natural differential (subtract from PH to give PB)	At low setting	1.1 bar (15.95 psi)			
	At middle setting	1.3 bar (18.85 psi)			
	At high setting	1.5 bar (21.75 psi)			
Maximum permissible pressure	Per cycle	5.75 bar (83.38 psi)			
	Accidental	8 bar (116 psi)			
Destruction pressure		20 bar (290 psi)			
Mechanical life		4 x 10^5 operating cycles			
Cable entry		2 cable entries, with grommet		2 entries with 13P cable gland (DIN Pg 13.5)	
Clamping capacity		–		9 to 13 mm	
Pressure switch type		Diaphragm			

(1) Component materials of units in contact with the fluid, see page 89.

Operating curves





— Adjustable value
---- Non adjustable value

Connections



Dimensions:
page 93

Electromechanical pressure switches
OsiSense XM
For power circuits, OsiSense FSG
Size 4.6 bar (66.7 psi), adjustable differential, for regulation between 2 thresholds. Switches with 2-pole 2 NC contact.
Degree protection IP 20 or IP 65

Fluid connection		**G 1/4 (female)**	**R 1/4 (male)**	**G 1/4 (female)**	**R 1/4 (male)**
					
Adjustable range of switching point (PH) (Rising pressure)		**1.4…4.6 bar (20.3…66.7 psi)**			
Degree of protection conforming to IEC/EN 60529		**IP 20**		**IP 65**	
References					
Fluids controlled	Fresh water, sea water, from 0°C to + 70°C *(1)*	**FSG2**	**FSG9**	**FSG2NE** *(2)*	**FSG9NE**
Weight (kg)		0.340			
Complementary characteristics not shown under general characteristics (page 89)					
Possible differential (subtract from PH to give PB)	Max. at low setting	2.1 bar (30.45 psi)			
	Max. at middle setting	2.2 bar (31.9 psi)			
	Max. at high setting	2.3 bar (33.35 psi)			
	Min. at low setting	1 bar (14.5 psi)			
	Min. at middle setting	1.1 bar (15.95 psi)			
	Min. at high setting	1.2 bar (17.4 psi)			
Maximum permissible pressure	Per cycle	5.75 bar (83.38 psi)			
	Accidental	8 bar (116 psi)			
Destruction pressure		20 bar (290 psi)			
Mechanical life		1 x 10^6 operating cycles			
Cable entry		2 cable entries, with grommet		2 entries with 13P cable gland (DIN Pg 13.5)	
Clamping capacity		–		9 to 13 mm	
Pressure switch type		Diaphragm			

(1) Component materials of units in contact with the fluid, see page 89.
*(2) Variant: for a G 3/8 female fluid entry that pivots throughout 360°, select the **FSG2NEG**.*

Operating curves



1 Maximum differential
2 Minimum differential



— Adjustable value

Connections



Dimensions:
page 93

Electromechanical pressure switches

OsiSense XM

For power circuits, OsiSense FYG
Sizes 7 and 10.5 bar (101.5 and 152.3 psi), adjustable differential, for regulation between 2 thresholds. Switches with 2-pole 2 NC contact. Degree of protection IP 20 or IP 65

Fluid connection		**G 1/4 (female)**			
					
Adjustable range of switching point (PH) (Rising pressure)		**2.8…7 bar (40.6…101.5 psi)**		**5.6…10.5 bar (81.2…152.3 psi)**	
Degree of protection conforming to EN/IEC 60529		**IP 20**	**IP 65**	**IP 20**	**IP 65**
References					
Fluids controlled	Fresh water, sea water, from 0°C to + 70°C *(1)*	**FYG22** *(2)*	**FYG22NE**	**FYG32** *(3)*	**FYG32NE**
Weight (kg)		0.340			
Complementary characteristics not shown under general characteristics (page 89)					
Possible differential (subtract from PH to give PB)	Max. at low setting	2.3 bar (33.35 psi)		3 bar (43.5 psi)	
	Max. at middle setting	2.5 bar (36.25 psi)		3.2 bar (46.4 psi)	
	Max. at high setting	2.7 bar (39.15 psi)		3.4 bar (49.3 psi)	
	Min. at low setting	1.2 bar (17.4 psi)		1.9 bar (27.55 psi)	
	Min. at middle setting	1.4 bar (20.3 psi)		2.1 bar (30.45 psi)	
	Min. at high setting	1.6 bar (23.2 psi)		2.3 bar (33.35 psi)	
Maximum permissible pressure	Per cycle	8.75 bar (126.9 psi)		13 bar (188.5 psi)	
	Accidental	15 bar (217.5 psi)		15 bar (217.5 psi)	
Destruction pressure		20 bar (290 psi)		20 bar (290 psi)	
Mechanical life		1 x 10^6 operating cycles			
Cable entry		2 cable entries, with grommet			
Pressure switch type		Diaphragm			

(1) Component materials of units in contact with the fluid, see page 89.
(2) Variant: for a 2.8 to 7 bar, IP 20, pressure switch with R 1/4 (male) fluid entry, select the ***FYG29.***
(3) Variant: for a 5.6 to 10.5 bar, IP 20, pressure switch with R 1/4 (male) fluid entry, select the ***FYG39.***

Operating curves

FYG22



1 Maximum differential
2 Minimum differential

FYG32



1 Maximum differential
2 Minimum differential

Connections



— Adjustable value

Dimensions:
page 93

Electromechanical pressure switches
OsiSense XM
For power circuits, OsiSense FTG, FSG and FYG

Dimensions

FTG2, FSG2



FTG2NE, FSG2NE



FTG9, FSG9



FTG9NE, FSG9NE



FYG22, FYG32



FYG22NE, FYG32NE



Characteristics:
page 89

References:
pages 90 to 92

Electromechanical pressure switches
OsiSense XM
For power circuits, OsiSense XMP

Presentation

Pressure switches OsiSense XMP are switches for power circuits (direct switching), with an adjustable differential.
They are used to control the pressure of water and air, up to 25 bar.

Equipment fitted to the various models

Case

Pressure switches OsiSense XMP, depending on the model, include:

- 3 types of case:
  - bare case,
  - case with On/Off knob (black): used as a switch for starting and stopping the installation,
  - case with reset knob (yellow): necessary when the safety requirements of the system include tripping in the event of overpressure. Resetting is not automatic on return to normal pressure, and it can only be achieved by manually turning the "Reset" knob.

- 2 degrees of protection:
  - IP 54,
  - IP 65.

Decompression valve

Depending on the model, 2 types of decompression valve can be fitted to pressure switches OsiSense XMP:
- Straight, instant connection, decompression valve (connection by Ø 6 mm plastic tube).
- Straight, olive connection, decompression valve (connection by Ø 6 mm plastic or metal tube).



Setting

When setting XMP pressure switches, adjust the switching point on rising pressure (PH) first and then the switching point on falling pressure (PB).

Switching point on rising pressure
The switching point on rising pressure (PH) is set by adjusting the screw-nut or knurled knob 1.
Tighten either the nut or knurled knob 1 to increase the high point switching value.

Switching point on falling pressure
The switching point on falling pressure is set by adjusting screw-nut 2.
Tighten nut 2 to reduce the low point switching value (increase in differential).

References:
pages 96 to 103

Dimensions:
page 105

Electromechanical pressure switches
OsiSense XM
For power circuits, OsiSense XMP

Environment characteristics

Conformity to standards		CE, IEC/EN 60947-4-1
Product certifications		EAC
Ambient air temperature	**°C**	For operation: - 25...+ 70 For storage: - 40...+ 70
Fluids controlled		Air, fresh water, sea water (0…+ 70°C)
Materials		Case: polyamide impregnated with fibreglass Component materials in contact with fluid: chromated zinc alloy (fluid entry), canvas covered nitrile (diaphragm)
Operating position		All positions
Vibration resistance		3 gn (10…500 Hz) conforming to IEC 60068-2-6
Shock resistance		50 gn, conforming to IEC 60068-2-27
Electric shock protection		Class I conforming to IEC 60536
Degree of protection		IP 54 conforming to IEC/EN 60529 or IP 65 for universal model
Operating rate	**Op. cycles/h**	≤ 600
Repeat accuracy		< 3.5%
Fluid connection		G 1/4, 4 x G 1/4 or G 3/8 (BSP female) conforming to NF E 03-005, ISO 228
Electrical connection		2 tapped entries for n° 13 (DIN Pg 13.5) cable gland

Contact block characteristics

Rated insulation voltage	**V**	Ui = 500 conforming to IEC/EN 60947-1
Rated impulse withstand voltage	**V**	U imp = 6 kV conforming to IEC/EN 60947-1
Type of contacts		One 2-pole 2 NC or 3-pole 3 NC contact, snap action
Resistance across terminals	**mΩ**	≤ 25 conforming to NF C 93-050 method A or IEC 255-7 category 3
Terminal referencing		Conforming to CENELEC EN 50013
Short-circuit protection		Cartridge fuse type Am
Connection		Screw clamp terminals. Minimum clamping capacity: 2 x 4 mm^2

Electrical durability
Operating rate: 600 operating cycles/hour
Load factor: 0.4

Power	Number of operating cycles	
kW	∼ 400 V, 3-phase	∼ 230 V, 3-phase
1.5	1 000 000	600 000
2.2	700 000	–
3	500 000	–

References:
pages 96 to 103

Dimensions:
page 105

Electromechanical pressure switches

OsiSense XMP, IP 54
Size 6 bar (87 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 2-pole 2 NC or 3-pole 3 NC contact

Fluid connection	**G 1/4 (female)**	
	 1	 2
Adjustable range of switching point (PH) (Rising pressure)	**1…6 bar (14.5…87 psi)**	
Type of contact	2-pole 2 NC	3-pole 3 NC
References *(1)*		
Switches without decompression valve		
Bare case 1	**XMPA06B2131**	**XMPA06C2131**
Case with reset knob 2	**XMPB06B2131**	**–**
Case with On/Off knob 2	**XMPC06B2131**	**XMPC06C2131**
Weight (kg)	0.430	
Switches with straight decompression valve, instant connection		
Bare case 1	**XMPD06B2131**	**XMPD06C2131**
Case with On/Off knob 2	**XMPE06B2131**	**XMPE06C2131**
Weight (kg)	0.450	

Complementary characteristics not shown under general characteristics (page 95)		
Possible differential (subtract from PH to give PB)	Min. at low setting	0.8 bar (11.6 psi)
	Min. at high setting	1.2 bar (17.4 psi)
	Max. at high setting	4.2 bar (60.9 psi)
Destruction pressure		30 bar (435 psi)
Mechanical life		1 million operating cycles
Cable entry		2 entries tapped for n° 13 cable gland, conforming to NF C 68-300 (DIN Pg 13.5)
Pressure switch type		Diaphragm

*(1) References for individually packaged switches. Also available packaged in lots of 10. To order, add the letter **C** to the reference selected from above. Example: reference for lot of 10 pressure switches **XMPA06B2131** in one package becomes **XMPA06B2131C**.*

Operating curves



1 Maximum differential
2 Minimum differential

Accessories: page 104
Dimensions: page 105

4 x G 1/4 (female)	**G 3/8 (female)**	
 2	 1	 2
1…6 bar (14.5…87 psi)		
3-pole 3 NC	2-pole 2 NC	3-pole 3 NC
References		
Switches without decompression valve		
–	**XMPA06B2242**	**XMPA06C2242**
–	**XMPB06B2242**	**–**
–	**XMPC06B2242**	**XMPC06C2242**
–	0.430	
Switches with straight decompression valve, instant connection		
–	**XMPD06B2242**	**XMPD06C2242**
XMPE06C2431	**–**	**XMPE06C2242**
0.450		

Complementary characteristics not shown under general characteristics (page 95)		
0.8 bar (11.6 psi)		
1.2 bar (17.4 psi)		
4.2 bar (60.9 psi)		
30 bar (435 psi)		
1 million operating cycles		
2 entries tapped for n° 13 cable gland, conforming to NF C 68-300 (DIN Pg 13.5)	2 entries incorporating n° 13 plastic cable gland (DIN Pg 13.5) Clamping capacity 9 to 13 mm	
Diaphragm		
Other versions	Pressure switches not listed above, comprising the equipment proposed for the choice of reference. Please consult our Customer Care Centre.	

Terminal connections

XMP●●●B●●●●	**XMP●●●C●●●●**
	

Accessories: page 104
Dimensions: page 105

Electromechanical pressure switches

OsiSense XMP, IP 54
Size 12 bar (174 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 2-pole 2 NC or 3-pole 3 NC contact

Fluid connection	**G 1/4 (female)**	
	 1	 2
Adjustable range of switching point (PH) (Rising pressure)	**1.3…12 bar (18.85…174 psi)**	
Type of contact	2-pole 2 NC	3-pole 3 NC

References *(1)*

Switches without decompression valve		
Bare case 1	**XMPA12B2131**	**XMPA12C2131**
Case with reset knob 2	**XMPB12B2131**	**–**
Case with On/Off knob 2	**XMPC12B2131**	**XMPC12C2131**
Weight (kg)	0.430	
Switches with straight decompression valve, instant connection		
Bare case 1	**XMPD12B2131**	**XMPD12C2131**
Case with On/Off knob 2	**XMPE12B2131**	**XMPE12C2131**
Weight (kg)	0.450	
Switches with straight decompression valve, olive connection		
Case with On/Off knob 2	**XMPR12B2131**	**XMPR12C2131**
Weight (kg)	0.450	

Complementary characteristics not shown under general characteristics (page 95)

Possible differential (subtract from PH to give PB)	Min. at low setting	1 bar (14.5 psi)
	Min. at high setting	1.7 bar (24.6 psi)
	Max. at high setting	8.4 bar (121.8 psi)
Destruction pressure		30 bar (435 psi)
Mechanical life		1 million operating cycles
Cable entry		2 entries tapped for n° 13 cable gland, conforming to NF C 68-300 (DIN Pg 13.5)
Pressure switch type		Diaphragm

*(1) References for individually packaged switches. Also available packaged in lots of 10. To order, add the letter **C** to the reference selected from above. Example: reference for lot of 10 pressure switches **XMPA12B2131** in one package becomes **XMPA12B2131C**.*

Operating curves



1 Maximum differential
2 Minimum differential

Accessories: page 104
Dimensions: page 105

4 x G 1/4 (female)		**G 3/8 (female)**	
 2		 1	 2
1.3…12 bar (18.85…174 psi)			
2-pole 2 NC	3-pole 3 NC	2-pole 2 NC	3-pole 3 NC

References

Switches without decompression valve			
–		**XMPA12B2242**	**XMPA12C2242**
–		**XMPB12B2242**	**–**
XMPC12B2431	**–**	**XMPC12B2242**	**XMPC12C2242**
0.430			
Switches with straight decompression valve, instant connection			
–	**XMPD12C2431**	**XMPD12B2242**	**XMPD12C2242**
XMPE12B2431	**XMPE12C2431**	**XMPE12B2242**	**XMPE12C2242**
0.450			
Switches with straight decompression valve, olive connection			
–			
–			

Complementary characteristics not shown under general characteristics (page 95)

1 bar (14.5 psi)	
1.7 bar (24.6 psi)	
8.4 bar (121.8 psi)	
30 bar (435 psi)	
1 million operating cycles	
2 entries tapped for n° 13 cable gland, conforming to NF C 68-300 (DIN Pg 13.5)	2 entries incorporating n° 13 plastic cable gland (DIN Pg 13.5) Clamping capacity 9 to 13 mm
Diaphragm	
Other versions	Pressure switches not listed above, comprising the equipment proposed for the choice of reference. Please consult our Customer Care Centre.

Terminal connections

XMP●●●B●●●●	**XMP●●●C●●●●**
	

Accessories: page 104
Dimensions: page 105

Electromechanical pressure switches

OsiSense XMP, IP 54
Size 25 bar (362.5 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 2-pole 2 NC or 3-pole 3 NC contact

Fluid connection		**G 1/4 (female)**
		 1
		 2
Adjustable range of switching point (PH) (Rising pressure)		**3.5…25 bar (50.75…362.5 psi)**
Type of contact		2-pole 2 NC
References		
Switches without decompression valve		
Bare case 1		**XMPA25B2131**
Case with reset knob 2		**XMPB25B2131**
Case with On/Off knob 2		**XMPC25B2131**
Weight (kg)		0.650
Switches with straight decompression valve, olive connection		
Case with On/Off knob 2		**XMPR25B2131**
Weight (kg)		0.670
Complementary characteristics not shown under general characteristics (page 95)		
Possible differential (subtract from PH to give PB)	Min. at low setting	3.4 bar (49.3 psi)
	Min. at high setting	4.5 bar (65.2 psi)
	Max. at high setting	20 bar (290 psi)
Destruction pressure		100 bar (1450 psi)
Mechanical life		1 million operating cycles
Cable entry		2 entries tapped for n° 13 cable gland, conforming to NF C 68-300 (DIN Pg 13.5)
Pressure switch type		Diaphragm

Operating curves



1 Maximum differential
2 Minimum differential

Accessories: page 104
Dimensions: page 105

		G 1/4 (female)
		 1
		 2
		3.5…25 bar (50.75…362.5 psi)
		3-pole 3 NC
References		
Switches without decompression valve		
		XMPA25C2131
		–
		XMPC25C2131
		0.650
Switches with straight decompression valve, olive connection		
		XMPR25C2131
		0.670
Complementary characteristics not shown under general characteristics (page 95)		
		3.4 bar (49.3 psi)
		4.5 bar (65.2 psi)
		20 bar (290 psi)
		100 bar (1450 psi)
		1 million operating cycles
		2 entries tapped for n° 13 cable gland, conforming to NF C 68-300 (DIN Pg 13.5)
		Diaphragm
Other versions		Pressure switches not listed above, comprising the equipment proposed for the choice of reference. Please consult our Customer Care Centre.

Terminal connections

XMP●●●B●●●●



XMP●●●C●●●●



Accessories: page 104
Dimensions: page 105

Electromechanical pressure switches

OsiSense XMP, IP 65
Sizes 6 to 25 bar (87 to 362.5 psi)
Adjustable differential, for regulation between 2 thresholds
Switches with 2-pole 2 NC or 3-pole 3 NC contact

Fluid connection	**G 1/4 (female)**					
						
Adjustable range of switching point (PH) (Rising pressure)	**1…6 bar (14.5…87 psi)**		**1.3…12 bar (18.85…174 psi)**		**3.5…25 bar (50.75…362.5 psi)**	
Type of contact	2-pole 2 NC	3-pole 3 NC	2-pole 2 NC	3-pole 3 NC	2-pole 2 NC	3-pole 3 NC
References						
Switches with straight decompression valve, olive connection						
Case with On/Off knob	**XMPR06B2133**	**XMPR06C2133**	**XMPR12B2133**	**XMPR12C2133**	**XMPR25B2133**	**XMPR25C2133**
Weight (kg)	0.450				0.670	
Complementary characteristics not shown under general characteristics (page 95)						
Possible differential (subtract from PH to give PB) Min. at low setting	0.8 bar (11.6 psi)		1 bar (14.5 psi)		3.4 bar (49.3 psi)	
Min. at high setting	1.2 bar (17.4 psi)		1.7 bar (24.6 psi)		4.5 bar (65.2 psi)	
Max. at high setting	4.2 bar (60.9 psi)		8.4 bar (121.8 psi)		20 bar (290 psi)	
Destruction pressure	30 bar (435 psi)				100 bar (1450 psi)	
Mechanical life	1 million operating cycles					
Cable entry	2 entries tapped for n° 13 cable gland, conforming to NF C 68-300 (DIN Pg 13.5)					
Adjustment of high setting point (PH)	By screw-nut					
Pressure switch type	Diaphragm					

Operating curves

XMPR06●●●●●



1 Maximum differential
2 Minimum differential

XMPR12●●●●●



1 Maximum differential
2 Minimum differential

XMPR25●●●●●



1 Maximum differential
2 Minimum differential



Accessories: page 104
Dimensions: page 105

4 x G 1/4 (female)					
					
1…6 bar (14.5…87 psi)		**1.3…12 bar (18.85…174 psi)**		**3.5…25 bar (50.75…362.5 psi)**	
2-pole 2 NC	3-pole 3 NC	2-pole 2 NC	3-pole 3 NC	2-pole 2 NC	3-pole 3 NC
References					
Switches with straight decompression valve, olive connection					
XMPR06B2433	**XMPR06C2433**	**XMPR12B2433**	**XMPR12C2433**	**XMPR25B2433**	**XMPR25C2433**
0.450				0.670	
Complementary characteristics not shown under general characteristics (page 95)					
0.8 bar (11.6 psi)		1 bar (14.5 psi)		3.4 bar (49.3 psi)	
1.2 bar (17.4 psi)		1.7 bar (24.6 psi)		4.5 bar (65.2 psi)	
4.2 bar (60.9 psi)		8.4 bar (121.8 psi)		20 bar (290 psi)	
30 bar (435 psi)				100 bar (1450 psi)	
1 million operating cycles					
2 entries tapped for n° 13 cable gland, conforming to NF C 68-300 (DIN Pg 13.5)					
By screw-nut					
Diaphragm					

Other versions

Pressure switches not listed above, comprising the equipment proposed for the choice of reference. Please consult our Customer Care Centre.

Terminal connections

XMP●●●B●●●●



XMP●●●C●●●●



Accessories: page 104
Dimensions: page 105

Electromechanical pressure switches
OsiSense XM
For power circuits, OsiSense XMP
Accessories and replacement parts



XMAZL001



XMPMDR01



DE9PM1201



DE9PM1202



XMPZ3●

References

Description		Reference	Weight kg
Fixing bracket		**XMAZL001**	0.035
Knurled adjustment knob, Ø 36 mm fits over adjustment screws to facilitate setting		**XMPMDR01**	0.010
13P cable gland	With anti pull-out ring (for cable Ø 6…9 mm)	**DE9PM1201**	0.005
	Without anti pull-out ring (for cable Ø 6…9 mm)	**DE9PM1202**	0.005
	With anti pull-out ring (for cable Ø 9…12.5 mm)	**DE9PM1203**	0.005

Description	For pressure switch	Sold in lots of	Unit reference	Weight kg
Diaphragms	Size 6 bar	50	**XMPZ31**	0.005
	Size 25 bar	50	**XMPZ33**	0.005

Electromechanical pressure switches
OsiSense XM
For power circuits, OsiSense XMP
Accessories and replacement parts

Dimensions

XMP●06●●●●● and XMP●12●●●●●

Fluid connection G 1/4 or G 3/8 (female)
Without decompression valve





ØA = G 1/4 or G 3/8 (female)

Fluid connection 4 x G 1/4 (female)
Without decompression valve





ØA = ØB = ØC = ØD = G 1/4 (female)

With straight, instant connection, decompression valve



With straight, olive connection, decompression valve



(1) 2 tapped entries for n° 13 cable gland

(2) Minimum clearance zone for screwing-on pressure switch at point A

XMP●25●●●●●

Fluid connection G 1/4 or 4 x G 1/4 (female)
Without decompression valve





XMP●25●21●●: ØA only = G 1/4 (female)

XMP●25●24●●: ØA = ØB = ØC = ØD = G 1/4 (female)

With straight, olive connection, decompression valve



(1) 2 tapped entries for n° 13 cable gland

(2) Minimum clearance zone for screwing-on pressure switch at point A

Fixing bracket XMAZL001



Product reference index

A

ACW1M119012 76
ACW1M129012 76
ACW2M119012 77
ACW2M129012 77
ACW3M119012 76
ACW3M129012 76
ACW4M119012 76
ACW4M129012 76
ACW5M119012 76
ACW5M129012 76
ACW6M119012 77
ACW6M129012 77
ACW7M119012 77
ACW7M129012 77
ACW8M119012 77
ACW8M129012 77
ACW9M119012 77
ACW9M129012 77
ACW10M119012 77
ACW10M129012 77
ACW20M119012 77
ACW20M129012 77
ACW21M119012 76
ACW21M129012 76
ACW22M119012 77
ACW22M129012 77
ACW23M119012 76
ACW23M129012 76
ACW24M119012 76
ACW24M129012 76
ACW25M119012 76
ACW25M129012 76
ACW26M119012 77
ACW26M129012 77
ACW27M129012 77
ACW28M119012 77
ACW28M129012 77
ACW29M129012 77
ADW3M119012 78
ADW3M129012 78
ADW4M119012 78
ADW4M129012 78
ADW5M119012 79
ADW5M129012 79
ADW6M119012 79
ADW6M129012 79
ADW7M119012 78
ADW7M129012 78
ADW7S1M129012 79
ADW23M129012 78
ADW24M129012 78
ADW25M129012 79
ADW26M129012 79
ADW27M129012 78

D

DE9PM1201 86 104
DE9PM1202 86 104
DE9PM1203 86 104

F

FSG2 91
FSG2NE 91
FSG9 91
FSG9NE 91
FTG2 90
FTG2NE 90
FTG9 90
FTG9NE 90
FYG22 92
FYG22NE 92
FYG32 92
FYG32NE 92

X

XMAH06L2135 85
XMAH06L2435 85
XMAH12L2135 85
XMAH12L2435 85
XMAH25L2135 85
XMAH25L2435 85
XMAV06L2135 85
XMAV06L2435 85
XMAV12L2135 85
XMAV12L2435 85
XMAV25L2135 85
XMAV25L2435 85
XMAZL001 86 104
XMLA001R2C11 30
XMLA001R2S12 30
XMLA001S2C11 30
XMLA001S2S12 30
XMLA001S2S13 30
XMLA002A2C11 33
XMLA002A2S12 33
XMLA002A2S13 33
XMLA002B2C11 33
XMLA002B2S12 33
XMLA002C2C11 33
XMLA002C2S12 33
XMLA004A2C11 36
XMLA004A2S12 36
XMLA004A2S13 36
XMLA004B2C11 36
XMLA004B2S12 36
XMLA004C2C11 36
XMLA004C2S12 36
XMLA004P2C11 36
XMLA004P2S12 36
XMLA010A2C11 40
XMLA010A2S12 40
XMLA010A2S13 40
XMLA010B2C11 40
XMLA010B2S12 40
XMLA010C2C11 40
XMLA010C2S12 40
XMLA010C2S13 40
XMLA010P2C11 40
XMLA010P2S12 40
XMLA020A2C11 44
XMLA020A2S12 44
XMLA020A2S13 44
XMLA020B2C11 44
XMLA020B2S12 44
XMLA020C2C11 44
XMLA020C2S12 44
XMLA020P2C11 44
XMLA020P2S12 44
XMLA035A2C11 48
XMLA035A2S12 48
XMLA035A2S13 48
XMLA035B2C11 48
XMLA035B2S12 48
XMLA035C2C11 48
XMLA035C2S12 48
XMLA035P2C11 48
XMLA035P2S12 48
XMLA070D2C11 52
XMLA070D2S12 52
XMLA070D2S13 52
XMLA070E2C11 52
XMLA070E2S12 52
XMLA070E2S13 52
XMLA070N2C11 52
XMLA070N2S12 52
XMLA160D2C11 56
XMLA160D2S12 56
XMLA160D2S13 56
XMLA160E2C11 56
XMLA160E2S12 56
XMLA160E2S13 56
XMLA160N2C11 56
XMLA160N2S12 56
XMLA300D2C11 60
XMLA300D2S12 60
XMLA300D2S13 60
XMLA300E2C11 60
XMLA300E2S12 60
XMLA300E2S13 60
XMLA300N2C11 60
XMLA300N2S12 60
XMLA500D2C11 64
XMLA500D2S12 64
XMLA500D2S13 64
XMLA500E2C11 64
XMLA500E2S12 64
XMLA500E2S13 64
XMLA500N2C11 64
XMLA500N2S12 64
XMLAM01T2C11 18
XMLAM01T2S12 18
XMLAM01V2C11 18
XMLAM01V2S12 18
XMLAM01V2S13 18
XMLB001P2S12 31
XMLB001R2C11 31
XMLB001R2S12 31
XMLB001R2S13 31
XMLB001S2C11 31
XMLB001S2S12 31
XMLB001S2S13 31
XMLB002A2C11 34
XMLB002A2S12 34
XMLB002A2S13 34
XMLB002B2C11 34
XMLB002B2S12 34
XMLB002C2C11 34
XMLB002C2S12 34
XMLB004A2C11 37
XMLB004A2S12 37
XMLB004A2S13 37
XMLB004B2C11 37
XMLB004B2S12 37
XMLB004C2C11 37
XMLB004C2S12 37
XMLB010A2C11 41
XMLB010A2S12 41
XMLB010A2S13 41
XMLB010B2C11 41
XMLB010B2S12 41
XMLB010B2S13 41
XMLB010C2C11 41
XMLB010C2S12 41
XMLB010C2S13 41
XMLB010P2C11 41
XMLB010P2S12 41
XMLB020A2C11 45
XMLB020A2S12 45
XMLB020A2S13 45
XMLB020B2C11 45
XMLB020B2S12 45
XMLB020B2S13 45
XMLB020C2C11 45
XMLB020C2S12 45
XMLB020P2C11 45
XMLB020P2S12 45
XMLB035A2C11 49
XMLB035A2S12 49
XMLB035A2S13 49
XMLB035B2C11 49
XMLB035B2S12 49
XMLB035C2C11 49
XMLB035C2S12 49
XMLB035P2S12 49
XMLB070D2C11 53
XMLB070D2S12 53
XMLB070D2S13 53
XMLB070E2C11 53
XMLB070E2S12 53
XMLB070N2C11 53
XMLB070N2S12 53
XMLB160D2C11 57
XMLB160D2S12 57
XMLB160D2S13 57
XMLB160E2C11 57
XMLB160E2S12 57
XMLB160N2C11 57
XMLB160N2S12 57
XMLB300D2C11 61
XMLB300D2S12 61
XMLB300D2S13 61
XMLB300E2C11 61
XMLB300E2S12 61
XMLB300N2C11 61
XMLB300N2S12 61
XMLB500D2C11 65
XMLB500D2S12 65
XMLB500D2S13 65
XMLB500E2C11 65
XMLB500E2S12 65
XMLB500N2C11 65
XMLB500N2S12 65
XMLBL05R2S12 23
XMLBL05S2S12 23
XMLBL35P2C11 26
XMLBL35P2S12 26
XMLBL35R2C11 26
XMLBL35R2S12 26
XMLBL35R2S13 26
XMLBL35S2C11 26
XMLBL35S2S12 26
XMLBM02T2C11 19
XMLBM02T2S12 19
XMLBM02T2S13 19
XMLBM02V2C11 19
XMLBM02V2S12 19
XMLBM02V2S13 19
XMLBM03R2S12 22
XMLBM03R2S13 22
XMLBM05A2C11 24
XMLBM05A2S12 24
XMLBM05A2S13 24
XMLBM05B2C11 24
XMLBM05B2S12 24
XMLBM05C2C11 24
XMLBM05C2S12 24
XMLBM05P2C11 24
XMLBM05P2S12 24
XMLBS02B2S12 34
XMLBS04B2S12 37
XMLBS10A2S12 41
XMLBS20A2S12 45
XMLBS35R2S12 27
XMLC001R2S12 32
XMLC001R2S13 32
XMLC001S2S12 32
XMLC001S2S13 32
XMLC002B2S12 35
XMLC002B2S13 35
XMLC004B2S12 38
XMLC004B2S13 38
XMLC004C2S12 38
XMLC004C2S13 38
XMLC010B2S12 42
XMLC010B2S13 42
XMLC010C2S12 42
XMLC010C2S13 42
XMLC020B2S12 46
XMLC020B2S13 46
XMLC020C2S12 46
XMLC020C2S13 46
XMLC035B2S12 50
XMLC035B2S13 50
XMLC035C2S12 50
XMLC035C2S13 50
XMLC070D2S12 54
XMLC070D2S13 54
XMLC070E2S12 54
XMLC070N2S12 54
XMLC160D2S12 58
XMLC160D2S13 58
XMLC160E2S12 58
XMLC160N2S12 58
XMLC300D2S12 62

Product reference index

XMLC300E2S12 62
XMLC300N2S12 62
XMLC500D2S12 66
XMLC500N2S12 66
XMLCL35R2S12 28
XMLCL35S2S12 28
XMLCL35S2S13 28
XMLCM02T2S12 20
XMLCM02V2S12 20
XMLCM05B2S12 25
XMLCM05C2S12 25
XMLCS02B2S12 35
XMLCS02B2S13 35
XMLCS04B2S12 38
XMLCS10A2S12 42
XMLCS20A2S12 46
XMLCS35R2S12 28
XMLCS35R2S13 28
XMLD004B1S12 39
XMLD010B1S11 43
XMLD010B1S12 43
XMLD010C1S11 43
XMLD020B1S12 47
XMLD020B1S13 47
XMLD020C1S12 47
XMLD035B1S12 51
XMLD070D1S12 55
XMLD070D1S13 55
XMLD070N1S12 55
XMLD160D1S12 59
XMLD160D1S13 59
XMLD160E1S12 59
XMLD300D1S12 63
XMLD300D1S13 63
XMLD300E1S12 63
XMLD300N1S12 63
XMLD500D1S12 67
XMLDL35R1S12 29
XMLDM02T1S12 21
XMLDM02V1S12 21
XMLZA024 68
XMLZA120 68
XMLZB024 68
XMLZB120 68
XMLZL001 68
XMLZL002 68
XMLZL003 68 86
XMLZL004 68
XMLZL005 68
XMLZL006 68
XMLZL010 68
XMLZL011 68
XMLZL012 68
XMLZL013 68
XMLZL014 68
XMLZL015 68
XMLZZ024 68
XMLZZ120 68
XMPA06B2131 96
XMPA06B2242 97
XMPA06C2131 96
XMPA06C2242 97
XMPA12B2131 98
XMPA12B2242 99
XMPA12C2131 98
XMPA12C2242 99
XMPA25B2131 100
XMPA25C2131 101
XMPB06B2131 96
XMPB06B2242 97
XMPB12B2131 98
XMPB12B2242 99
XMPB25B2131 100
XMPC06B2131 96
XMPC06B2242 97
XMPC06C2131 96
XMPC06C2242 97
XMPC12B2131 98
XMPC12B2242 99
XMPC12B2431 99
XMPC12C2131 98
XMPC12C2242 99
XMPC25B2131 100
XMPC25C2131 101
XMPD06B2131 96
XMPD06B2242 97
XMPD06C2131 96
XMPD06C2242 97
XMPD12B2131 98
XMPD12B2242 99
XMPD12C2131 98
XMPD12C2242 99
XMPD12C2431 99
XMPE06B2131 96
XMPE06C2131 96
XMPE06C2242 97
XMPE06C2431 97
XMPE12B2131 98
XMPE12B2242 99
XMPE12B2431 99
XMPE12C2131 98
XMPE12C2242 99
XMPE12C2431 99
XMPMDR01 104
XMPR06B2133 102
XMPR06B2433 103
XMPR06C2133 102
XMPR06C2433 103
XMPR12B2131 98
XMPR12B2133 102
XMPR12B2433 103
XMPR12C2131 98
XMPR12C2133 102
XMPR12C2433 103
XMPR25B2131 100
XMPR25B2133 102
XMPR25B2433 103
XMPR25C2131 101
XMPR25C2133 102
XMPR25C2433 103
XMPZ31 86 104
XMPZ33 86 104
XMXA06L2135 84
XMXA06L2435 84
XMXA12L2135 84
XMXA12L2435 84
XMXA25L2135 84
XMXA25L2435 84
XZCC43FCP40B 68

Schneider Electric Industries SAS

Head Office
35, rue Joseph Monier
F-92500 Rueil-Malmaison
France

www.tesensors.com

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Design: Schneider Electric
Photos: Schneider Electric

DIA4ED2150201EN

June 2016 - V2.0