www.flex-tools.com

this is proformance FLEX

CHE 4-32 R SDS-plus

Universal rotary hammer drill, 4 kg, SDS-plus

Order no. 468029

GTIN 4030293209527



- 900 watt hammer drill and chisel hammer in D-build with high impact energy and low vibrations
- Drilling chuck can be removed without tools
- Rotation stop for chiselling
- Max. drilling range up to 32 mm
- For light-duty chiselling work when removing plaster and tiles
- Quick tool change: universal application, with SDS Plus drill chuck or 13 mm quick-release chuck
- Function switch with four functions: drilling, hammer drilling, chiselling, chisel adjustment
- Accelerator switch for a slow and gentle start
- Non-rotating additional handle with depth stop





Technical data

Power consumption	900 W
Voltage	230 V
Frequency	50/60Hz Hz
Tool holder, drill and chisel	SDS-plus
Max. single impact energy	4.8 J
No-load speed	0 - 850 rpm
No-load blows	0 - 3700 bpm
Chuck clamping width	1,5 - 13 mm
Max. drilling diameter in concrete	32 mm
Max. drilling diameter in masonry (drill bit)	82 mm
Max. drilling diameter in wood	32 mm
Max. drilling diameter in steel	13 mm
Cable length	4.0 m
Dimensions WxLxH	400 x 86 x 235 mm
Weight	4.6 kg

Standard equipment

1 Chuck (468878)
1 Chuck (468851)
1 Handle (436232)
1 Depth stop (417769)
1 Carrying case L-BOXX® (414093)
1 Case insert (469041)