
PERFORMANCE MADE SMARTER



Repeater / power supply

5104A


– 1- or 2-channel version
– 3- / 5-port 3.75 kVAC galvanic isolation
– Loop supply > 17.1 V
– 20 programmable measurement ranges
– Universal supply by AC or DC

Application
- Power supply and signal isolator for 2-wire transmitters.
- Signal isolator for analog current / voltage signals.
- 1 : 1 or signal conversion of analog current / voltage signals.

Technical characteristics
- The 20 factory-calibrated measurement ranges in the 5104A can be selected by the internal DIP-switches without the need for recalibration. Special measurement ranges can be delivered.
- PR5104A is based on microprocessor technology for gain and offset. The analog signal is transmitted at a response time of less than 25 ms.
- Inputs, outputs, and supply are floating and galvanically separated.
- The output can be connected either as an active current / voltage transmitter or as a 2-wire transmitter.

Mounting / installation
- Mounted vertically or horizontally on a DIN rail. By way of the 2-channel version up to 84 channels per meter can be mounted.

Applications



This page is automatically generated on the basis of information provided on www.prelectronics.com and affiliated websites. It is provided to you as a service and for information purpose only. While we have attempted to maintain the information as accurately as possible, the page may contain errors or omissions for which we disclaim any and all liability

Order:

Type	Input		Output		Channels	
5104A	0...20 mA	: A	Special	: 0	Single	: A
	4...20 mA	: B	0...20 mA	: 1	Double	: B
	0...10 V	: E	4...20 mA	: 2		
	2...10 V	: F	0...1 V	: 4		
	Special	: X	0.2...1 V	: 5		
			0...10 V	: 6		
			2...10 V	: 7		

Environmental Conditions

Operating temperature..... -20°C to +60°C
Calibration temperature..... 20...28°C
Relative humidity..... < 95% RH (non-cond.)
Protection degree..... IP20

Mechanical specifications

Dimensions (HxWxD)..... 109 x 23.5 x 130 mm
Weight approx..... 225 g
DIN rail type..... DIN 46277
Wire size..... 1 x 2.5 mm^2 stranded wire
Screw terminal torque..... 0.5 Nm

Common specifications

Supply

Supply voltage, universal..... 21.6...253 VAC, 50...60 Hz or 19.2...300 VDC
Fuse..... 400 mA SB / 250 VAC
Max. required power..... ≤ 3 W (2 channels)
Internal power dissipation..... ≤ 2 W (2 channels)

Isolation voltage

Isolation voltage, test / working..... 3.75 kVAC / 250 VAC
PELV/SELV..... IEC 61140

Response time

Response time (0...90%, 100...10%)..... < 25 ms

Auxiliary supplies

2-wire supply (pin 44...42 and 54...52)..... 28...17.1 VDC / 0...20 mA

Signal / noise ratio..... Min. 60 dB (0...100 kHz)
EMC immunity influence..... < ±0.5% of span
Extended EMC immunity: NAMUR NE21, A criterion, burst..... < ±1% of span

Input specifications

Common input specifications

Max. offset..... 20% of max. value

Current input

Measurement range..... 0...20 mA
Min. measurement range (span)..... 16 mA
Input resistance..... Nom. 10 Ω + PTC 10 Ω

Voltage input

Measurement range..... 0...10 VDC
Min. measurement range (span)..... 8 VDC
Input resistance..... > 2 MΩ

Output specifications

Current output

Signal range..... 0...20 mA
Min. signal range..... 16 mA
Load (@ current output)..... ≤ 600 Ω
Load stability..... ≤ 0.01% of span / 100 Ω
Current limit..... ≤ 28 mA

Passive 2-wire mA output

Max. external 2-wire supply..... 29 VDC
Effect of external 2-wire supply voltage variation..... < 0.005% of span / V

Voltage output

Signal range..... 0...1 VDC / 0...10 VDC
Min. signal range..... 0.8 VDC / 8 VDC
Load (@ voltage output)..... ≥ 500 kΩ

of span..... = of the presently selected range

Observed authority requirements

EMC..... 2014/30/EU
LVD..... 2014/35/EU
EAC..... TR-CU 020/2011

Approvals

UL..... UL 508 / C22.2 no. 14
DNV-GL Marine..... Stand. f. Certific. No. 2.4